



Pronar Wheels Catalogue



Index

<u>Wheels 15.3"</u>	3
<u>Wheels 15.5"</u>	5
<u>Wheels 16"</u>	6
<u>Wheels 16.5"</u>	9
<u>Wheels 17"</u>	10
<u>Wheels 18"</u>	12
<u>Wheels 20"</u>	14
<u>Wheels 22.5"</u>	17
<u>Wheels 24"</u>	25
<u>Wheels 26"</u>	31
<u>Wheels 26.5"</u>	33
<u>Wheels 28"</u>	35
<u>Wheels 30"</u>	38
<u>Wheels 30.5"</u>	40
<u>Wheels 32"</u>	41
<u>Wheels 34"</u>	44
<u>Wheels 36"</u>	47
<u>Wheels 38"</u>	49
<u>Wheels 42"</u>	54
<u>Wheels 44"</u>	56
<u>Wheels 46"</u>	57
<u>Wheels 48"</u>	58
<u>Wheels 54"</u>	59



Wheels 15.3"

Wheel Size	Nb of bolt holes	Central hole diameter	PCD	Bolt hole diameter	Offset	Material thickness	Type of wheel*	Load capacity at 40 km/h	Pronar part no
9,00x15,3	6	161	205	21,5/27	ET 0	3,5 / 6	welded	1632	153.09.01
9,00x15,3	6	161	205	21,5/27	ET -30	3,5 / 6	welded	1632	153.09.04
9,00x15,3	5	110	114	15	ET 0	3,5 / 6	welded	1632	153.09.06
9,00x15,3	6	117,8	152,4	18/23,5	ET +12	4,0 / 8	welded	1907	153.09.07
9,00x15,3	6	161	205	21,5/27	ET 0	4,0 / 8	welded	1907	153.09.08
9,00x15,3	6	161	205	21,5/27	ET 0	4,5 / 10	welded	3059	153.09.09
9,00x15,3	6	161	205	21,5/27	ET +45	4,0 / 8	welded	?	153.09.11
9,00x15,3	5	127	165,1	18/23	ET 0	4,0 / 8	welded	1907	153.09.12
9,00x15,3	5	135	175	20,5/26	ET 0	3,5 / 6	welded	?	153.09.15
9,00x15,3	5	152,4	203,2	21,5/27	ET 0	4,0 / 8	welded	?	153.09.22
9,00x15,3	6	161	205	21,5/27	ET 0	3,5 / 6	welded	1734	153.09.26
9,00x15,3	6	161	205	21,5/27	ET 0	4,0 / 8	welded	1907	153.09.27
9,00x15,3	6	161	205	21,5/27	ET 0	4,5 / 10	welded	3059	153.09.28
9,00x15,3	6	161	205	21,5/27	ET -30	4,5 / 8	welded	2243	153.09.29
9,00x15,3	5	157	205	18,5/24	ET 0	3,5 / 6	welded	2060	153.09.31
9,00x15,3	5	95	140	18/23,5	ET 0	3,5 / 6	welded	1632	153.09.33
9,00x15,3	5	110	160	18/23,5	ET 0	3,5 / 6	welded	1632	153.09.34
9,00x15,3	6	161	205	21,5/27	ET -40	4,0 / 8	welded	?	153.09.36
9,00x15,3	6	161	205	21,5/27	ET 0	4,5 / 8	welded	1907	153.09.44
9,00x15,3	6	161	205	21,5/27	ET -40	3,5 / 6	welded	1632	153.09.48
9,00x15,3	6	161	205	21,5/27	ET +25	4,0 / 8	welded	2651	153.09.52
9,00x15,3	5	110	160	18/23,5	ET +8	3,5 / 6	welded	?	153.09.57
9,00x15,3	6	161	205	21,5/27	ET +25	4,0 / 8	welded	?	153.09.58
9,00x15,3	6	161	205	21,5/27	ET -43	4,0 / 8	welded	1907	153.09.59
9,00x15,3	6	161	205	21,5/27	ET 0	4,0 / 6	welded	2651	153.09.60
9,00x15,3	6	161	205	21,5/27	ET +80	4,0 / 8	welded	1907	153.09.63
9,00x15,3	5	94	140	14,5/21	ET -30	4,0 / 8	welded	1907	153.09.64
9,00x15,3	6	161	205	21,5/27	ET 0	4,5 / 8	welded	3059	153.09.66
9,00x15,3	6	161	205	21,5/27	ET -35	3,5 / 6	welded	1632	153.09.67
9,00x15,3	6	161	205	21,5/27	ET 0	3,5 / 4,5	welded	1907	153.09.68
9,00x15,3	5	93	140	17	ET 0	3,5 / 6	welded	1632	153.09.69
9,00x15,3	6	161	205	21,5/27	ET 0	3,5 / 4,5	welded	1907	153.09.70
9,00x15,3	6	100,5	140	18,5/24	ET 0	4,0 / 6	welded	1978	153.09.71
9,00x15,3	8	152,4	215?	18/23,5	ET 0	4,5 / 8	welded	?	153.09.72
9,00x15,3	8	200	240	18/23,5	ET 0	4,5 / 8	welded	?	153.09.73
9,00x15,3	6	161	205	21,5/27	ET 0	4,0 / 8	welded	2549	153.09.74
9,00x15,3	6	117,8	152,4	15/20	ET -20	4,0 / 8	welded	?	153.09.75
9,00x15,3	5	110	160	18/23,5	ET -25	3,5 / 6	welded	?	153.09.76
9,00x15,3	6	100,5	140	18,5/24	ET 0	4,0 / 8	welded	?	153.09.77
9,00x15,3	5	127	165,1	18/23	ET 0	3,5 / 6	welded	?	153.09.78
9,00x15,3	6	161	205	21,5/27	ET +40	3,5 / 6	welded	1632	153.09.79
9,00x15,3	5	101,5	140	18/23,5	ET 0	4,0 / 8	welded	2651	153.09.80
9,00x15,3	6	161	205	21,5/27	ET -20	4,5 / 10	welded	3059	153.09.81
9,00x15,3	6	161	205	21,5/27	ET -25	4,5 / 10	welded	3059	153.09.82
9,00x15,3	6	161	205	21,5/27	ET -30	3,5 / 6	welded	1632	153.09.83



Wheels Catalogue

Wheel Size	Nb of bolt holes	Central hole diameter	PCD	Bolt hole diameter	Offset	Material thickness	Type of wheel*	Load capacity at 40 km/h	Pronar part no
9,00x15,3	6	141	190	21,5/27	ET 0	4,0 / 8	welded	?	153.09.84
9,00x15,3	6	141	190	21,5/27	ET -12	3,5 / 6	welded	?	153.09.85
9,00x15,3	6	100,5	140	18,5/24	ET -90	4,0 / 8	welded	?	153.09.86
9,00x15,3	5	161	205	21,5/27	ET -15	4,0 / 8	welded	?	153.09.87
9,00x15,3	5	141	190	21,5/27	ET 0	4,0 / 8	welded	?	153.09.88
9,00x15,3	6	161	205	21,5/27	ET -12	4,5 / 10	welded	3059	153.09.89
9,00x15,3	6	161	205	18,5/24	ET 0	4,0 / 8	welded	?	153.09.90
9,00x15,3	8	125	180	21,5/27	ET 0	4,0 / 8	welded	?	153.09.91
9,00x15,3	6	100,5	140	18,5/24	ET -60	4,0 / 8	welded	?	153.09.92
9,00x15,3	6	161	205	21,5/27	ET -17	4,0 / 8	welded	2651	153.09.93
9,00x15,3	6	130	170	21,5/27	ET +35	4,0 / 8	welded	1632	153.09.94
9,00x15,3	6	161	205	21,5/27	ET +52	3,5 / 6	welded	1632	153.09.95
9,00x15,3	6	161	205	21,5/27	ET -40	3,5 / 4,5	welded	1907	153.09.96
9,00x15,3	5	156	205	18/23,5	ET 0	4,0 / 8	welded	2549	153.09.97
9,00x15,3	5	95	140	18/23,5	ET +12	3,5 / 6	welded	1632	153.09.98
9,00x15,3	6	161	205	21,5/27	ET +19	3,5 / 4,5	welded	1907	153.09.99
9,00x15,3	5	95	140	18/23,5	ET +50	3,5 / 6	welded	1632	153.09.100
9,00x15,3	5	66,5	112	18,5/23,5	ET +40	3,5 / 6	welded	1632	153.09.101
9,00x15,3	5	110	160	18/23,5	ET -50	4,0 / 8	welded	2651	153.09.102
9,00x15,3	5	117,5	178	21,5/27	ET -50	4,0 / 8	welded	2651	153.09.103
9,00x15,3	5	110	160	17	ET 0	3,5 / 6	welded	1632	153.09.104
9,00x15,3	6	117,8	152,4	18/23,5	ET -20	4,0 / 8	welded	1907	153.09.105
9,00x15,3	6	163	222,3	32/38	ET 0	4,0 / 10	welded	?	153.09.106
9,00x15,3	6	161	205	21,5/27	ET 0	3,5 / 6	welded	1907	153.09.107
9,00x15,3	6	161,8	205	21,5/27	ET +19	3,5 / 6	welded	1907	153.09.108
9,00x15,3	6	161	205	21,5/27	ET -12	3,5 / 4,5	welded	1907	153.09.109
9,00x15,3	5	127	165,1	18/23	ET -17	4,0 / 8	welded	1907	153.09.110
9,00x15,3	6	161	205	21,5/27	ET -5	3,5 / 4,5	welded	1907	153.09.111
9,00x15,3	6	101	162	20	ET +50	4,5 / 8	welded	?	153.09.112



Wheels 15.5"

Wheel Size	Nb of bolt holes	Central hole diameter	PCD	Bolt hole diameter	Offset	Material thickness	Type of wheel*	Load capacity at 40 km/h	Pronar part no
13,00x15,5	6	161	205	21,5/27	ET -15	5,0 / 10	welded	3253	155.13.01
13,00x15,5	6	161	205	21,5/27	ET -15	5,0 / 10	welded	3253	155.13.01A
13,00x15,5	6	161	205	21,5/27	ET -15	4,5 / 8	welded	2509	155.13.02
13,00x15,5	6	161	205	21,5/27	ET 0	5,0 / 10	welded	3253	155.13.06
13,00x15,5	6	161	205	21,5/27	ET 0	5,0 / 10	welded	3253	155.13.06A
13,00x15,5	6	161	205	21,5/27	ET -15	5,0 / 10	welded	3253	155.13.07
13,00x15,5	6	161	205	21,5/27	ET -15	5,0 / 10	welded	3253	155.13.09
13,00x15,5	6	161	205	21,5/27	ET -30	5,0 / 10	welded	?	155.13.11
13,00x15,5	6	161	205	21,5/27	ET -47,5	4,5 / 8	welded	2509	155.13.14
13,00x15,5	6	161	205	21,5/27	ET -70	4,5 / 8	welded		155.13.15
13,00x15,5	6	161	205	21,5/27	ET -15	5,0 / 10	welded	3304	155.13.16
13,00x15,5	6	161	205	21,5/27	ET 0	4,5 / 8	welded	2509	155.13.18
13,00x15,5	6	161	205	21,5/27	ET 0	4,5 / 8	welded	2509	155.13.18A
13,00x15,5	6	161	205	21,5/27	ET -15	4,5 / 8	welded	3059	155.13.20
13,00x15,5	6	161	205	21,5/27	ET -70	4,5 / 8	welded	2509	155.13.21
13,00x15,5	6	161	205	21,5/27	ET 0	5,0 / 10	welded	3304	155.13.22
13,00x15,5	6	161	205	21,5/27	ET -15	5,0 / 10	welded	?	155.13.23
13,00x15,5	5	94	140	18/23,5	ET 0	4,5 / 8	welded	2509	155.13.24
13,00x15,5	6	161	205	21,5/27	ET 0	5,0 / 10	welded	3304	155.13.25
13,00x15,5	6	161	205	21,5/27	ET -15	4,5 / 6	welded	2900	155.13.26
13,00x15,5	6	161	205	21,5/27	ET -50	5,0 / 10	welded	2509	155.13.27
13,00x15,5	6	161	205	21,5/27	ET -60	4,5 / 8	welded	2509	155.13.28
13,00x15,5	6	161	205	21,5/27	ET -60	5,0 / 10	welded	3050	155.13.29
13,00x15,5	6	161	205	21,5/27	ET -15	5,5 / 10	welded	3500	155.13.30
13,00x15,5	6	161	205	21,5/?	ET -15	4,5 / 6	welded	2900	155.13.31
13,00x15,5H2	6	161	205	21,5/27	ET -15	5,0 / 10	welded	3253	155.13.50
13,00x15,5H2	6	161	205	21,5/27	ET -45	4,5 / 8	welded	2509	155.13.51
13,00x15,5H2	6	161	205	21,5/27	ET -15	4,5 / 8	welded	2509	155.13.52
13,00x15,5H2	6	161	205	21,5/27	ET -15	5,0 / 10	welded	3304	155.13.53
13,00x15,5H2	6	161	205	21,5/27	ET 0	4,5 / 8	welded	2906	155.13.55
13,00x15,5H2	6	102	162	18/25	ET -47,5	4,5 / 8	welded	2906	155.13.56
13,00x15,5H2	6	117,8	152,4	18	ET -65	4,5 / 8	welded	2906	155.13.57
13,00x15,5H2	6	161	205	21,5/27	ET -15	4,5 / 8	welded	3059	155.13.58
13,00x15,5H2	6	161	205	21,5/27	ET -15	4,5 / 8	welded	2509	155.13.61
13,00x15,5H2	6	161	205	21,5/?	ET -15	4,5 / 6	welded	2900	155.13.62
13,00x15,5H2	6	161	205	21,5/?	ET -40	4,5 / 6	welded	2900	155.13.63
13,00x15,5H2	6	161	205	21,5/?	ET -15	4,5 / 6	welded	2900	155.13.64



Wheels 16"

Wheel Size	Nb of bolt holes	Central hole diameter	PCD	Bolt hole diameter	Offset	Material thickness	Type of wheel*	Load capacity at 40 km/h	Pronar part no
4,00Ex16	4	85	130	18/23,5	ET +25	3,5 / 5	welded	418	16.40.03
4,50Ex16	5	135	175	20/25	ET -32	3,0 / 6	welded	489	16.45.01
4,50Ex16	5	95	140	18/23,5	ET +45	3,0 / 5	welded	489	16.45.02
4,50Ex16	6	117,8	152,4	18/23,5	ET +46	3,0 / 6	welded	489	16.45.04
4,50Ex16	5	66,6	112	18/23,5	ET +40	3,0 / 6	welded	?	16.45.06
4,50Ex16	6	117,7	152,4	18/23,5	ET +45	3,0 / 6	welded	?	16.45.07
4,50Ex16	6	117,7	152,4	18/23,5	ET +15	4,0 / 8	welded	602	16.45.08
4,50Ex16	6	117,8	152,4	14,2/18,2	?	3,5 / 6	welded	500	16.45.11
4,50Ex16	5	101,7	139,7	16	?	3,5 / 8	lugs	449	16.45.12
4,50Ex16	5	95	140	21,5	ET 0	3,5 / 6	welded	500	16.45.14
4,50Ex16	5	95	140	18/23,5	ET +45	4,0 / 8	welded	561	16.45.15
4,50Ex16	5	95	140	18/23,5	ET 0	4,0 / 8	welded	877	16.45.16
4,50Ex16	6	117,4	152,4	18/23,5	ET +45	3,0 / 4,5	welded	?	16.45.18
4,50Ex16	6	117,7	152,4	18/23,5	ET +45	3,0 / 5,0	welded	367	16.45.19
4,50Ex16	5	103	140	18/23,5	ET 0	4,0 / 6	welded	704	16.45.20
4,50Ex16	5	95	140	18/23,5	ET 0	4,0 / 8	welded	877	16.45.21
4,50Ex16	5	110	153	14,5/21	ET +20	4,0 / 8	welded	877	16.45.22
4,50Ex16	5	101,7	139,7	16/19	ET 0	3,0 / 6	welded	?	16.45.23
4,50Ex16	5	95	140	21,5/27	ET 0	3,5 / 6	welded	500	16.45.24
4,50Ex16						3,5	lugs		16.45.35
5,00Fx16	5	101,7	139,7	16/19	ET -1	3,5 / 6	welded	489	16.50.01
5,00Fx16	5	95	140	18/23,5	ET 0	3,5 / 6	welded	489	16.50.04
5,00Fx16	5	95	140	18/23,5	ET -15	3,5 / 6	welded	489	16.50.05
5,50Fx16	6	117,7	152,4	18/23,5	ET +36	3,5 / 8	welded	?	16.55.06
5,50Fx16	5	101,7	139,7	16	?	4,0 / 8	lugs	489	16.55.08
5,50Fx16	6	161	205	21,5/27	ET 0	3,5 / 8	welded	489	16.55.10
5,50Fx16	6	117,7	152,4	18/23,5	ET +28,6	4,0 / 8	welded	602	16.55.11
5,50Fx16	6	117,7	152,4	18/23,5	ET +29	3,5 / 8	welded	500	16.55.16
5,50Fx16	5	101,7	139,7	16/19	ET 0	3,5 / 6	welded	500	16.55.23
5,50Fx16	5	161	205	21,5/27	ET 0	3,5 / 8	welded	489	16.55.28
5,50Fx16	5	80	115	16/19	ET 0	3,5 / 6	welded	?	16.55.30
5,50Fx16	6	161	205	21,5	ET +3	3,5 / 8	welded	489	16.55.31
5,50Fx16	5	95	140	18/23,5	ET 0	3,5 / 6	welded	?	16.55.32
5,50Fx16	5	95	140	15,5	ET 0	4,0 / 8	welded	?	16.55.33
5,50Fx16	6	80	120	20	ET +45	4,0 / 8	welded	?	16.55.34
5,50Fx16	3+3	-	-	17 18,5/24	ET 0	3,5 / 12	crown	?	16.55.35
5,50Fx16	6	161	205	21,5/27	ET +47	3,5 / 8	welded	?	16.55.36
5,50Fx16	6	160	205	19	ET 4	4,0 / 8	welded	?	16.55.37
5,50Fx16	-	-	-	-	ET +30,5	4,0	lugs	?	16.55.38
5,50Fx16	6	135	170	17	ET +44	4,0 / 8	welded	?	16.55.39
5,50Fx16	-	-	-	-	-	4,0	lugs	?	16.55.40
5,50Fx16	6	117,8	152,4	18	ET +66	4,0 / 8	lugs	489	16.55.41
5,50Fx16	5	95	135	19	ET 0	3,5 / 6	welded	?	16.55.43
5,50Fx16	6	161	205	21,5/27	ET 0	4,5 / 8	welded	600	16.55.44



Wheels Catalogue

Wheel Size	Nb of bolt holes	Central hole diameter	PCD	Bolt hole diameter	Offset	Material thickness	Type of wheel*	Load capacity at 40 km/h	Pronar part no
5,50Fx16	6	117	152,4	18	ET +55	3,5 / 6	welded	?	16.55.45
5,50Fx16	8	221	275	19	ET 4	4,0 / 8	welded	?	16.55.46
6,00Lx16	5	111	139,7	16,5/18,6	ET 0	4,5 / 8	welded	1122	16.60.01
6,00Lx16	6	117,7	152,4	18/23,5	ET +36	4,0 / 8	welded	1254	16.60.03
6,00Lx16	8	145	190	20/27	?	4,5 / 8	welded	1652	16.60.11
6,00Lx16	8	145	190	20/27	ET -4,5	4,5 / 8	welded	1652	16.60.13
6,00Lx16	6	250	285	17	ET -40	4,5 / 6	welded	602	16.60.14
6,00Lx16	6	161	205	19	ET -40	4,5 / 6	welded	?	16.60.15
6,00Lx16	8	221	275	19	ET -40	4,5 / 6	welded	?	16.60.16
6,00Lx16	6	153	220	17	ET +35	4,5 / 8	welded	1254	16.60.18
W6x16	6	117,8	152,4	18	?	4,5 / 8	lugs	?	16.60.17
W7x16	5	135	175	20/25	ET +29	3,5 / 6	welded	1652	16.70.02
W7x16	6	161	205	21,5/27	ET 0	3,5 / 6	welded	1897	16.70.06
W7x16	8	152,6	203,2	17	ET -15	4,0 / 8	welded	?	16.70.08
W7x16	6	161	205	21,5/27	ET 0	3,5 / 6	welded	?	16.70.09
W8x16	6	117,7	152,4	18/23,5	ET +28,6	4,0 / 8	welded	2651	16.80.02
W8x16	5	101,7	139,7	16	ET +73	5,0 / 8	lugs	1152	16.80.05
W8x16	6	161	205	21,5/27	ET 0	3,5 / 6	welded	1897	16.80.06
W8x16	5	101,7	139,7	16	ET -7	5,0 / 8	lugs	1152	16.80.08
W8x16	8	153	203,2	17	?	4,0 / 8	lugs	?	16.80.13
W8x16	6	117,8	152,4	18	?	5,0 / 8	lugs	?	16.80.15
W8x16	6	90	120	14	ET +37	5,0 / 8	lugs	?	16.80.16
W8x16	6	117,7	152,4	18/23,5	ET -25	4,0 / 8	welded	?	16.80.17
W8x16	6	117,8	152,4	18	ET +10	4,0 / 6	welded	?	16.80.18
W8x16	6	161	205	21,5/27	ET -25	4,0 / 8	welded	?	16.80.19
W8x16	6	102	162	18/25	ET +15	3,5 / 6	welded	1897	16.80.20
W8x16	6	117,8	152,4	16	ET +35	3,5 / 6	welded	?	16.80.21
W8x16	6	117,8	152,4	18	?	5,0 / 8	lugs	?	16.80.22
W8x16	6	90	120	14	ET -30	5,0 / 8	lugs	?	16.80.23
W8x16	6	117,8	152,4	18	ET -30	5,0 / 8	lugs	?	16.80.24
W8x16	5	101,7	139,7	16	ET +27	5,0 / 8	lugs	?	16.80.25
W8x16	6	90	150	15	ET +30	4,0 / 6	welded	?	16.80.26
W8x16	5	94	140	18,5/23,5	ET +150	5,0 / 12	welded	?	16.80.27
W8x16	6	117,8	152,4	18	ET +10	5,0 / 8	lugs	?	16.80.28
W8x16	6	117,7	152,4	18	ET +28,6	4,0 / 8	welded	?	16.80.29
W8x16	5	135	175	20/25	ET +40	4,0 / 6	welded	?	16.80.30
W8x16	6	117,7	152,4	18,5/23,5	ET +28,6	4,0 / 8	welded	2651	16.80.31
W8x16	5	111	150	15	ET -8	4,0 / 8	welded	?	16.80.32
W8x16	6	160	205	21,5/27	ET 0	4,0 / 12	welded	?	16.80.33
W8x16	8	200	240	21	ET 0	4,0 / 12	welded	?	16.80.34
W8x16	6	117,7	152,4	18,5/23,5	ET 0	4,0 / 8	welded	2651	16.80.35
W8x16	6	117,8	152,4	18	ET -20	5,0 / 8	lugs	?	16.80.36
W8x16	6	117,8	152,4	17	ET +50	3,5 / 6	welded	?	16.80.37
W8x16	6	177,7	152,4	18	ET +40	5,0 / 8	welded	2750	16.80.38
W8x16	8	153	203,2	17	ET +15	5,0 / 8	lugs	?	16.80.39
W8x16	6	117,8	152,4	15	ET -20	5,0 / 8	lugs	?	16.80.40
9,00x16	6	161	205	21,5/27	ET 0	4,0 / 8	welded	1907	16.90.03
9,00x16	6	117,8	152,4	18/21,5	ET -20	4,0 / 8	welded	1907	16.90.07



Wheels Catalogue

Wheel Size	Nb of bolt holes	Central hole diameter	PCD	Bolt hole diameter	Offset	Material thickness	Type of wheel*	Load capacity at 40 km/h	Pronar part no
9,00x16	6	161	205	21,5/27	ET 0	4,0 / 8	welded	1907	16.90.08
9,00x16	6	161	205	21,5/27	ET 0	3,5 / 6	welded	1652	16.90.09
9,00x16	6	166	210	20/25	ET 0	4,0 / 8	welded	?	16.90.10
9,00x16	6	161	205	21,5/27	ET 0	4,0 / 6	welded	2345	16.90.11
9,00x16	6	117,8	152,4	18	ET -5	3,5 / 6	welded	1562	16.90.12
9,00x16	6	102	162	18/25	ET +15	3,5 / 8	welded	?	16.90.13
9,00x16	6	161	205	21,5/27	ET 0	3,5 / 6	welded	1988	16.90.14
11x16	6	161	205	21,5/27	ET 0	4,0 / 8	welded	2651	16.11.01
11x16	6	161	205	21,5/27	ET -50	4,5 / 10	welded	2651	16.11.03
11x16	6	161	205	21,5/27	ET -20	4,0 / 8	welded	2651	16.11.04
11x16	5	80	115	21,5	ET 0	4,5 / 8	welded	3080	16.11.06
11x16	6	163	222,25	32/38	ET 0	4,5 / 8	welded	2651	16.11.07
11x16	5	95	140	21,5	ET -50	4,5 / 10	welded	?	16.11.08
11x16	6	161	205	21,5/27	ET 0	4,5 / 8	welded	3080	16.11.09
11x16	8	153	203,2	17	ET -15	4,5 / 8	welded	2651	16.11.10
11x16	8	221	275	21,5/27	ET -30	4,5 / 8	welded	3569	16.11.11
11x16	5	95	140	18/23,5	ET -55	4,5 / 10	welded	2651	16.11.12
11x16	8	153	203,2	17	ET -25	4,5 / 8	welded	2651	16.11.13
11x16	6	161	205	21,5/27	ET +15	4,5 / 8	welded	3263	16.11.14
12x16	6	117,4	152,4	16	ET -30	5,0 / 10	welded	?	16.12.01
12x16	6	135,3	170	17,3	ET -70	5,0 / 10	welded	?	16.12.02



Wheels 16.5"

Wheel Size	Nb of bolt holes	Central hole diameter	PCD	Bolt hole diameter	Offset	Material thickness	Type of wheel*	Load capacity at 40 km/h	Pronar part no
8,25x16,5	8	152,5	203,2	?	?	4,8 / 6	welded	2060	165.825.01
8,25x16,5	5	135	175	20/25	ET -19	4,8 / 8	welded	2060	165.825.02
8,25x16,5	6	161	205	21,5/27	ET -30	4,8 / 8	welded	2060	165.825.03
8,25x16,5	5	110	160	18,5/24	ET -21	4,8 / 10	welded	2060	165.825.04
8,25x16,5	6	161	205	21,5/27	ET -70	4,8 / 8	welded	2060	165.825.05
8,25x16,5	10	93	140	16	ET +20	5,0 / 6	welded	2170	165.825.06
9,75x16,5	6	161	205	21,5/27	ET -35	5,0 / 8	welded	?	165.975.01
9,75x16,5	8	152,5	203,2	17/?	ET +39	4,0 / 7	welded	?	165.975.02
9,75x16,5	6	95	140	17	ET -22	5,0 / 10	welded	?	165.975.03
9,75x16,5	8	230	275	24	ET -159	5,0 / 10	welded	?	165.975.04
9,75x16,5	6	172	222,25	32,2/37,5	ET +104	5,0 / 10	welded	?	165.975.05
9,75x16,5	8	152,5	203,2	17/?	ET +39	4,0 / 7	welded	?	165.975.06
9,75x16,5	8	152,4	203,2	16,5/23,9	ET +27,5	5,0 / 10	welded	?	165.975.07
9,75x16,5	6	165	222,25	32,2/37,5	ET -61	5,0 / 10	welded	?	165.975.08



Wheels 17"

Wheel Size	Nb of bolt holes	Central hole diameter	PCD	Bolt hole diameter	Offset	Material thickness	Type of wheel*	Load capacity at 40 km/h	Pronar part no
13,00x17	6	161	205	21,5/27	ET 0	4,5 / 10	welded	3059	17.13.01
13,00x17	6	161	205	21,5/27	ET 0	4,5 / 10	welded	3059	17.13.02
13,00x17	6	161	205	21,5/27	ET -40	4,5 / 10	welded	3059	17.13.03
13,00x17	6	161	205	21,5/27	ET -80	4,5 / 10	welded	2549	17.13.04
13,00x17	6	161	205	21,5/27	ET -15	4,5 / 8	welded	?	17.13.06
13,00x17	6	161	205	21,5/27	ET -30	4,5 / 8	welded	2804	17.13.07
13,00x17	6	161	205	21,5/27	ET 0	4,5 / 10	welded	3059	17.13.08
13,00x17	8	221	275	27/32	ET 0	4,5 / 8	welded	3059	17.13.09
13,00x17	6	161	205	21,5/27	ET 0	4,5 / 6	welded	3304	17.13.10
13,00x17	6	161	205	21,5/27	ET -50	4,5 / 10	welded	3059	17.13.11
13,00x17	6	161	205	21,5/27	ET 0	4,5 / 10	welded	3059	17.13.12
13,00x17	8	221	275	27/32	ET 0	4,5 / 8	welded	3059	17.13.13
13,00x17	8	221	275	21,5/27	ET 0	4,5 / 8	welded	3059	17.13.14
13,00x17	8	221	275	21,5/27	ET 0	4,5 / 10	welded	?	17.13.15
13,00x17	6	161	205	21,5/27	ET 0	4,5 / 8	welded	?	17.13.16
13,00x17	6	161	205	21,5/27	ET -85	4,5 / 10	welded	2549	17.13.17
13,00x17	6	161	205	21,5/27	ET -50	4,5 / 10	welded	3059	17.13.18
13,00x17	6	161	205	21,5/27	ET -120	4,5 / 8	welded	?	17.13.19
13,00x17	6	161	205	21,5/27	ET 0	4,5 / 6	welded	3350	17.13.20
13,00x17	6	161	205	21,5/27	ET 0	4,5 / 6	welded	3350	17.13.21
13,00x17	6	117,4	152,4	18/23,5	ET 0	4,5 / 8	welded	?	17.13.22
16,00x17	8	221	275	21,5 / 27	ET -35	5,0 / 10	welded	4079	17.16.01
16,00x17	6	161	205	21,5/27	ET 0	5,0 / 10	welded	4079	17.16.02
16,00x17	6	161	205	21,5/27	ET -70	5,0 / 10	welded	4079	17.16.03
16,00x17	6	161	205	21,5/27	ET -50	5,0 / 10	welded	4079	17.16.05
16,00x17	6	161	205	21,5/27	ET -35	5,0 / 10	welded	4079	17.16.06
16,00x17	6	161	205	21,5/27	ET +55	5,0 / 10	welded	4079	17.16.10
16,00x17	6	161	205	21,5/27	ET 0	5,0 / 10	welded	4079	17.16.02.6
16,00x17	6	161	205	21,5/27	ET -50	5,0 / 10	welded	4079	17.16.05.6
16,00x17	6	161	205	21,5/27	ET -35	5,0 / 10	welded	4079	17.16.06.6
16,00x17	6	161	205	21,5/27	ET -70	5,0 / 10	welded	4079	17.16.11
16,00x17	6	161	205	21,5/27	ET 0	5,0 / 10	welded	4150	17.16.12
16,00x17	6	161	205	21,5/27	ET -70	4,5 / 8	welded	2651	17.16.18
16,00x17	8	221	275	21,5/27	ET -20	5,0 / 8	welded	4079	17.16.19
16,00x17	6	161	205	21,5/27	ET -70	5,0 / 10	welded	4079	17.16.20
16,00x17	6	161	205	21,5/27	ET -70	5,0 / 10	welded	3967	17.16.11.6
16,00x17	6	161	205	21,5/27	ET -70	5,0 / 10	welded	3967	17.16.15.6
16,00x17	6	161	205	21,5/27	ET -70	5,0 / 10	welded	4079	17.16.20.6
16,00x17	6	161	205	21,5/27	ET -60	5,0 / 10	welded	4079	17.16.21
16,00x17	6	161	205	21,5/27	ET -20	5,0 / 10	welded	?	17.16.22
16,00x17	5	110	160	18,5/23,5	ET 0	5,0 / 10	welded	?	17.16.23
16,00x17	6	161	205	21,5/27	ET 0	5,0 / 6	welded	3875	17.16.25
16,00x17	6	161	205	21,5/27	ET -70	5,0 / 6	welded	3875	17.16.26
16,00x17	8	221	275	21,5/27	ET +50	5,0 / 8	welded	?	17.16.28
16,00x17	6	161	205	21,5/27	ET -35	5,0 / 10	welded	?	17.16.29



Wheels Catalogue

Wheel Size	Nb of bolt holes	Central hole diameter	PCD	Bolt hole diameter	Offset	Material thickness	Type of wheel*	Load capacity at 40 km/h	Pronar part no
16,00x17	8	221	275	27/32	ET 0	5,0 / 8	welded	4130	17.16.30
16,00x17	8	221	275	27/32	ET -20	5,0 / 8	welded	4130	17.16.31
16,00x17	8	221	275	27/32	ET -30	5,0 / 8	welded	4130	17.16.32
16,00x17	8	221	275	27/32	ET -10	5,0 / 8	welded	4130	17.16.33
16,00x17	8	221	275	27/32	ET -70	5,0 / 8	welded	4130	17.16.34
16,00x17	8	221	275	21,5/27	ET -35	5,0 / 8	welded	4130	17.16.35
16,00x17	8	221	275	21,5/27	ET 0	5,0 / 8	welded	4130	17.16.36
16,00x17	8	221	275	21,5/27	ET -70	5,0 / 8	welded	4130	17.16.37
16,00x17	6	161	205	21,5/27	ET -100	5,0 / 10	welded	?	17.16.38
16,00x17	6	161	205	21,5/27	ET 0	5,0 / 6	welded	?	17.16.39
16,00x17	8	221	275	21,5/27	ET 0	5,0 / 8	welded	?	17.16.40
16,00x17	8	221	275	27/32	ET -10	5,0 / 8	welded	4130	17.16.33.6
16,00x17	8	221	275	21,5/27	ET -35	5,0 / 8	welded	4130	17.16.35.6
16,00x17	8	221	275	21,5/27	ET 0	5,0 / 8	welded	4130	17.16.36.6
16,00x17	6	161	205	21,5/27	ET -30	5,0 / 6	welded	?	17.16.41
16,00x17	6	161	205	21,5/27	ET 0	5,2 / 10	welded	4752	17.16.42
16,00x17	8	221	275	21,5/27	ET -70	5,0 / 8	welded	?	17.16.43
16,00x17	8	221	275	21,5/27	ET -70	5,0 / 10	welded	4079	17.16.44
16,00x17	8	221	275	21,5/27	ET -50	5,0 / 8	welded	4079	17.16.45
16,00x17	6	161	205	21,5/27	ET -15	4,5 / 8	welded	3875	17.16.46
16,00x17	8	221	275	21,5/27	ET -50	5,0 / 10	welded	4079	17.16.47
16,00x17	8	221	275	27/32	ET -70	5,0 / 10	welded	4079	17.16.48
16,00x17	8	221	275	21,5/27	ET -35	5,0 / 8	welded	?	17.16.49
16,00x17	8	221	275	21,5/27	ET -35	5,0 / 8	welded	?	17.16.50
16,00x17	8	221	275	21,5/27	ET 0	5,0 / 8	welded	4200	17.16.61
16,00x17	8	221	275	21,5/27	ET -70	5,0 / 8	welded	?	17.16.62
16,00x17	6	161	205	21,5/27	ET -35	5,0 / 6	welded	?	17.16.63
16,00x17H2	8	221	275	27/32	ET -35	5,0 / 8	welded	4589	17.16.16
16,00x17H2	8	221	275	27/32	ET -10	5,0 / 8	welded	4589	17.16.17
16,00x17H2	6	161	205	21,5/27	ET 0	5,0 / 6	welded	3875	17.16.51
16,00x17H2	8	221	275	21,5/27	ET 0	5,0 / 8	welded	4130	17.16.52
16,00x17H2	6	161	205	21,5/27	ET -40	5,0 / 6	welded	3875	17.16.53
16,00x17H2	6	161	205	21,5/27	ET -25	5,0 / 6	welded	3875	17.16.54
16,00x17H2	8	221	275	27/32	ET -40	5,0 / 8	welded	4589	17.16.55
16,00x17H2	8	221	275	21,5/27	ET -105	5,0 / 8	welded	4200	17.16.56



Wheels 18"

Wheel Size	Nb of bolt holes	Central hole diameter	PCD	Bolt hole diameter	Offset	Material thickness	Type of wheel*	Load capacity at 40 km/h	Pronar part no
4,50Ex18	4	85	130	18/23,5	ET +22	4,0 / 8	welded	663	18.45.01
4,50Ex18	4	85	130	18/23,5	ET +22	3,2 / 6	welded	540	18.45.02
5,50Fx18	6	161	205	21,5/27	ET +45	4,0 / 8	welded	1071	18.55.06
5,50Fx18	5	94	140	16	ET +45	4,0 / 8	welded	?	18.55.07
5,50Fx18	6	117,8	152,4	18	ET +37	4,0 / 8	welded	?	18.55.08
5,50Ex18	6	161	205	21,5/27	ET +45	4,0 / 8	welded	1250	18.55.09
5,50Fx18	5	94	140	16	ET +55	4,0 / 8	welded	1200	18.55.10
5,50Fx18	6	117,8	152,4	18	ET 28,5	4,0 / 8	welded	?	18.55.11
9x18	6	161	205	21,5/27	ET 0	4,5 / 10	welded	3059	18.09.03
9x18	6	130	165	17	ET +10	4,0 / 8	welded	2651	18.09.08
9x18	5	290	335	21,5/38	ET 0	4,0 / 12	welded	3059	18.09.11
9x18	8	221	275	21,5/27	ET 0	4,5 / 10	welded	3059	18.09.12
9x18	8	152,4	203,2	17,5/23,5	ET -15	4,5 / 10	welded	?	18.09.22
9x18	8	221	275	18/23,5	ET +57	4,5 / 10	welded	?	18.09.25
9x18	5	290	335	21,5/38	ET +29	4,5 / 10	welded	3059	18.09.27
9x18	6	117,4	152,4	16	ET -50	4,5 / 10	welded	?	18.09.28
9x18	8	221	275	21,5/27	ET -13	4,5 / 10	welded	3059	18.09.30
9x18	8	221	275	21,5/27	ET +57	4,5 / 10	welded	?	18.09.31
9x18	8	152,4	203,2	19	ET +7	4,5 / 10	welded	3059	18.09.32
9x18	6	117,4	152,4	16	ET +7	4,5 / 10	welded	3059	18.09.33
9x18	8	153	203,2	17	ET +41	4,0 / 8	lugs	1152	18.09.34
9x18	6	117,8	152,4	18	ET +72	4,0 / 8	lugs	?	18.09.36
9x18	5	290	335	21,5/38	ET +18	4,5 / 10	welded	?	18.09.37
9x18	6	163	205	18	ET +60	5,0 / 10	welded	?	18.09.38
9x18	6	161	205	21,5/27	ET +45	4,5 / 10	welded	?	18.09.39
9x18	-	80	-	-	?	4,0 / 8	lugs	?	18.09.40
9x18	8	152,4	203,2	21,5/27	ET 0	4,5 / 10	welded	3059	18.09.41
9x18	8	221	275	27/32	ET +45	4,5 / 10	welded	3059	18.09.42
9x18	6	117,8	152,4	18	ET +7	4,5 / 8	lugs	?	18.09.43
9x18	6	240,5	274	17	ET +32	5,0 / 10	welded	3059	18.09.44
9x18	6	117,8	152,4	14,7	ET 0	4,0 / 8	lugs	?	18.09.45
9x18	6	135	170	17	ET +10	4,0 / 8	lugs	?	18.09.46
9x18	6	117,4	152,4	18	ET +25	4,5 / 8	welded	?	18.09.47
9x18	6	95	140	17	ET -10	5,0 / 10	welded	3059	18.09.48
W9x18	8	152,4	203,2	15	ET -50	4,0 / 8	lugs	1550	18.09.49
11x18	8	221	275	27/32	ET 0	4,5 / 10	welded	3059	18.11.01
11x18	8	221	275	27/32	ET 0	4,5 / 10	welded	3059	18.11.02
11x18	8	221	275	27/32	ET 0	4,5 / 10	welded	?	18.11.03
11x18	6	161	205	21,5/27	ET 0	4,5 / 10	welded	3059	18.11.04
11x18	6	161	205	21,5/27	ET 0	4,5 / 10	welded	2575	18.11.06
11x18	8	221	275	19	ET +35	4,5 / 10	welded	3059	18.11.09
11x18	8	221	275	21,5/27	ET 0	4,5 / 10	welded	3059	18.11.10
11x18	8	221	275	21,5/27	ET +14	5,0 / 10	welded	3253	18.11.13
11x18	8	221	275	27/32	ET -50	4,5 / 10	welded	3059	18.11.22
11x18	5	290	335	21,5/38	ET -7	4,5 / 10	welded	2305	18.11.23



Wheels Catalogue

Wheel Size	Nb of bolt holes	Central hole diameter	PCD	Bolt hole diameter	Offset	Material thickness	Type of wheel*	Load capacity at 40 km/h	Pronar part no
11x18	8	221	275	21,5/27	ET -10	5,0 / 10	welded	?	18.11.25
11x18	8	221	275	21,5/27	ET +75	4,5 / 10	welded	2651	18.11.27
11x18	8	221	275	21,5/27	ET 0	5,0 / 10	welded	3875	18.11.28
11x18	6	161	205	21,5/27	ET 0	4,5 / 10	welded	3059	18.11.29
11x18	5	290	335	21,5/38	ET +32	4,5 / 10	welded	3059	18.11.30
11x18	8	221	275	21,5/27	ET -50	4,5 / 10	welded	?	18.11.31
11x18	6	163	205	18	ET +60	4,5 / 10	welded	?	18.11.33
11x18	6	161	205	21,5/27	ET -35	4,5 / 10	welded	2723	18.11.34
11x18	8	223,5	275	21,5	ET +10	4,5 / 10	welded	?	18.11.35
11x18	6	161	205	21,5/27	ET +14	4,5 / 10	welded	2723	18.11.36
11x18	8	221	275	21,5/27	ET -100	5,0 / 10	welded	2855	18.11.37
11x18	8	221	275	21,5/27	ET 0	5,0 / 10	welded	3875	18.11.38
11x18	8	221	275	21,5/27	ET +30	4,5 / 10	welded	3875	18.11.39
11x18	8	152,6	203,2	19	ET -55	4,5 / 10	welded	?	18.11.40
11x18	6	161	205	21,5/27	ET +57	4,5 / 10	welded	2723	18.11.41
11x18	6	161	205	21,5/25	ET 0	4,5 / 10	welded	3059	18.11.42
11x18	8	221	275	21,5	ET +35	4,5 / 10	welded	?	18.11.43
13x18	6	161	205	21,5/27	ET 0	5,0 / 10	welded	3151	18.13.01
13x18	8	221	275	27/32	ET 0	5,0 / 10	welded	3151	18.13.02
13x18	8	152,4	203,2	18	ET +15	5,0 / 10	welded	3151	18.13.03
13x18	8	221	275	21,5/27	ET 0	5,0 / 10	welded	3151	18.13.04
13x18	6	161	205	21,5/27	ET 0	5,0 / 10	welded	3151	18.13.06
13x18	6	161	205	21,5/28	ET 0	5,0 / 10	welded	3151	18.13.08
13x18	8	221	275	21,5/28	ET 0	5,0 / 10	welded	3263	18.13.10
13x18	8	221	275	21,5/28	ET -25	5,0 / 10	welded	3151	18.13.11
13x18	6	161	205	21,5/27	ET +50	5,0 / 10	welded	3151	18.13.12
13x18	6	161	205	21,5/27	ET 0	5,0 / 10	welded	?	18.13.13
13x18	8	221	275	21,5/27	ET -50	5,0 / 10	welded	3263	18.13.14
13x18	6	161	205	21,5/27	ET -25	5,0 / 10	welded	3151	18.13.16
13x18H2	6	161	205	21,5/27	ET 0	4,5 / 10	welded	3151	18.13.100
13x18H2	8	221	275	21,5/27	ET 0	4,5 / 10	welded	3151	18.13.101
13x18H2	8	221	275	27/32	ET 0	4,5 / 8	welded	2651	18.13.102
13x18H2	6	161	205	21,5/27	ET 0	4,5 / 8	welded	2651	18.13.103



Wheels 20"

Wheel Size	Nb of bolt holes	Central hole diameter	PCD	Bolt hole diameter	Offset	Material thickness	Type of wheel*	Load capacity at 40 km/h	Pronar part no
5,50Fx20	5	135	175	20/26	ET +36	4,0 / 8	welded	?	20.55.02
5,50Fx20	6	161	205	21,5/27	ET 0	4,0 / 8	welded	734	20.55.03
5,50Fx20	6	117,7	152,4	18/23,5	ET +28,6	5,0 / 10	welded	877	20.55.05
5,50Fx20	6	117,8	152,4	18/23,5	ET +30	4,0 / 8	welded	612	20.55.08
5,50Fx20	6	117,8	152,4	16/22	ET +16	4,0 / 8	welded	?	20.55.09
5,50Fx20	6	117,8	152,4	18/23,5	ET +30	4,0 / 7	welded	?	20.55.10
5,50Fx20	5	94	140	18/23,5	ET +10	4,0 / 8	welded	?	20.55.11
5,50Fx20	5	102	140	18,5/23,5	ET 0	4,0 / 8	welded	734	20.55.12
5,50Fx20	8	221	275	21,5/27	ET +30	4,0 / 7	welded	612	20.55.13
5,50Fx20	6	160	205	19	ET -4	4,0 / 8	welded	612	20.55.14
5,50Fx20	-	-	-	-	ET +30,5	4	lugs	-	20.55.15
5,50Fx20	8	221	275	19	ET -4	4,0 / 8	welded	?	20.55.16
W7x20	8	145	190	20/26	ET +115	4,0 / 8	welded	948	20.07.01
W7x20	6	161	205	21,5/27	ET 0	4,0 / 8	welded	?	20.07.05
W7x20	6	102	165	17	ET +27	4,0 / 8	welded	?	20.07.06
W7x20	6	102	161	14	ET +52	4,0 / 8	welded	?	20.07.07
W7x20	6	120	180	20/26	ET +17,5	4,0 / 10	welded	?	20.07.09
W7x20	5	135	175	20/25	ET +25	4,0 / 8	welded	1754	20.07.11
W8x20	6	117,4	152,4	18	ET +17	3,5 / 8	lugs	?	20.08.01
W8x20	6	135	170	17	ET +117	4,0 / 10	lugs	1000	20.08.02
W8x20	-	80	-	-	ET +117	3,5 / 8	lugs	?	20.08.03
W8x20	6	117,8	152,4	18	ET +50	4,0 / 8	welded	?	20.08.04
W8x20	6	117,8	152,4	18	ET +100	4,0 / 8	welded	?	20.08.05
W8x20	8	221	275	21/26	ET 0	5,0 / 10	welded	5099	20.08.06
W8x20	6	117,8	152,4	18	ET +17	4,0 / 8	welded	?	20.08.07
W8x20	5	94	140	18,5/24	ET 0	4,0 / 10	welded	?	20.08.08
W9x20	8	145	190	20/26	ET +80	4,5 / 8	welded	?	20.09.02
W9x20	5	135	175	20/26	ET +80	4,5 / 8	welded	2651	20.09.04
W9x20	5	135	175	20/25	ET +31	4,5 / 8	welded	1754	20.09.05
W9x20	8	145	190	20/26	ET +105	4,5 / 8	welded	?	20.09.06
W9x20	6	161	205	21,5/27	ET 0	4,5 / 10	welded	3059	20.09.07
W9x20	6	161	205	21,5/27	ET -20	4,5 / 10	welded	?	20.09.13
W9x20	6	161	205	21,5/27	ET +45	4,5 / 12	welded		20.09.14
W9x20	6	110	150	17	ET -6	4,5 / 10	welded	3059	20.09.15
W10x20	6	117,4	152,4	16	ET +72	4,0 / 8	lugs	2651	20.10.01
W10x20	8	153	203,2	17	ET 0	4,0 / 10	lugs	1754	20.10.06
W10x20	8	152,6	203,2	17	ET +41	4,0 / 8	welded	2305	20.10.07
W10x20	8	152,6	203,2	17	ET +31,5	4,0 / 8	welded	2305	20.10.08
W10x20	8	152,6	203,2	17	ET +71,5	4,0 / 8	welded	2305	20.10.09
W10x20	8	152,6	203,2	17	ET +31,5	4,0 / 8	welded	2305	20.10.12
W10x20	6	117,4	152,4	18	ET +17	4,0 / 8	lugs	?	20.10.14
W10x20	6	135	170	17	ET +72	4,0 / 8	lugs	?	20.10.15
W10x20	8	221	275	21,5/27	ET +20	4,0 / 8	welded	2305	20.10.16
W10x20	6	161	205	21,5	ET 0	4,0 / 10	welded	?	20.10.17
W10x20	6	161	205	21,5/27	ET 0	4,0 / 10	welded	?	20.10.18



Wheels Catalogue

Wheel Size	Nb of bolt holes	Central hole diameter	PCD	Bolt hole diameter	Offset	Material thickness	Type of wheel*	Load capacity at 40 km/h	Pronar part no
W10x20	6	161	205	21,5/27	ET 0	4,0 / 10	welded	?	20.10.19
W10x20	8	221	275	21,5/27	ET +80	4,0 / 8	welded	2305	20.10.20
W10x20	8	152,6	203,2	17	ET 0	4,0 / 8	welded	2305	20.10.21
W10x20	8	153	203,2	17	ET +71,5	4,0 / 8	lugs	1754	20.10.22
W10x20	8	221	275	21,5	ET +45	4,0 / 10	welded	2305	20.10.23
W10x20	8	152,6	203,2	17	ET +26	4,0 / 8	welded	2305	20.10.24
W10x20	8	152,6	203,2	17	ET +26	4,0 / 10	lugs	2305	20.10.25
11x20	8	221	275	27/32	ET 0	4,5 / 10	welded	3059	20.11.05
W11x20	8	221	275	21,5/27	ET +35	4,0 / 8	welded	?	20.11.06
W11x20	6	135	170	17	ET -57	4,0 / 8	welded	?	20.11.07
11x20	8	221	275	21,5/27	ET -60	4,5 / 10	welded	?	20.11.08
11x20	8	221	275	21,5/27	ET +12	4,5 / 10	welded	3059	20.11.09
11x20	5	110	160	16	ET 0	4,5 / 10	welded	3059	20.11.14
11x20	8	221	275	27/32	ET +50	4,5 / 10	welded	3059	20.11.16
11x20	6	161	205	21,5	ET -20	4,5 / 10	welded	3059	20.11.17
11x20	6	161	205	21,5	ET +45	4,5 / 10	welded	3059	20.11.18
W11x20	6	161	205	21,5/27	ET +70	4,0 / 8	welded	2498	20.11.19
W11x20	6	161	205	21,5/27	ET +40	4,0 / 8	welded	2498	20.11.20
W11x20	6	161	205	21,5	ET 0	4,0 / 10	welded	?	20.11.21
11x20	10	281	335	27	ET +85	4,5 / 10	welded	?	20.11.22
W11x20	6	135	170	17	ET 0	4,0 / 8	lugs	?	20.11.23
W11x20	6	135	170	17	ET -90	4,0 / 10	welded	?	20.11.24
11x20	6	161	205	21,5	ET -64	4,5 / 10	welded	?	20.11.25
W11x20	8	221	275	21,5/27	ET +17,5	4,0 / 10	welded	?	20.11.26
W11x20	10	176	225	23	ET +27,5	4,0 / 10	welded	3059	20.11.27
W11x20	8	153	203,2	17	ET 0	4,0 / 10	lugs	?	20.11.28
11x20	6	135	170	17	ET +15	4,0 / 10	welded	3150	20.11.30
W11x20	6	161	205	21,5	ET +35	4,0 / 10	welded	3150	20.11.31
W11x20	6	161	205	19	ET 0	4,0 / 10	welded	3150	20.11.32
W11x20	5	93	140	17	ET +18,5	4,0 / 10	welded	3150	20.11.33
W11x20	6	161	205	21,5/27	ET +35	4,0 / 8	welded	2498	20.11.34
11x20	8	222	275	22/29,5	ET +5	4,5 / 12	welded	?	20.11.35
W11x20	8	152,6	203,2	16,5/21,5	ET -101	4,0 / 10	welded	?	20.11.36
W12x20	8	145	190	20/26	ET +80	4,5 / 10	welded	?	20.12.01
W12x20	5	135	175	20/26	ET +80	4,5 / 10	welded	2651	20.12.03
W12x20	8	222	275	21/26	ET -60	5,0 / 10	welded	1652	20.12.05
W12x20	5	135	175	20/26	ET +70	4,5 / 10	welded	?	20.12.07
W12x20	5	135	175	20/26	ET +70	4,5 / 10	welded	?	20.12.08
W13x20	10	281	335	27/32	ET 0	5,0 / 10	welded	3365	20.13.02
W13x20	5	117,4	152,4	16	ET -33	5,0 / 10	welded	3365	20.13.03
W13x20	8	221	275	21,5/27	ET +11,5	5,0 / 10	welded	3365	20.13.06
W13x20	8	221	275	21,5/27	ET +85	5,0 / 10	welded	3365	20.13.09
W13x20	8	221	275	21,5/27	ET 0	5,0 / 10	welded	3365	20.13.10
W13x20	6	161	205	21,5/27	ET 0	5,0 / 10	welded	?	20.13.15
W13x20	8	281	335	24/29	ET 0	5,0 / 10	welded	3365	20.13.16
W13x20	6	161	205	17,5	ET -82	4,5 / 8	welded	?	20.13.19
W13x20	6	161	205	17,5	?	4,5 / 8	welded	2498	20.13.20
W13x20	5	290	335	21,5/37	ET-20	4,5 / 8	welded	?	20.13.22



Wheels Catalogue

Wheel Size	Nb of bolt holes	Central hole diameter	PCD	Bolt hole diameter	Offset	Material thickness	Type of wheel*	Load capacity at 40 km/h	Pronar part no
W13x20	8	221	275	21,5/27	ET +35	5,0 / 10	welded	3365	20.13.23
W13x20	8	221	275	27/32	ET 0	5,0 / 10	welded	3365	20.13.26
W13x20	8	221	275	21,5/27	ET -7,5	5,0 / 10	welded	3365	20.13.28
W13x20	8	221	275	27/32	ET +50	5,0 / 10	welded	3365	20.13.29
W13x20	8	221	275	27/32	ET -15	5,0 / 10	welded	3365	20.13.33
W13x20	8	221	275	27/32	ET -10	5,0 / 10	welded	3365	20.13.34
W13x20	8	152,4	203,2	20	ET -15	5,0 / 10	welded	3365	20.13.35
W13x20	5	290	335	21,5/37	ET -45	4,5 / 8	welded	2651	20.13.37
W13x20	6	161	205	21,5/27	ET 0	4,5 / 8	welded	3059	20.13.38
W13x20	8	221	275	21,5/27	ET +30	5,0 / 12	welded	3569	20.13.39
W13x20	6	161	205	21/27	ET -60	5,0 / 10	welded	3569	20.13.40
W13x20	8	221	275	21/27	ET -60	5,0 / 10	welded	?	20.13.41
W13x20	6	161	205	21,5	ET +60	5,0 / 12	welded	3365	20.13.42
W13x20	-	70	-	-	ET +90	5,0 / 10	welded	?	20.13.43
W13x20	6	161	205	21,5/27	ET 0	5,0 / 10	welded	?	20.13.44
W13x20	8	152,4	203,2	17	ET +30	5,0 / 10	welded	3365	20.13.45
W13x20	10	281	335	27/32	ET 0	4,5 / 8	welded	?	20.13.46
W13x20	8	221	275	27/32	ET -100	5,0 / 10	welded	3365	20.13.47
W13x20	6	161	205	21,5/27	ET -45	5,0 / 10	welded	3365	20.13.48
W13x20	6	180	230	20	ET -30	5,0 / 10	welded	?	20.13.49
W13x20	10	281	335	27/32	ET 0	4,5 / 8	welded	?	20.13.50
W13x20	10	94	140	18,5/24	ET 0	5,0 / 12	welded	?	20.13.51
W13x20	10	290	335	21,5/38	ET +37	5,0 / 12	welded	2651	20.13.52
W13x20	6	117,4	152,4	16	ET -80	4,5 / 10	welded	?	20.13.53
W13x20	8	221	275	25,5	ET +20	5,0 / 12	welded	3569	20.13.54
W14x20	8	221	275	21,5/27	ET 0	5,0 / 12	welded	3569	20.14.02
W14x20	5	291,1	335	21,5/38	ET 0	5,0 / 10	welded	3365	20.14.09
W14x20	8	221	275	21,5/27	ET -35	5,0 / 10	welded	3569	20.14.10
W14x20	6	161	205	21,5/27	ET 0	5,0 / 10	welded	3569	20.14.12
W14x20	8	221	275	27/32	ET -10	5,0 / 10	welded	?	20.14.13
W14x20	8	152,4	203,2	21,5	ET +110	5,0 / 12	welded	3569	20.14.15
W14x20	8	221	275	22,5	ET 0	5,0 / 12	welded	4000	20.14.16
W16Lx20	8	221	275	21,5/27	ET 0	5,0 / 10	welded	4487	20.16.01
W16Lx20	10	281	335	27/32	ET 0	5,0 / 10	welded	4487	20.16.02
W16Lx20	6	161	205	21,5/27	ET -100	5,0 / 10	welded	?	20.16.03
W16Lx20	8	221	275	27/32	ET -50	5,0 / 10	welded	4589	20.16.04
W16Lx20	6	161	205	21,5/27	ET -120	5,0 / 10	welded	?	20.16.05



Wheel 22.5"

Wheel Size	Nb of bolt holes	Central hole diameter	PCD	Bolt hole diameter	Offset	Material thickness	Type of wheel*	Load capacity at 40 km/h	Pronar part no
24,00x22,5H2	10	281	335	27/32	ET -50	6,0 / 14	welded	6700	225.24.101
24,00x22,5H2	10	281	335	27/32	ET -100	6,0 / 14	welded	6700	225.24.102
24,00x22,5H2	10	281	335	27/32	ET -120	6,0 / 14	welded	6700	225.24.103
24,00x22,5H2	10	281	335	27/32	ET -15	6,0 / 14	welded	6700	225.24.104
24,00x22,5H2	8	221	275	21,5/27	ET -50	6,0 / 14	welded	6700	225.24.105
24,00x22,5H2	8	221	275	21,5/27	ET -100	6,0 / 14	welded	6700	225.24.106
24,00x22,5H2	10	281	335	27/32	ET 0	6,0 / 14	welded	6700	225.24.107
24,00x22,5H2	10	281	335	27/32	ET -70	6,0 / 14	welded	6700	225.24.108
24,00x22,5H2	10	281	335	27/32	ET -15	6,0 / 14	welded	6700	225.24.109
24,00x22,5H2	10	221	275	21,5/32	ET 0	6,0 / 14	welded	6700	225.24.110
24,00x22,5H2	10	281	335	27/32	ET -50	6,0 / 14	welded	6700	225.24.111
24,00x22,5H2	10	281	335	27/32	ET -100	6,0 / 14	welded	6700	225.24.112
24,00x22,5H2	10	281	335	27/32	ET -50	6,0 / 14	welded	6700	225.24.113
24,00x22,5H2	6	161	205	21,5/27	ET -115	6,0 / 14	welded	6700	225.24.114
24,00x22,5H2	8	221	275	27/32	ET -15	6,0 / 14	welded	6700	225.24.115
24,00x22,5H2	12	390	430	17	ET -80	6,0 / 14	multifit	?	225.24.116
24,00x22,5H2	12	390	430	17	ET -130	6,0 / 14	multifit	?	225.24.117
24,00x22,5H2	10	221	285,75	20,5	ET -38	7,0 / 14	welded	?	225.24.118
24,00x22,5H2	10	281	335	24	ET -75	7,0 / 14	welded	?	225.24.119
24,00x22,5H2	6	161	205	21,5/27	ET -15	6,0 / 14	welded	6700	225.24.120
24,00x22,5H2	10	281	335	27/32	ET -50	6,0 / 14	welded	6700	225.24.101.6
24,00x22,5H2	10	281	335	27/32	ET -15	6,0 / 14	welded	6700	225.24.104.6
24,00x22,5H2	10	281	335	27/32	ET 0	6,0 / 14	welded	6700	225.24.107.6
24,00x22,5H2	10	281	335	27/32	ET -150	6,0 / 14	welded	6700	225.24.121
24,00x22,5H2	8	221	275	21,5/27	ET -120	6,0 / 14	welded	?	225.24.122
24,00x22,5H2	8	221	275	21,5/27	ET 0	6,0 / 14	welded	?	225.24.PA
24,00x22,5H2	8	221	275	27/32	ET 0	6,0 / 14	welded	?	225.24.124
24,00x22,5H2	8	221	275	21,5/27	ET -130	6,0 / 14	welded	?	225.24.125
24,00x22,5H2	8	221	275	27/32	ET -50	6,0 / 14	welded	6720	225.24.126
24,00x22,5H2	10	281	335	25,4	ET 0	7,0 / 14	welded	6720	225.24.127.6
24,00x22,5H2	10	221	285,75	20,5	ET -50	7,0 / 14	welded	?	225.24.128
24,00x22,5H2	10	281	335	20,5	ET -50	7,0 / 14	welded	?	225.24.129
24,00x22,5H2	10	281	335	27/32	ET -70	6,0 / 14	welded	7050	225.24.130.6
24,00x22,5H2	10	281	335	27/32	ET +50	6,0 / 14	welded	7050	225.24.131
24,00x22,5H2	10	281	335	27/32	ET -50	6,0 / 15	welded	6700	225.24.132
20,00x22,5	10	281	335	27/32	ET -20	6,0 / 12	welded	5914	225.20.101
20,00x22,5	8	221	275	21,5/27	ET 0	6,0 / 12	welded	5914	225.20.102
20,00x22,5	10	281	335	27/32	ET -60	6,0 / 12	welded	?	225.20.103
20,00x22,5	10	281	335	27/32	ET 0	6,0 / 12	welded	5914	225.20.104
20,00x22,5	8	221	275	21,5/27	ET -50	6,0 / 12	welded	5914	225.20.106
20,00x22,5	10	281	335	27/32	ET -50	6,0 / 12	welded	5914	225.20.108
20,00x22,5	8	221	275	21,5/27	ET -70	6,0 / 12	welded	5914	225.20.110
20,00x22,5	10	281	335	27/32	ET -50	6,0 / 12	welded	?	225.20.113
20,00x22,5	6	161	205	21,5/27	ET -85	6,0 / 12	welded	5914	225.20.114
20,00x22,5	8	221	275	21,5/27	ET -50	6,0 / 12	welded	5914	225.20.115



Wheels Catalogue

Wheel Size	Nb of bolt holes	Central hole diameter	PCD	Bolt hole diameter	Offset	Material thickness	Type of wheel*	Load capacity at 40 km/h	Pronar part no
20,00x22,5	10	281	335	27/32	ET 0	6,0 / 12	welded	5914	225.20.116
20,00x22,5	8	221	275	27/32	ET 0	6,0 / 12	welded	?	225.20.117
20,00x22,5	10	281	335	27/32	ET +50	6,0 / 12	welded	?	225.20.118
20,00x22,5	6	161	205	21,5/27	ET -50	6,0 / 12	welded	?	225.20.119
20,00x22,5	10	281	335	27/32	ET 0	6,0 / 14	welded	?	225.20.121
20,00x22,5	8	221	275	27/32	ET 0	6,0 / 14	welded	?	225.20.122
20,00x22,5	10	281	335	27/32	ET -70	6,0 / 12	welded	5914	225.20.123
20,00x22,5	10	281	335	24	ET -15	6,0 / 12	welded	5914	225.20.124
20,00x22,5	8	221	275	27/32	ET +160	6,0 / 14	welded	?	225.20.125
20,00x22,5	6	161	205	21,5/27	ET -140	6,0 / 14	welded	5914	225.20.126
20,00x22,5	10	281	335	27/32	ET -50	6,0 / 14	welded	5914	225.20.127
20,00x22,5	8	221	275	27/32	ET -15	6,0 / 12	welded	?	225.20.128
20,00x22,5	8	221	275	27/32	ET +50	6,0 / 12	welded	?	225.20.129
20,00x22,5	10	281	335	27/32	ET -140	6,0 / 14	welded	?	225.20.130
20,00x22,5	10	281	335	27/32	ET +35	6,0 / 12	welded	?	225.20.131
20,00x22,5	10	281	335	27/32	ET -20	6,0 / 12	welded	5914	225.20.132
20,00x22,5	8	221	275	21,5/27	ET -15	6,0 / 12	welded	5914	225.20.133
20,00x22,5	8	221	275	27/32	ET +10	6,0 / 12	welded	?	225.20.134
20,00x22,5	10	281	335	27/32	ET 0	6,0 / 12	welded	5914	225.20.135
20,00x22,5	8	221	275	21,5/27	ET 0	6,0 / 12	welded	?	225.20.136
20,00x22,5	8	221	275	27/32	ET -60	6,0 / 12	welded	?	225.20.137
20,00x22,5	10	281	335	27/32	ET -60	6,0 / 12	welded	?	225.20.138
20,00x22,5	8	221	275	24/30	ET +10	6,0 / 12	welded	?	225.20.139
20,00x22,5	8	221	275	27/32	ET -15	6,0 / 12	welded	5914	225.20.140
20,00x22,5	10	281	335	27/32	ET -70	6,0 / 12	welded	?	225.20.141
20,00x22,5	10	281	335	24	ET -15	6,0 / 12	welded	5914	225.20.142
20,00x22,5	10	281	335	27/32	ET 0	6,0 / 14	welded	?	225.20.143
20,00x22,5	10	281	335	27/32	ET 0	6,0 / 12	welded	?	225.20.144
20,00x22,5	8	221	275	27/32	ET -70	6,0 / 12	welded	?	225.20.145
20,00x22,5	6	161	205	21,5/27	ET 0	6,0 / 12	welded	?	225.20.146
20,00x22,5	10	281	335	27/32	ET 0	6,0 / 12	welded	6150	225.20.147
20,00x22,5	8	221	275	27/32	ET 0	6,0 / 12	welded	5914	225.20.148
20,00x22,5	10	291	335	27/32	ET 0	6,0 / 12	welded	5914	225.20.149
20,00x22,5	8	221	275	27/32	ET -70	6,0 / 12	welded	5914	225.20.200
20,00x22,5	8	221	275	21,5/27	ET 0	6,0 / 12	welded	?	225.20.201
20,00x22,5	12	390	430	17	ET -40	6,0 / 14	multifit	?	225.20.202
20,00x22,5	12	390	430	17	ET -100	6,0 / 14	welded	?	225.20.203
20,00x22,5	8	221	275	21,5/27	ET -10	6,0 / 12	welded	?	225.20.204
20,00x22,5	10	?	?	?	ET -70	6,0 / 12	welded	5914	225.20.205
20,00x22,5	10	281	335	27/32	ET -70	6,0 / 12	welded	5914	225.20.206
20,00x22,5	10	281	335	27/32	ET -35	6,0 / 12	welded	?	225.20.207
20,00x22,5	10	281	335	27/32	ET -100	6,0 / 14	welded		225.20.208
20,00x22,5	10	281	335	27/32	ET +150	6,0 / 12	welded	?	225.20.209
20,00x22,5	8	221	275	21,5/27	ET -100	6,0 / 14	welded	?	225.20.210
20,00x22,5	6	161	205	21,5/27	ET -30	6,0 / 12	welded	6000	225.20.211
20,00x22,5	8	221	275	27/32	ET -70	6,0 / 12	welded	5914	225.20.212
20,00x22,5	8	221	275	27/32	ET -100	6,0 / 14	welded	5914	225.20.213
20,00x22,5H2	10	281	335	27/32	ET 0	6,0 / 12	welded	5914	225.20.150



Wheels Catalogue

Wheel Size	Nb of bolt holes	Central hole diameter	PCD	Bolt hole diameter	Offset	Material thickness	Type of wheel*	Load capacity at 40 km/h	Pronar part no
20,00x22,5H2	10	281	335	27/32	ET 0	6,0 / 12	welded	6118	225.20.151
20,00x22,5H2	10	281	335	27/32	ET -50	6,0 / 12	welded	5914	225.20.152
20,00x22,5H2	8	221	275	21,5/27	ET -50	6,0 / 12	welded	5914	225.20.153
20,00x22,5H2	10	281	335	27/32	ET -20	6,0 / 12	welded	6118	225.20.154
20,00x22,5H2	6	161	205	21,5/27	ET -100	6,0 / 12	welded	?	225.20.155
20,00x22,5H2	10	281	335	27/32	ET -15	6,0 / 12	welded	6118	225.20.156
20,00x22,5H2	10	281	335	27/32	ET -100	6,0 / 12	welded	6118	225.20.157
20,00x22,5H2	10	281	335	27	ET 0	6,0 / 12	welded	6118	225.20.158
20,00x22,5H2	8	221	275	21,5/27	ET 0	6,0 / 12	welded	5914	225.20.159
20,00x22,5H2	10	281	335	27	ET -45	6,0 / 12	welded	?	225.20.161
20,00x22,5H2	10	281	335	27/32	ET +15	6,0 / 12	welded	6118	225.20.162
20,00x22,5H2	8	221	275	27/32	ET 0	6,0 / 12	welded	5914	225.20.163
20,00x22,5H2	10	281	335	27/32	ET -15	6,0 / 12	welded	6118	225.20.164
20,00x22,5H2	8	221	275	27/32	ET -130	6,0 / 14	welded	5914	225.20.166
20,00x22,5H2	10	221	285	31,5/38	ET -88	7,0 / 12	welded	?	225.20.167
20,00x22,5H2	10	281	335	27/32	ET -60	6,0 / 12	welded	5914	225.20.168
20,00x22,5H2	8	221	275	21,5/27	ET -100	6,0 / 14	welded	5914	225.20.169
20,00x22,5H2	10	281	335	27/32	ET 0	6,0 / 12	welded	6118	225.20.151.6
20,00x22,5H2	10	281	335	27/32	ET -20	6,0 / 12	welded	6118	225.20.154.6
20,00x22,5H2	10	281	335	25,4	ET 0	7,0 / 12	welded	6700	225.20.160.6
20,00x22,5H2	8	221	275	27/32	ET 0	6,0 / 12	welded	6150	225.20.163.6
20,00x22,5H2	10	281	335	27/32	ET -40	6,0 / 12	welded	6118	225.20.165.6
20,00x22,5H2	10	221	285,75	20,5	ET -38	7,0 / 14	welded	?	225.20.170
20,00x22,5H2	10	281	335	24	ET -25	7,0 / 14	welded	?	225.20.171
20,00x22,5H2	10	221	285,75	25	ET -97	7,0 / 14	welded	?	225.20.172
20,00x22,5H2	8	221	275	27/32	ET -100	6,0 / 14	welded	5914	225.20.174
20,00x22,5H2	8	221	275	21,5/27	ET -100	6,0 / 14	welded	5914	225.20.176
20,00x22,5H2	8	221	275	21,5/27	ET -50	6,0 / 14	welded	5914	225.20.177
20,00x22,5H2	8	221	275	21,5/27	ET -90	6,0 / 14	welded	5914	225.20.178
20,00x22,5H2	10	281	335	27/32	ET -50	6,0 / 12	welded	6150	225.20.179
20,00x22,5H2	10	281	335	27/32	ET +120	6,0 / 12	welded	?	225.20.173.6
20,00x22,5H2	10	281	335	27/32	ET -50	6,0 / 14	welded	6118	225.20.175.6
18,00x22,5H2	10	281	335	25,4	ET 0	6,0 / 12	welded	7199	225.18.101.6
18,00x22,5H2	10	281	335	27/32	ET 0	6,0 / 12	welded	7250	225.18.102.6
18,00x22,5H2	10	281	335	27	ET 0	6,0 / 12	welded	?	225.18.103
18,00x22,5H2	10	281	335	27/32	ET -50	6,0 / 12	welded	7250	225.18.104.6.Z
18,00x22,5H2	10	281	335	27/32	ET -50	6,0 / 12	welded	7250	225.18.104.6
18,00x22,5H2	10	281	335	27/32	ET 0	7,0 / 12	welded	7342	225.18.105.6
18,00x22,5H2	10	281	335	27/32	ET -50	6,0 / 12	welded	6150	225.18.106.6
18,00x22,5H2	10	281	335	27/32	ET 0	6,0 / 12	welded	?	225.18.102.6
16,00x22,5	10	281	335	27/32	ET 0	6,0 / 10	welded	5506	225.16.101
16,00x22,5	8	221	275	21,5/27	ET 0	6,0 / 10	welded	5506	225.16.102
16,00x22,5	6	161	205	21,5/27	ET -76,2	6,0 / 12	welded	5506	225.16.103
16,00x22,5	10	281	335	27/32	ET -30	6,0 / 10	welded	5506	225.16.104
16,00x22,5	8	221	275	21,5/27	ET -50	6,0 / 10	welded	5500	225.16.105
16,00x22,5	10	281	335	24	ET -15	6,0 / 10	welded	5506	225.16.106
16,00x22,5	8	221	275	21,5/27	ET 0	6,0 / 10	welded	5500	225.16.107



Wheels Catalogue

Wheel Size	Nb of bolt holes	Central hole diameter	PCD	Bolt hole diameter	Offset	Material thickness	Type of wheel*	Load capacity at 40 km/h	Pronar part no
16,00x22,5	8	221	275	21,5/27	ET -50	6,0 / 10	welded	5506	225.16.109
16,00x22,5	6	161	205	21,5/27	ET 0	6,0 / 12	welded	?	225.16.111
16,00x22,5	10	281	335	27/32	ET -90	6,0 / 10	welded	5506	225.16.112
16,00x22,5	10	281	335	27/32	ET -50	6,0 / 10	welded	5506	225.16.114
16,00x22,5	8	221	275	27/32	ET 0	6,0 / 10	welded	?	225.16.116
16,00x22,5	8	221	275	21,5/27	ET +30	6,0 / 10	welded	?	225.16.117
16,00x22,5	5	176	225	24	ET -100	6,0 / 12	welded	5506	225.16.121
16,00x22,5	5	110	160	17	ET -32	6,0 / 12	welded	5506	225.16.122
16,00x22,5	6	161	205	21,5/27	ET 0	6,0 / 10	welded	5506	225.16.123
16,00x22,5	8	221	275	27/32	ET -20	6,0 / 10	welded	5506	225.16.124
16,00x22,5	8	221	275	27/32	ET -70	6,0 / 12	welded	5506	225.16.125
16,00x22,5	6	161	205	21,5/27	ET -50	6,0 / 12	welded	5506	225.16.126
16,00x22,5	8	221	275	21,5/27	ET 0	6,0 / 10	welded	5506	225.16.127
16,00x22,5	10	281	335	27/32	ET 0	6,0 / 10	welded	5506	225.16.128
16,00x22,5	8	221	275	21,5	ET 0	6,0 / 10	welded	5506	225.16.129
16,00x22,5	6	161	205	21,5/27	ET -70	6,0 / 12	welded	5506	225.16.130
16,00x22,5	6	161	205	21,5/27	ET -95	6,0 / 12	welded	5506	225.16.131
16,00x22,5	6	161	205	21,5/27	ET -70	6,0 / 12	welded	5506	225.16.132
16,00x22,5	8	221	275	21,5/27	ET -65	6,0 / 12	welded	5506	225.16.133
16,00x22,5	8	221	275	21,5/27	ET -15	6,0 / 10	welded	5506	225.16.134
16,00x22,5	8	221	275	21,5/27	ET +70	6,0 / 12	welded	5506	225.16.135
16,00x22,5	8	221	275	21,5/27	ET -50	6,0 / 10	welded	5506	225.16.136
16,00x22,5	8	221	275	21,5/27	ET +50	6,0 / 10	welded	5506	225.16.137
16,00x22,5	6	161	205	21,5/27	ET 0	6,0 / 12	welded	5506	225.16.138
16,00x22,5	8	161	205	21,5/27	ET -65	6,0 / 12	welded	5506	225.16.139
16,00x22,5	8	221	275	21,5/27	ET -50	5,0 / 10	welded	5506	225.16.140
16,00x22,5	10	281	335	27/32	ET -40	6,0 / 10	welded	5506	225.16.141
16,00x22,5	8	221	275	27/32	ET -15	6,0 / 10	welded	5506	225.16.142
16,00x22,5	10	281	335	27/32	ET -15	6,0 / 10	welded	5506	225.16.143
16,00x22,5	6	161	205	21,5/27	ET -95	6,0 / 12	welded	?	225.16.144
16,00x22,5	6	161	205	21,5/27	ET -15	6,0 / 12	welded	5506	225.16.145
16,00x22,5	8	221	275	27/32	ET -15	6,0 / 10	welded	5506	225.16.146
16,00x22,5	6	161	205	21,5/27	ET -50	6,0 / 12	welded	?	225.16.147
16,00x22,5	10	281	335	27/32	ET +30	6,0 / 12	welded	5506	225.16.148
16,00x22,5	6	161	205	21,5/27	ET -70	6,0 / 10	welded	?	225.16.149
16,00x22,5	8	221	275	21,5/27	ET +100	6,0 / 12	welded	5506	225.16.200
16,00x22,5	6	161	205	21,5/27	ET 0	6,0 / 10	welded	?	225.16.201
16,00x22,5	10	220	285	27/32	ET -15	6,0 / 10	welded	4589	225.16.202
16,00x22,5	8	221	275	27/32	ET -50	6,0 / 10	welded	5506	225.16.203
16,00x22,5	9	203	241,3	16/22	ET -15	6,0 / 12	welded	?	225.16.204
16,00x22,5	10	281	335	24	ET -15	6,0 / 10	welded	5506	225.16.205
16,00x22,5	10	281	335	27/32	ET -50	5,5 / 10	welded	5506	225.16.206
16,00x22,5	8	221	275	21,5/27	ET +50	6,0 / 10	welded	?	225.16.207
16,00x22,5	6	161	205	21,5/27	ET -35	6,0 / 12	welded	5506	225.16.208
16,00x22,5	6	161	205	21,5/27	ET -50	6,0 / 10	welded	5506	225.16.209
16,00x22,5	6	161	205	21,5/27	ET -70	6,0 / 12	welded	?	225.16.210
16,00x22,5	9	203	241,3	16/22	ET -70	6,0 / 12	welded	?	225.16.211
16,00x22,5	10	281	335	27/32	ET -100	6,0 / 10	welded	4997	225.16.212



Wheels Catalogue

Wheel Size	Nb of bolt holes	Central hole diameter	PCD	Bolt hole diameter	Offset	Material thickness	Type of wheel*	Load capacity at 40 km/h	Pronar part no
16,00x22,5	6	161	205	21,5/27	ET +50	6,0 / 10	welded	?	225.16.213
16,00x22,5	10	175	225	27/32	ET 0	6,0 / 10	welded	?	225.16.214
16,00x22,5	10	281	335	27/32	ET +35	6,0 / 10	welded	5506	225.16.215
16,00x22,5	8	221	275	21,5/27	ET -65	6,0 / 10	welded	5506	225.16.216
16,00x22,5	10	281	335	27/32	ET 0	6,0 / 10	welded	5506	225.16.217
16,00x22,5	8	221	275	21,5/27	ET 0	6,0 / 10	welded	5506	225.16.218
16,00x22,5	8	221	275	21,5/27	ET 0	6,0 / 10	welded	5506	225.16.219
16,00x22,5	6	161	205	21,5/27	ET -15	6,0 / 10	welded	5506	225.16.220
16,00x22,5	8	221	275	27/32	ET -15	6,0 / 10	welded	5506	225.16.221
16,00x22,5	8	221	275	27/32	ET -50	6,0 / 10	welded	5506	225.16.222
16,00x22,5	10	281	335	27/32	ET +50	6,0 / 10	welded	5506	225.16.223
16,00x22,5	6	161	205	21,5/27	ET -105	6,0 / 12	welded	5506	225.16.224
16,00x22,5	6	161	205	21,5/27	ET -90	6,0 / 12	welded	?	225.16.225
16,00x22,5	8	221	275	21,5/27	ET +65	6,0 / 12	welded	5506	225.16.226
16,00x22,5	6	161	205	21,5/27	ET -50	6,0 / 12	welded	?	225.16.227
16,00x22,5	12	390	430	17	ET -20	6,0 / 14	multifit	?	225.16.228
16,00x22,5	10	221	275	22	ET -50	6,0 / 10	welded	5506	225.16.229
16,00x22,5	8	221	275	22	ET +149	6,0 / 12	welded	?	225.16.230
16,00x22,5	8	221	275	21,5/27	ET +70	6,0 / 12	welded	5506	225.16.231
16,00x22,5	6	161	205	21,5/27	ET -30	6,0 / 10	welded	5506	225.16.232
16,00x22,5	8	221	275	24/30	ET -25	6,0 / 12	welded	5506	225.16.233
16,00x22,5	10	281	335	27/32	ET +25	6,0 / 10	welded	5506	225.16.234
16,00x22,5	10	281	335	26	ET 0	7,0 / 10	welded	?	225.16.235
16,00x22,5	6	161	205	21,5/27	ET 0	6,0 / 12	welded	5506	225.16.236
16,00x22,5	8	221	275	24/30	ET 0	6,0 / 12	welded	5506	225.16.237
16,00x22,5	10	281	335	27/32	ET 0	7,0 / 14	welded	6500	225.16.238
16,00x22,5	10	281	335	24/29	ET +50	7,0 / 14	welded	6000	225.16.239
16,00x22,5	10	281	335	27/32	ET -50	6,0 / 12	welded	?	225.16.240
16,00x22,5	8	221	275	20	ET -50	6,0 / 12	welded	5500	225.16.241
16,00x22,5	10	281	335	25,4	ET -15	6,0 / 14	welded	5506	225.16.242
16,00x22,5	5	290	335	21,5/38	ET -20	6,0 / 12	welded	5550	225.16.243
16,00x22,5	8	221	275	21,5/27	ET -20	6,0 / 10	welded	?	225.16.244
16,00x22,5	8	221	275	21,5	ET +40	6,0 / 12	welded	?	225.16.245
16,00x22,5H2	10	281	335	27/32	ET -50	6,0 / 10	welded	6118	225.16.150
16,00x22,5H2	10	281	335	27/32	ET 0	6,0 / 10	welded	6118	225.16.151
16,00x22,5H2	10	281	335	27/32	ET 0	6,0 / 10	welded	6118	225.16.152
16,00x22,5H2	10	281	335	27/32	ET -50	6,0 / 10	welded	6118	225.16.153
16,00x22,5H2	10	281	335	27/32	ET +25	6,0 / 10	welded	6118	225.16.154
16,00x22,5H2	10	281	335	27/32	ET +50	6,0 / 10	welded	5506	225.16.155
16,00x22,5H2	10	281	335	27/32	ET 0	6,0 / 10	welded	6118	225.16.156
16,00x22,5H2	8	221	275	21,5/27	ET 0	6,0 / 10	welded	6118	225.16.157
16,00x22,5H2	8	221	275	21,5/27	ET -50	6,0 / 10	welded	6118	225.16.158
16,00x22,5H2	10	281	335	27/32	ET 0	5,5 / 10	welded	?	225.16.159
16,00x22,5H2	10	281	335	27/32	ET 0	6,0 / 12	welded	?	225.16.160
16,00x22,5H2	8	221	275	21,5/27	ET 0	6,0 / 12	welded	?	225.16.161
16,00x22,5H2	6	161	205	21,5/27	ET 0	6,0 / 10	welded	6118	225.16.162
16,00x22,5H2	10	281	335	27/32	ET -40	6,0 / 10	welded	6120	225.16.163
16,00x22,5H2	8	221	275	21,5/27	ET 0	6,0 / 10	welded	?	225.16.164



Wheels Catalogue

Wheel Size	Nb of bolt holes	Central hole diameter	PCD	Bolt hole diameter	Offset	Material thickness	Type of wheel*	Load capacity at 40 km/h	Pronar part no
16,00x22,5H2	8	221	275	21,5/27	ET -50	5,5 / 10	welded	6118	225.16.165
16,00x22,5H2	6	161	205	21,5/27	ET 0	6,0 / 10	welded	?	225.16.166
16,00x22,5H2	8	221	275	27/32	ET -100	5,5 / 12	welded	5914	225.16.167
16,00x22,5H2	8	221	275	27/32	ET -80	6,0 / 12	welded	5914	225.16.168
16,00x22,5H2	10	281	335	27/32	ET -30	6,0 / 10	welded	6120	225.16.169
16,00x22,5H2	10	281	335	27/32	ET -50	6,0 / 10	welded	6300	225.16.150.6
16,00x22,5H2	10	281	335	27/32	ET 0	6,0 / 10	welded	6300	225.16.151.6
16,00x22,5H2	10	281	335	27/32	ET 0	6,0 / 10	welded	6300	225.16.152.6
16,00x22,5H2	10	281	335	27/32	ET -50	6,0 / 10	welded	6118	225.16.153.6
16,00x22,5H2	10	281	335	27/32	ET 0	6,0 / 10	welded	6118	225.16.156.6
16,00x22,5H2	8	221	275	21,5/27	ET 0	5,5 / 10	welded	5800	225.16.157.6
16,00x22,5H2	10	281	335	27/32	ET -30	6,0 / 10	welded	6300	225.16.169.6
16,00x22,5H2	8	153	203,2	19	ET -20	5,5 / 10	welded	6118	225.16.170
16,00x22,5H2	8	153	203,2	19	ET -105	5,5 / 10	welded	?	225.16.171
16,00x22,5H2	8	221	275	27/32	ET 0	6,0 / 10	welded	6118	225.16.172
16,00x22,5H2	8	221	275	21,5/27	ET -15	6,0 / 10	welded	6118	225.16.173
16,00x22,5H2	8	221	275	27/32	ET +50	6,0 / 12	welded	?	225.16.176
16,00x22,5H2	10	221	285,75	20,5	ET -48	7,0 / 14	welded	?	225.16.177
16,00x22,5H2	6	161	205	21,5/27	ET -50	6,0 / 10	welded	?	225.16.178
16,00x22,5H2	8	221	275	27/32	ET -80	6,0 / 12	welded	5914	225.16.179
16,00x22,5H2	10	221	285,75	25	ET -46	7,0 / 14	welded	?	225.16.180
16,00x22,5H2	8	221	275	21,5/27	ET -100	5,5 / 12	welded	5914	225.16.183
16,00x22,5H2	8	221	275	21,5/27	ET 0	5,5 / 10	welded	5600	225.16.184
16,00x22,5H2	8	221	275	21,5/27	ET -50	5,5 / 10	welded	5600	225.16.185
16,00x22,5H2	10	281	335	27	ET +10	6,0 / 12	welded	6118	225.16.174.6
16,00x22,5H2	6	161	205	21,5/27	ET -95	6,0 / 12	welded	5506	225.16.175.6
16,00x22,5H2	10	281	335	27/32	ET -50	6,0 / 10	welded	6118	225.16.181.6
16,00x22,5H2	10	281	335	27/32	ET 0	6,0 / 12	welded	7800	225.16.182.6
16,00x22,5H2	10	281	335	27/32	ET +75	6,0 / 12	welded	?	225.16.186.6
16,00x22,5H2	8	221	275	21,5/27	ET -49	6,0 / 10	welded	6118	225.16.187
16,00x22,5H2	8	221	275	21,5/27	ET -49	6,0 / 10	welded	6118	225.16.188
16,00x22,5H2	8	221	275	21,5/27	ET -49	6,0 / 10	welded	6118	225.16.189
16,00x22,5H2	8	221	275	21,5/27	ET -50	5,5 / 10	welded	5600	225.16.190
16,00x22,5H2	8	221	275	27/32	ET 0	5,5 / 10	welded	5600	225.16.191
16,00x22,5H2	10	281	335	27/32	ET -15	6,0 / 12	welded	5400	225.16.192
16,00x22,5H2	8	221	275	27/32	ET -15	6,0 / 12	welded	5400	225.16.193
16,00x22,5H2	10	281	335	27/32	ET 0	6,0 / 12	welded	6659	225.16.194
16,00x22,5H2	8	221	275	21,5/27	ET -50	5,5 / 10	welded	5600	225.16.195
16,00x22,5H2	10	281	335	27/32	ET -50	5,5 / 10	welded	5600	225.16.196
16,00x22,5H2	10	281	335	27/32	ET -50	5,5 / 10	welded	5600	225.16.197
16,00x22,5H2	10	281	335	27/32	ET 0	5,5 / 10	welded	5600	225.16.198
16,00x22,5H2	8	221	275	21,5/27	ET 0	5,5 / 10	welded	5600	225.16.199
16,00x22,5H2	8	221	275	21,5/27	ET +150	5,5 / 12	welded	5950	225.16.260
16,00x22,5H2	8	221	275	27/32	ET +80	5,5 / 10	welded	5600	225.16.262
16,00x22,5H2	8	221	275	21,5/27	ET -50	5,5 / 10	welded	5800	225.16.190.6
16,00x22,5H2	8	221	275	27/32	ET 0	5,5 / 10	welded	5800	225.16.191.6
16,00x22,5H2	10	281	335	27/32	ET -50	5,5 / 10	welded	6300	225.16.196.6
16,00x22,5H2	10	281	335	27/32	ET 0	6,0 / 12	welded	7800	225.16.261.6



Wheels Catalogue

Wheel Size	Nb of bolt holes	Central hole diameter	PCD	Bolt hole diameter	Offset	Material thickness	Type of wheel*	Load capacity at 40 km/h	Pronar part no
14,00x22,5	10	281	335	27/32	ET 0	7,0 / 10	welded	5506	225.14.101
14,00x22,5	8	221	275	21,5/27	ET 0	7,0 / 10	welded	5506	225.14.102
14,00x22,5	10	281	335	27/32	ET +25	7,0 / 10	welded	5506	225.14.103
14,00x22,5	10	281	335	27/32	ET -30	7,0 / 10	welded	5506	225.14.104
14,00x22,5	10	281	335	27/32	ET 0	7,0 / 12	welded	6506	225.14.105
14,00x22,5	10	281	335	27/32	ET -100	7,0 / 12	welded	5506	225.14.106
14,00x22,5	10	281	335	27 27	ET -100	7,0 / 12	welded	5506	225.14.107
14,00x22,5	10	281	335	27/32	ET 0	5,5 / 10	welded	5506	225.14.01
14,00x22,5	10	281	335	27/32	ET 0	6,0 / 12	welded	6506	225.14.05
14,00x22,5	10	281	335	27/32	ET 0	5,5 / 10	welded	?	225.14.10
13,00x22,5	6	161	205	21,5/27	ET 0	7,0 / 10	welded	?	225.13.101
13,00x22,5	8	221	275	21,5/27	ET 0	7,0 / 10	welded	5608	225.13.102
13,00x22,5	10	281	335	27/32	ET 0	7,0 / 10	welded	?	225.13.103
13,00x22,5	10	281	335	27/32	ET -30	7,0 / 10	welded	?	225.13.104
13,00x22,5	10	281	335	27/32	ET 0	7,0 / 10	welded	5608	225.13.105
13,00x22,5	10	281	335	27/32	ET -35	7,0 / 10	welded	5608	225.13.106
13,00x22,5	8	221	275	21,5/27	ET 0	7,0 / 10	welded	5608	225.13.107
13,00x22,5	6	161	205	21,5/27	ET -15	7,0 / 12	welded	?	225.13.108
13,00x22,5	8	153	203,2	16/22	ET +27	7,0 / 12	welded	?	225.13.109
13,00x22,5	10	223	285	19,5	ET 0	7,0 / 12	welded	?	225.13.110
13,00x22,5	8	152,4	203,2	16,5/22	ET 0	7,0 / 12	welded	?	225.13.111
13,00x22,5	8	221	275	21,5/27	ET 0	7,0 / 12	welded	5608	225.13.112
13,00x22,5	8	221	275	21,5/27	ET -15	7,0 / 12	welded	?	225.13.113
11,75/22,5	8	221	275	21,5/27	ET 0	7,0 / 10	welded	5099	225.1175.101
11,75/22,5	8	221	275	27/32	ET 0	7,0 / 10	welded	5099	225.1175.102
11,75/22,5	6	161	205	21,5/27	ET 0	7,0 / 12	welded	5303	225.1175.103
11,75/22,5	6	161	205	21,5/27	ET 0	7,0 / 10	welded	5303	225.1175.104
11,75/22,5	10	281	335	27/32	ET 0	7,0 / 10	welded	5099	225.1175.106
11,75/22,5	8	221	275	27/32	ET -30	7,0 / 10	welded	?	225.1175.109
11,75/22,5	6	161	205	21,5/27	ET 0	7,0 / 10	welded	5099	225.1175.117
11,75/22,5	6	161	205	21,5/27	ET -15	7,0 / 10	welded	5099	225.1175.118
11,75/22,5	8	221	275	21,5/27	ET -60	7,0 / 10	welded	?	225.1175.119
11,75/22,5	10	220	285	27/32	ET 0	7,0 / 10	welded	5099	225.1175.120
11,75/22,5	10	281	335	27/32	ET 0	6,0 / 10	welded	5099	225.1175.106 .P
11,75/22,5	10	281	335	27/32	ET -30	6,0 / 10	welded	4589	225.1175.108 .P
11,75/22,5	8	221	275	27/32	ET -30	6,0 / 10	welded	?	225.1175.109 .P
11,75/22,5	10	290	335	21,5/38	ET -20	7,0 / 12	welded	4589	225.1175.121
11,75/22,5	8	221	275	21,5/27	ET -25	7,0 / 10	welded	5099	225.1175.122
11,75/22,5	10	203	241,3	16/22	ET -15	7,0 / 10	welded	5099	225.1175.123
11,75/22,5	8	221	275	27/32	ET -50	7,0 / 10	welded	5099	225.1175.124
11,75/22,5	8	153	203,2	17	ET +41	6,0 / 12	welded	4589	225.1175.125
11,75/22,5	12	390	430	17	ET -20	7,0 / 14	multifit	?	225.1175.126
11,75/22,5	10	281	335	27/32	ET -50	7,0 / 10	welded	5099	225.1175.127
11,75/22,5	8	221	275	21,5/27	ET -38	7,0 / 10	welded	5099	225.1175.128
11,75/22,5	8	152,4	203,2	17,5/23	ET -80	6,0 / 10	welded	?	225.1175.129



Wheels Catalogue

Wheel Size	Nb of bolt holes	Central hole diameter	PCD	Bolt hole diameter	Offset	Material thickness	Type of wheel*	Load capacity at 40 km/h	Pronar part no
11,75/22,5	8	152,4	203,2	17,5/23	ET -13	6,0 / 10	welded	?	225.1175.130
11,75/22,5	6	161	205	21,5/27	ET 0	7,0 / 10	welded	5150	225.1175.131
9,00x22,5	8	151	203,2	20	ET -40	5,0 / 8	welded	?	225.09.101
9,00x22,5	8	290	330	17	ET -68	5,0 / 8	welded	?	225.09.102
9,00x22,5	10	281	335	25,4	ET -15	5,0 / 12	welded	?	225.09.103
9,00x22,5	8	221	275	21,5/27	ET 0	5,0 / 12	welded	?	225.09.104
9,00x22,5	8	221	275	21,5/27	ET 0	5,0 / 12	welded	?	225.09.105
9,00x22,5	6	161	205	21,5/27	ET 0	5,0 / 12	welded	?	225.09.106



Wheels 24"

Wheel Size	Nb of bolt holes	Central hole diameter	PCD	Bolt hole diameter	Offset	Material thickness	Type of wheel*	Load capacity at 40 km/h	Pronar part no
TW13x24	8	221	275	21,5/27	ET 0	5,0 / 12	welded	?	24.13TW.01
W7x24	8	221	275	21	ET -80	4,0 / 12	lugs	795	24.07.02
W8x24	8	152,4	203,2	18/23,5	ET -20	4,0 / 6	welded	800	24.08.03
W8x24	6	161	205	21,5/27	?	4,0 / 10	lugs	1254	24.08.05
W8x24	8	145	190	20/26	ET -30	? / 12	lugs	?	24.08.07
W8x24	10	281,5	335	21	ET 0	4,0 / 8	welded	?	24.08.11
W8x24	6	161	205	21,5/27	ET +27	4,0 / 8	welded	1061	24.08.12
W8x24	6	161	205	21,5/28	ET +72	4,0 / 8	welded	1061	24.08.13
W8x24	-	-	-	-	-	4,0 / 10	lugs	?	24.08.16
W8x24	8	153	203,2	17	?	4,0 / 10	lugs	?	24.08.17
W8x24	-	-	-	-	-	4,0 / 10	welded	?	24.08.18
W8x24	6	161	205	21,5/27	?	4,0 / 10	lugs	1254	24.08.19
W8x24	5	94	140	16	ET +35	4,0 / 10	welded	?	24.08.20
W8x24	8	221	275	21,5/27	ET +20	4,0 / 10	welded	?	24.08.21
W8x24	8	152,4	203,2	17,5/21,5	ET -20	4,0 / 5	welded	800	24.08.22
W8x24	6	382,5	425	17	ET +45	4,0 / 8	welded	?	24.08.23
W9x24	8	221	275	18/23,5	ET +35	4,0 / 10	welded	1652	24.09.05
W9x24	8	221	275	18/23,5	ET +35	4,0 / 10	welded	1770	24.09.06
W10x24	6	382,5	425	17	ET +46	4,0 / 8	welded	1601	24.10.04
W10x24	6	117,4	152,4	16	?	4,0 / 8	lugs	?	24.10.07
W10x24	6	284,2	325	21	?	4,0 / 12	lugs	1448	24.10.08
W10x24	8	221	275	21	?	4,0 / 12	lugs	?	24.10.09
W10x24	8	153	203,2	17	?	4,0 / 10	lugs	?	24.10.13
W10x24	8	221	275	21	?	4,0 / 12	lugs	1448	24.10.17
W10x24	6	117,4	152,4	16	?	4,0 / 8	lugs	1448	24.10.19
W10x24	10	281	335	21	ET -50	4,0 / 10	welded	?	24.10.23
W10x24	8	145	190	20/26	?	4,0 / 12	lugs	?	24.10.24
W10x24	8	152,4	203,2	17,5/21,5	ET -35	3,5 / 5	welded	?	24.10.25
W10x24	5	94	140	18,5/24	ET +20	4,0 / 8	welded	1601	24.10.26
W10x24	8	221	275	21,5	?	4,5 / 10	lugs	1397	24.10.27
W10x24	8	153	203,2	17	?	4,0 / 10	lugs	1448	24.10.33
W10x24	8	221	275	21,5/27	ET +43,5	4,5 / 10	lugs	?	24.10.38
W10x24	8	145	190	20/26	ET 0	4,0 / 10	lugs	2651	24.10.42
W10x24	8	221	275	21	ET +30	4,0 / 12	lugs	?	24.10.44
W10x24	6	161	205	21,5	ET +70	4,0 / 8	welded	1601	24.10.46
W10x24	6	161	205	21,5	ET +40	4,0 / 8	welded	1601	24.10.47
W10x24	-	145	-	-	ET +131	4,0 / 10	lugs	?	24.10.49
W10x24	8	221	275	21,5	ET -70	4,0 / 10	welded	?	24.10.50
W10x24	8	221	275	21,5/27	ET -50	4,0 / 10	lugs	?	24.10.51
W10x24	12	390	430	17	ET -30	4,0 / 10	multifit	?	24.10.52
W10x24	8	153	203,2	17	ET +95	4,0 / 10	lugs	?	24.10.53
W10x24	6	161	205	21,5	ET +47	4,0 / 8	welded	1601	24.10.54
W10x24	6	135	170	18	ET -75	4,0 / 8	welded	?	24.10.55



Wheels Catalogue

Wheel Size	Nb of bolt holes	Central hole diameter	PCD	Bolt hole diameter	Offset	Material thickness	Type of wheel*	Load capacity at 40 km/h	Pronar part no
W10x24	8	152,4	203,2	19	ET -140	4,0 / 10	lugs	?	24.10.56
W10x24	8	221	275	21/27	ET +107	4,0 / 12	lugs	?	24.10.57
W10x24	8	221	275	27/32	ET +9	4,0 / 12	welded	1700	24.10.58
W10x24	6/8	153	203,2/290	15/17,5	ET -100	4,0 / 8	lugs	?	24.10.59
W10x24	6	285,5	325	20	ET +39,5	4,0 / 10	lugs	?	24.10.60
W10x24	6	250,5	285	18	ET +25	4,0 / 12	welded	?	24.10.61
W10x24	6	135	170	17	ET 0	4,0 / 8	lugs	?	24.10.62
W10x24	6	285,5	325	20	ET +39,5	4,0 / 8	lugs	?	24.10.63
W10x24	6	135	170	18	ET +27	4,0 / 8	welded	?	24.10.64
W10x24	8	221	275	21,5/27	ET 0	4,5 / 12	welded	1850	24.10.65
W10x24	8	152,4	203,2	18	ET +19	4,0 / 10	welded	?	24.10.66
W10x24	8	152,4	203,2	17	ET +19	4,0 / 10	lugs	?	24.10.67
W10x24	8	222	275	22/29,5	ET +5	4,0 / 12	welded	1700	24.10.68
W10x24	6	161	205	21,5	ET +47	4,0 / 10	welded	?	24.10.69
W10x24	6	135	170	17	ET +26	4,0 / 10	lugs	?	24.10.70
W10x24	6	161	205	20	ET +75	4,0 / 10	welded	?	24.10.71
W10x24	8	221	275	21,5/28	ET +22	4,0 / 8	lugs	?	24.10.72
W10x24	6	135,2	170	17	ET +48	4,0 / 10	welded	?	24.10.73
W11x24	6	117,4	152,4	16	?	4,0 / 8	lugs	1448	24.11.03
W11x24	8	221	275	21	?	4,0 / 12	lugs	?	24.11.10
W11x24	8	153	203,2	17	ET +47	4,0 / 10	lugs	1448	24.11.11
W11x24	8	152,6	203,2	17	ET +41	4,0 / 10	welded	1897	24.11.12
W11x24	8	221	275	21,5	ET +42	4,0 / 12	lugs	?	24.11.10
W11x24	6	135	170	18	ET -66	4,0 / 8	welded	?	24.11.13
W11x24	8	153,6	203,2	17	ET +41	4,0 / 10	welded	?	24.11.14
W11x24	6	135,2	170	17	?	4,0 / 10	lugs	?	24.11.15
W11x24	8	290,5	330	17	ET 0	4,0 / 12	welded	?	24.11.16
W11x24	8	152,6	203,2	17	ET +41	4,0 / 10	welded	?	24.11.17
W11x24	8	152,6	203,2	17	ET +56	4,0 / 10	welded	1897	24.11.18
W11x24	6	135	170	17	ET -9	4,0 / 10	lugs	?	24.11.25
W11x24	6	135	170	18	ET +30	4,0 / 8	welded	?	24.11.26
W11x24	6	135	170	18	ET -21	4,0 / 8	welded	?	24.11.27
W11x24	8	152,4	203,2	21,5	ET -10	4,0 / 12	lugs	?	24.11.28
W11x24	6	117,4	152,4	16	ET -33	4,0 / 8	lugs	1600	24.11.29
W11x24	6	135,2	170	17	ET -14	4,0 / 10	welded	?	24.11.30
W11x24	8	153	203,2	17	ET -22,5	4,0 / 10	lugs	?	24.11.31
W11x24	8	152,4	203,2	17	ET -20	4,0 / 12	lugs	?	24.11.32
W12x24	8	222	275	21/26	ET +130	? / 12	lugs	?	24.12.02
W12x24	8	153	203,2	21,5/27	ET -60	4,0 / 10	welded	?	24.12.04
W12x24	8	152,4	203,2	18/23,5	ET -70	4,0 / 6	welded	?	24.12.09
W12x24	8	152,4	203,2	17,5/21,5	ET -70	3,5 / 5	welded	1250	24.12.13
W12x24	8	109	152,4	17	ET -148,5	4,0 / 12	lugs	?	24.12.16
W12x24	6	382,5	425	17	ET -54	4,0 / 8	welded	2651	24.12.19
W12x24	8	145	190	20/26	ET +72	4,0 / 12	lugs	2651	24.12.30
W12x24	8	152,4	203,2	18,5/24	ET -110	4,0 / 8	welded	?	24.12.31
W12x24	8	221	275	21,5	?	4,5 / 10	lugs	1754	24.12.38
W12x24	8	152,6	203,2	17	ET +42,5	4,0 / 10	welded	2651	24.12.41
W12x24	8	152,6	203,2	17	ET +49	4,0 / 10	welded	2651	24.12.42



Wheels Catalogue

Wheel Size	Nb of bolt holes	Central hole diameter	PCD	Bolt hole diameter	Offset	Material thickness	Type of wheel*	Load capacity at 40 km/h	Pronar part no
W12x24	8	152,4	203,2	19	ET +15	4,0 / 10	lugs	1448	24.12.43
W12x24	6	161	205	21,5/27	ET 0	4,0 / 12	welded	?	24.12.47
W12x24	6	161	205	21,5/24	ET 0	4,0 / 8	welded	1601	24.12.48
W12x24	8	153	203,2	17	ET +42,5	4,5 / 10	lugs	?	24.12.49
W12x24	10	281	335	27/32	ET -50	4,5 / 10	welded	?	24.12.53
W12x24	8	153	203,2	17	ET +15	4,0 / 10	lugs	?	24.12.54
W12x24	8	221	275	21,5/27	ET 0	4,5 / 12	welded	3750	24.12.55
W12x24	6	161	205	21,5/27	ET 0	4,0 / 12	welded	?	24.12.56
W12x24	8	221	275	21,5	ET -60	4,5 / 12	welded	?	24.12.57
W12x24	6	118	152,4	19	ET -84	4,5 / 12	lugs	?	24.12.58
W12x24	8	152,4	203,2	17,5/21,5	ET -70	3,5 / 5	welded	1254	24.12.59
W12x24	8	152,4	203,2	17	ET -5	4,0 / 10	lugs	?	24.12.60
W12x24	8	152,4	203,2	19	?	4,0 / 12	lugs	1448	24.12.62
W12x24	6	285,25	325	19,8	?	4,0 / 10	lugs	?	24.12.65
W12x24	8	221	275	21,5/27	?	4,5 / 10	lugs	?	24.12.67
W12x24	8	221	275	21,5/27	ET +10	4,5 / 10	welded	3000	24.12.68
W12x24	8	221	275	21	?	4,0 / 12	lugs	1448	24.12.70
W12x24	8	290,5	330	17	?	4,5 / 12	lugs	?	24.12.75
W12x24	6	161	205	21,5/24	ET -35	4,0 / 8	welded	1601	24.12.76
W12x24	8	290	330	18	ET -20	5,0 / 12	welded	?	24.12.77
W12x24	8	221	275	20	ET -80	5,0 / 12	welded	?	24.12.78
W12x24	6	161	205	21,5/24	ET -35	4,0 / 8	welded	?	24.12.79
W12x24	8	290,5	330	17	ET +100	4,5 / 12	welded	?	24.12.80
W12x24	8	152,4	203,2	18/23,5	ET -70	4,0 / 6	welded	?	24.12.81
W12x24	-	51	-	-	ET +102	4,5 / 10	lugs	?	24.12.82
W12x24	12	390	430	17	ET -30	4,0 / 10	multifit	?	24.12.83
W12x24	8	110	152,4	20,5	ET +105	4,5 / 10	welded	?	24.12.84
W12x24	8	152,6	203,2	17	ET -20	4,0 / 10	welded	2651	24.12.85
W12x24	8	152,6	203,2	17	ET +24	4,0 / 10	welded	2651	24.12.86
W12x24	8	221	275	21,5/27	ET +10	4,5 / 12	welded	2896	24.12.87
W12x24	8	145	190	20/26	ET +72	4,5 / 12	welded	2896	24.12.88
W12x24	6	135,2	170	17	ET -45	4,0 / 10	lugs	?	24.12.89
W12x24	8	152,6	203,2	17	ET +27	4,0 / 10	welded	?	24.12.90
W12x24	8	221	275	27/32	ET 0	5,0 / 12	welded	2900	24.12.91
W12x24	8	152,6	203,2	17	ET -20	4,0 / 10	welded	2651	24.12.92
W12x24	8	152,6	203,2	17	ET +24	4,0 / 10	welded	2651	24.12.93
W12x24	18	280	330	18	ET +11	5,0 / 12	welded	?	24.12.94
W12x24	8	152,6	203,2	17	ET +13	4,0 / 10	welded	?	24.12.95
W12x24	8	152,4	203,2	21,5	ET -84	4,5 / 12	lugs	?	24.12.96
W12x24	8	221	275	24	ET 0	4,5 / 12	lugs	1448	24.12.97
W12x24	12	230	260	15,5	ET 0	5,0 / 14	welded	?	24.12.98
W12x24	6	135,2	170	17	ET +30	4,0 / 10	lugs	?	24.12.99
W12x24	8	152,4	203,2	17,5/21,5	ET -60	3,5 / 5	welded	1250	24.12.100
W12x24	8	152,4	203,2	17,5/21,5	ET 0	3,5 / 5	welded	1254	24.12.101
W12x24	6	161	205	20	ET -45	4,5 / 14	welded	?	24.12.102
W12x24	18	281	330	18	ET +11	5,0 / 12	welded	?	24.12.103
W12x24	8	221	275	22	ET +50	4,0 / 10	welded	?	24.12.104
W12x24	10	154	225	22/27/32	ET 0	5,0 / 14	welded	2900	24.12.105



Wheels Catalogue

Wheel Size	Nb of bolt holes	Central hole diameter	PCD	Bolt hole diameter	Offset	Material thickness	Type of wheel*	Load capacity at 40 km/h	Pronar part no
W12x24	8	221	275	21,5	ET +72,5	4,0 / 12	welded	?	24.12.NC
W12x24	6	161	205	20	ET -20	4,5 / 14	welded	3750	24.12.107
W12x24	8	152,4	203,2	19	ET +50	4,0 / 10	lugs	?	24.12.108
W12x24	8	152,4	203,2	19	ET +60	4,0 / 10	lugs	?	24.12.109
W12x24	8	152,4	203,2	19	ET -50	4,0 / 10	lugs	?	24.12.110
W12x24	10	178	225	24/32	ET 0	5,0 / 14	welded	?	24.12.111
W12x24	8	221	275	21,5	ET +20	4,5 / 12	welded	?	24.12.112
W12x24	8	221	275	21,5	ET 0	4,5 / 12	welded	?	24.12.113
W12x24	8	152,4	203,2	17,5/21,5	ET +3	3,5 / 5	welded	1380	24.12.114
W12x24	8	152,4	203,2	19	ET +54	4,5 / 10	lugs	?	24.12.115
W13x24	8	221	275	21,5/27	ET -100	4,5 / 12	welded	3355	24.13.02
W13x24	8	221	275	21,5	ET -100	4,5 / 12	welded	?	24.13.13
W13x24	10	281	335	27/32	ET 0	5,0 / 12	welded	4630	24.13.16
W13x24	8	221	275	27/32	ET +70	4,5 / 10	welded	2651	24.13.17
W13x24	6	382,5	425	17	ET +46	4,0 / 8	welded	?	24.13.18
W13x24	10	281	335	23,5	ET +47,5	4,0 / 8	welded	1897	24.13.19
W13x24	8	221	275	21,5/27	ET +19	5,0 / 14	welded	?	24.13.22
W13x24	8	221	275	21,5/27	ET +19	5,0 / 14	welded	4752	24.13.23
W13x24	8	153	203,2	18	ET -11	4,0 / 8	welded	?	24.13.24
W13x24	6	161	205	21,5/27	ET -50	5,0 / 12	welded	4630	24.13.25
W13x24	8	221	275	21,5/27	ET 0	5,0 / 12	welded	3365	24.13.26
W13x24	8	221	275	24	ET -50	5,0 / 12	welded	?	24.13.27
W13x24	6	131	165	15,5/25	ET -100	5,0 / 12	welded	3355	24.13.28
W13x24	8	221	275	21,5/27	ET +15	4,5 / 10	welded	2651	24.13.29
W13x24	6	120	165	16,5/25	ET -140	5,0 / 12	welded	3355	24.13.30
W13x24	4	221	275	21,5/27	ET -35	5,0 / 10	welded	3702	24.13.31
W13x24	6	161	205	21,5/27	ET -35	5,0 / 12	welded	4630	24.13.32
W13x24	6	285,5	325	20	ET +0,5	4,5 / 10	lugs	?	24.13.33
W13x24	6	161	205	21,5/27	ET +45	5,0 / 12	welded	?	24.13.34
W13x24	10	281	335	27/32	ET -37	5,0 / 12	welded	4630	24.13.35
W13x24	6	161	205	21,5/27	ET -20	5,0 / 12	welded	4700	24.13.37
W14Lx24	8	221	275	27/32	ET +65	5,0 / 12	welded	?	24.14.06
W14Lx24	10	281,5	335	27/32	ET +13,8	5,0 / 14	welded	?	24.14.07
W14Lx24	8	152,4	203,2	17,5/21,5	ET -90	4,0 / 6	welded	1550	24.14.10
W14Lx24	12	371	481	25	ET -48	5,0 / 16	welded	?	24.14.11
W14Lx24	8	221	275	20	ET -40	5,0 / 12	welded	4630	24.14.15
W14Lx24	5	291	335	27/38	ET +15	5,0 / 12	welded	?	24.14.16
W14Lx24		51			ET +105	5,0 / ?	lugs	?	24.14.18
W15L24	8	221	275	24	ET +80	5,0 / 12	welded	?	24.15.15
W15L24	8	290	330	18,5	ET -15	5,0 / 12	welded	4630	24.15.19
W15L24	8	221	275	21,5	ET -70	5,0 / 12	welded	4252	24.15.20
W15L24	8	221	275	22/27	ET -10	5,0 / 12	welded	4252	24.15.23
W15L24	8	221	275	21,5/27	ET 0	5,0 / 12	welded	4252	24.15.24
W15L24	8	221	275	21,5	ET +30	5,0 / 12	welded	?	24.15.25
W15L24	8	221	275	21,5	ET -60	5,0 / 12	welded	4252	24.15.26
W15L24	8	153	203,2	17	ET -40	5,0 / 10	lugs	?	24.15.27
W15L24	8	153	203,2	19	ET -75	4,5 / 10	welded	?	24.15.28
W15L24	8	153	203,2	19	ET +15	4,5 / 10	welded	?	24.15.29



Wheels Catalogue

Wheel Size	Nb of bolt holes	Central hole diameter	PCD	Bolt hole diameter	Offset	Material thickness	Type of wheel*	Load capacity at 40 km/h	Pronar part no
W15L24	12	390	430	17	ET -30	5,0 / 10	multifit	?	24.15.30
W15L24	8	152,6	203,2	17	ET -20	5,0 / 10	welded	?	24.15.31
W15L24	8	152,6	203,2	17	ET +24	5,0 / 10	welded	?	24.15.32
W15L24	5	175	225	24	ET +100	5,0 / 12	welded	?	24.15.33
W15L24	8	221	275	21,5	ET -90	5,0 / 12	welded	4252	24.15.34
W15L24	10	281	335	27/32	ET -35	5,0 / 12	welded	?	24.15.35
W15L24	8	152,6	203,2	17	ET -40	5,0 / 10	welded	2651	24.15.36
W15L24	8	152,6	203,2	17	ET +24	5,0 / 10	welded	2651	24.15.37
W15L24	6	161	205	19	ET -85	5,0 / 12	welded	?	24.15.38
W15L24	10	281	335	27/32	ET 0	5,0 / 12	welded	?	24.15.39
W15L24	10	281	335	23,5	ET -60	5,0 / 10	welded	?	24.15.40
W15L24	8	153	203,2	17	ET 0	5,0 / 10	lugs	?	24.15.41
W15L24	8	153	203,2	19	ET -50	4,5 / 10	welded	?	24.15.42
W15L24	10	281	335	27/32	ET -37	5,0 / 12	welded	?	24.15.43
W15L24	6	161	205	20	ET +25	5,0 / 14	welded	4960	24.15.44
W15L24	10	281	335	27/32	ET -50	5,0 / 12	welded		24.15.45
W15L24	8	152,4	203,2	19	ET +10	5,0 / 10	lugs	?	24.15.46
W15L24	8	152,4	203,2	19	ET -20	5,0 / 10	lugs	?	24.15.47
W15L24	8	152,4	203,2	19	ET +80	5,0 / 10	welded	?	24.15.48
W15L24	6	161	205	20	ET -25	5,0 / 14	welded	4960	24.15.49
W15L24	6	161	205	20	ET -50	5,0 / 14	welded	4960	24.15.50
W15L24	6	135	170	18	ET -50	4,5 / 10	welded	?	24.15.51
W15L24	10	281	335	24	ET -26,5	5,0 / 12	welded	3350	24.15.52
W16Lx24	10	281	335	27/36	ET -15	5,0 / 12	welded	4630	24.16.02
W16Lx24	8	221	275	21,5/27	ET 0	5,0 / 12	welded	4630	24.16.04
W16Lx24	8	170	275	27/32	ET -31	5,0 / 12	welded	4630	24.16.05
W16Lx24	8	140	203,2	17	ET -60	5,0 / 12	welded	?	24.16.15
W16Lx24	8	221	275	24	ET -50	5,0 / 12	welded	4507	24.16.17
W16Lx24	8	221	275	26	ET +30	5,0 / 12	welded	?	24.16.18
W16Lx24	6	161	205	21,5	ET -120	5,0 / 12	welded	3355	24.16.19
W16Lx24	8	152,4	203,2	22	ET +100	5,0 / 12	welded	?	24.16.20
W16Lx24	6	161	205	21,5	ET +26	5,0 / 12	welded	3355	24.16.21
W16Lx24	8	221	275	26	ET +30	5,0 / 12	welded	?	24.16.22
W16Lx24	8	180	230	20,5	ET -75	5,0 / 12	welded	?	24.16.23
W16Lx24	8	180	230	20,5	ET -40	5,0 / 12	welded	?	24.16.24
W16x24	8	221	275	21,5/27	ET -50	5,0 / 12	welded	4507	24.16.13
W16x24	8	221	275	21,5/27	ET 0	5,0 / 12	welded	4507	24.16.14
DW13x24	8	221	275	21,5	ET +12,5	4,5 / 12	welded	4700	24.13.36
DW18Lx24	8	221	275	21,5/27	ET -50	5,0 / 12	welded	4874	24.18.08
DW18Lx24	8	221	275	21,5/27	ET -25	5,0 / 12	welded	4874	24.18.09
DW18Lx24	8	221	275	21,5/27	ET 0	5,0 / 12	welded	4874	24.18.10
DW18Lx24	8	281	335	27/32	ET 0	5,0 / 12	welded	4874	24.18.12
DW18Lx24	8	221	275	21,5/27	ET -50	5,0 / 12	welded	4874	24.18.208
DW18Lx24	8	221	275	21,5/27	ET -25	5,0 / 12	welded	4874	24.18.209
DW18Lx24	8	221	275	21,5/27	ET 0	5,0 / 12	welded	4874	24.18.210
DW18Lx24	10	281	335	27/32	ET -50	5,0 / 12	welded	4874	24.18.213
DW18Lx24	10	281	335	27/32	ET -15	5,0 / 12	welded	?	24.18.214
DW18Lx24	8	221	275	21,5/27	ET 0	5,0 / 12	welded	4874	24.18.215



Wheels Catalogue

Wheel Size	Nb of bolt holes	Central hole diameter	PCD	Bolt hole diameter	Offset	Material thickness	Type of wheel*	Load capacity at 40 km/h	Pronar part no
DW18Lx24	10	281	335	27/32	ET 0	5,0 / 12	welded	?	24.18.216
DW18Lx24	12	370	425	27/32	ET +11	5,0 / 14	welded	?	24.18.217
DW18Lx24	10	281	335	27/32	ET -50	5,0 / 12	welded	4874	24.18.13
DW18Lx24	10	281	335	27/32	ET -15	5,0 / 12	welded	?	24.18.14
DW18Lx24	8	221	275	21,5/27	ET 0	5,0 / 12	welded	4874	24.18.15
DW18Lx24	10	281	335	27/32	ET 0	5,0 / 12	welded	?	24.18.16



Wheel 26"

Wheel Size	Nb of bolt holes	Central hole diameter	PCD	Bolt hole diameter	Offset	Material thickness	Type of wheel*	Load capacity at 40 km/h	Pronar part no
DW12Lx26"	6	135	170	18	ET -35	4,5 / 12	welded	?	26.12.01
DW12Lx26"	6	135	170	18	ET -10	4,5 / 12	welded	?	26.12.02
DW12Lx26"	6	135	170	17	ET -35	4,5 / 10	crown	?	26.12.03
DW12Lx26"	6	135	170	17	ET -10	4,5 / 10	crown	?	26.12.04
DW16Lx26"	8	152,4	203,2	18	ET -70	5,0 / 12	welded	4252	26.12.05
DW16Lx26"	10	281	335	27/32	ET +19	5,0 / 12	welded	4252	26.12.06
DW16Lx26"	8	140	203,2	21,5	ET -6	5,0 / 12	welded	4252	26.12.07
DW16Lx26"	8	221	275	21,5/27	ET 0	5,0 / 12	welded	4252	26.12.08
DW16Lx26"	8	221,5	275	22	ET +70	5,0 / 12	welded	4252	26.12.09
DW16Lx26"	8	221	275	27/32	ET -70	5,0 / 12	welded	4252	26.12.13
DW16Lx26"	10	283,5	335	22	ET +5	5,0 / 12	welded	4252	26.12.14
DW16Lx26"	10	281	335	27/32	ET -10	5,0 / 12	welded	4252	26.12.15
DW16Lx26"	10	281	335	27/32	ET +70	5,0 / 12	welded	?	26.16.16
DW20Ax26"	10	281	335	27/32	ET 0	5,7 / 12	welded	?	26.20.02
DW20Ax26"	12	371	425	27/32	ET -50	6,0 / 12	welded	6302	26.20.134
DW20Ax26"	8	221	275	26	ET +84	6,0 / 12	welded	?	26.20.143
DW20Bx26"	10	281	335	27/32	ET -50	5,7 / 12	welded	6302	26.20.04
DW20Bx26"	8	221	275	21,5/27	ET 0	5,7 / 12	welded	6302	26.20.08
DW20Bx26"	8	221	275	21,5/27	ET -50	5,7 / 12	welded	6302	26.20.11
DW20Bx26"	10	281	335	27/32	ET 0	5,7 / 12	welded	?	26.20.26
DW20Bx26"	10	281	335	27/32	ET -50	5,7 / 12	welded	6302	26.20.29
DW20Bx26"	10	281	335	27/32	ET -70	5,7 / 12	welded	6302	26.20.30
DW20Bx26"	12	371	425	27/32	ET -50	5,7 / 12	welded	6302	26.20.34
DW20Bx26"	8	221	275	27/32	ET -50	5,7 / 12	welded	6302	26.20.36
DW20Bx26"	8	221	275	27/32	ET 0	5,7 / 12	welded	6302	26.20.38
DW20Bx26"	10	280,5	335	24	ET 0	7,0 / 14	welded	?	26.20.39
DW20Bx26"	10	281	335	27/32	ET 0	6,0 / 12	welded	6302	26.20.102
DW20Bx26"	10	281	335	27/36	ET -50	6,0 / 12	welded	6302	26.20.104
DW20Bx26"	8	221	275	21,5/27	ET 0	6,0 / 12	welded	6302	26.20.108
DW20Bx26"	8	221	275	21,5/27	ET -50	6,0 / 12	welded	6302	26.20.111
DW20Bx26"	10	281	335	27/32	ET -90	6,0 / 12	welded	6302	26.20.112
DW20Bx26"	8	221	275	21,5/27	ET -75	6,0 / 14	welded	6302	26.20.114
DW20Bx26"	8	152,4	203,2	21,5/27	ET 0	6,0 / 12	welded	?	26.20.115
DW20Bx26"	10	281	335	27/32	ET -80	6,0 / 12	welded	?	26.20.116
DW20Bx26"	8	152,4	203,2	20	ET -50	6,0 / 12	welded	?	26.20.120
DW20Bx26"	10	281	335	27/32	ET 0	6,0 / 14	welded	?	26.20.121
DW20Bx26"	10	281	335	27/32	ET -50	6,0 / 14	welded	?	26.20.122
DW20Bx26"	8	221	275	21,5/27	ET 0	6,0 / 14	welded	?	26.20.123
DW20Bx26"	8	221	275	21,5/27	ET -50	6,0 / 14	welded	?	26.20.124
DW20Bx26"	10	281	335	27/32	ET 0	6,0 / 12	welded	6300	26.20.126
DW20Bx26"	10	281	335	27/32	ET -100	6,0 / 12	welded	6302	26.20.127
DW20Bx26"	8	221	275	27/32	ET -70	6,0 / 12	welded	6302	26.20.128
DW20Bx26"	10	281	335	27/32	ET -50	6,0 / 12	welded	6302	26.20.129
DW20Bx26"	10	281	335	27/32	ET -70	6,0 / 12	welded	6302	26.20.130



Wheels Catalogue

Wheel Size	Nb of bolt holes	Central hole diameter	PCD	Bolt hole diameter	Offset	Material thickness	Type of wheel*	Load capacity at 40 km/h	Pronar part no
DW20Bx26"	8	221	275	27/32	ET -25	6,0 / 14	welded	?	26.20.131
DW20Bx26"	8	221	275	21,5/27	ET 0	6,0 / 12	welded	6302	26.20.132
DW20Bx26"	8	155	203,2	27/32	ET +18	6,0 / 12	welded	?	26.20.135
DW20Bx26"	8	221	275	27/32	ET -50	6,0 / 12	welded	6302	26.20.136
DW20Bx26"	10	281	335	27/32	ET -100	6,0 / 12	welded	6302	26.20.137
DW20Bx26"	8	221	275	27/32	ET 0	6,0 / 12	welded	6302	26.20.138
DW20Bx26"	8	368	415	24/30	ET -45	6,0 / 12	welded	6302	26.20.140
DW20Bx26"	10	281	335	27/32	ET +56	6,0 / 12	welded	?	26.20.141
DW20Bx26"	10	283	335	27/32	ET +53	6,0 / 12	welded	?	26.20.142
DW20Bx26"	8	214	275	32/37	ET +35	7,0 / 12	welded	6302	26.20.144
DW20Bx26"	8	368	415	24/30	ET +24,5	6,0 / 12	welded	6302	26.20.145
DW20Bx26"	18	281	330	18	ET -21	7,0 / 18	welded	?	26.20.146
DW20Bx26"	20	321	380	18	ET -79	7,0 / 18	welded	?	26.20.147
DW20Bx26"	8	155	203,2	27/32	ET +18	6,0 / 14	welded	5300	26.20.148
DW20Bx26"	8	221	275	24	ET -41	6,0 / 14	welded	?	26.20.149
DW20Bx26"	10	281	335	27/32	ET +56	6,0 / 12	welded	?	26.20.151
DW20Bx26"	12	371	425	27/32	ET +110	6,0 / 12	welded	6302	26.20.152
DW20Bx26"	10	281	335	27/32	ET +80	6,0 / 14	welded	?	26.20.154
DW20Bx26"	10	281	335	27/32	ET -50	6,0 / 12	welded	6302	26.20.155
DW20Bx26"	8	221	275	27/32	ET 0	6,0 / 12	welded	6302	26.20.156
DW25Ax26"	8	221	275	26	ET +30	7,0 / 14	welded	?	26.25.125
DW25Ax26"	8	368	415	24/30	ET -45	7,0 / 12	welded	?	26.25.126
DW25Bx26"	8	221	275	27/32	ET -112	7,0 / 12	welded	?	26.25.16
DW25Bx26"	10	281	335	27/32	ET -150	7,0 / 14	welded	6302	26.25.17
DW25Bx26"	10	281	335	27/32	ET 0	7,0 / 14	welded	6302	26.25.103
DW25Bx26"	10	281	335	27/32	ET -50	7,0 / 14	welded	6302	26.25.104
DW25Bx26"	10	281	335	27/32	ET -12	7,0 / 14	welded	6302	26.25.105
DW25Bx26"	10	281	335	27/32	ET -100	7,0 / 14	welded	6302	26.25.106
DW25Bx26"	8	221	275	24	ET +30	7,0 / 12	welded	6149	26.25.107
DW25Bx26"	8	221	275	24	ET -65	7,0 / 14	welded	6302	26.25.108
DW25Bx26"	8	221	275	27/36	ET -112	7,0 / 14	welded	?	26.25.111
DW25Bx26"	10	281	335	27/32	ET -70	7,0 / 14	welded	?	26.25.112
DW25Bx26"	8	221	275	21,5/27	ET 0	7,0 / 14	welded	?	26.25.113
DW25Bx26"	12	371	425	27/38	ET 0	7,0 / 14	welded	?	26.25.114
DW25Bx26"	8	221	275	27/32	ET -112	7,0 / 12	welded	?	26.25.116
DW25Bx26"	10	281	335	27/32	ET -150	7,0 / 14	welded	6302	26.25.117
DW25Bx26"	10	281	335	27/32	ET -50	7,0 / 14	welded	6302	26.25.122
DW25Bx26"	10	281	335	27/32	ET 0	7,0 / 12	welded	6302	26.25.123
DW25Bx26"	8	164	222,25	26	ET +65	7,0 / 14	welded	?	26.25.124
DW25Bx26"	12	371	425	26	ET 0	7,0 / 18	welded	?	26.25.127
DW25Bx26"	8	221	275	24	ET -88	7,0 / 14	welded	?	26.25.128
DW25Bx26"	10	281	335	27	ET +100	7,0 / 12	welded	6302	26.25.129
DW25Bx26"	12	371	425	27/38	ET 0	7,0 / 14	welded	6300	26.25.153



Wheels 26.5"

Wheel Size	Nb of bolt holes	Central hole diameter	PCD	Bolt hole diameter	Offset	Material thickness	Type of wheel*	Load capacity at 40 km/h	Pronar part no
20,00x26,5H2	10	281	335	27/32	ET 0	6,0 / 12	welded	6700	265.20.01
20,00x26,5H2	8	221	275	21,5/27	ET -50	6,0 / 12	welded	6700	265.20.02
20,00x26,5H2	8	221	275	21,5/27	ET 0	6,0 / 12	welded	6700	265.20.03
20,00x26,5H2	10	281	335	27/32	ET -50	6,0 / 12	welded	6700	265.20.04
20,00x26,5H2	10	281	335	27/32	ET -50	7,0 / 14	welded	9150	265.20.04.6
20,00x26,5H2	10	281	335	27/32	ET 0	6,0 / 12	welded	6700	265.20.05
20,00x26,5H2	10	281	335	27/32	ET -50	6,0 / 12	welded	6700	265.20.06
20,00x26,5H2	10	281	335	27/32	ET -100	6,0 / 12	welded	6700	265.20.07
20,00x26,5H2	8	221	275	21,5/27	ET 0	6,0 / 12	welded	6700	265.20.08
20,00x26,5H2	10	281	335	27/32	ET +50	6,0 / 12	welded	6700	265.20.09
20,00x26,5H2	8	221	275	21,5/27	ET -15	6,0 / 12	welded	6700	265.20.10
20,00x26,5H2	8	221	275	21,5/27	ET -15	7,0 / 14	welded	9157	265.20.10.6
20,00x26,5H2	10	281	335	27/32	ET -50	7,0 / 14	welded	9157	265.20.11.6
20,00x26,5H2	10	281	335	27/32	ET -50	7,0 / 14	welded	9157	265.20.11.6.Z
20,00x26,5H2	10	280,5	335	24	ET 0	7,0 / 14	welded	?	265.20.12
20,00x26,5H2	10	281	335	27/32	ET -15	6,0 / 12	welded	6700	265.20.13
20,00x26,5H2	10	281	335	27/32	ET 0	7,0 / 14	welded	9157	265.20.13.6
20,00x26,5H2	10	281	335	27/32	ET +25	6,0 / 12	welded	6700	265.20.14
20,00x26,5H2	10	281	330	27/32	ET -70	6,0 / 12	welded	6700	265.20.15
20,00x26,5H2	8	153	203,2	19	ET -40	6,0 / 14	welded	6700	265.20.16
20,00x26,5H2	8	221	275	27/32	ET +50	6,0 / 14	welded	6700	265.20.17
20,00x26,5H2	8	221	275	27/32	ET +100	6,0 / 14	welded	?	265.20.18
20,00x26,5H2	12	390	430	17	ET -100	6,0 / 14	multifit	?	265.20.19
20,00x26,5H2	12	390	430	17	ET -40	6,0 / 14	multifit	?	265.20.20
20,00x26,5H2	10	281	335	27/32	ET -85	6,0 / 12	welded	6700	265.20.21
20,00x26,5H2	10	281	335	27/32	ET +50	6,0 / 12	welded	6700	265.20.22
20,00x26,5H2	10	281	335	27/32	ET 0	7,0 / 14	welded	9157	265.20.23
20,00x26,5H2	10	281	335	27/32	ET 0	7,0 / 14	welded	9157	265.20.23.6
20,00x26,5H2	10	281	335	27/32	ET -50	6,0 / 12	welded	6700	265.20.24
20,00x26,5H2	10	281	335	27/32	ET +80	6,0 / 12	welded	6700	265.20.25
20,00x26,5H2	10	281	335	27/32	ET 0	7,0 / 12	welded	7900	265.20.26
20,00x26,5H2	10	281	335	27/32	ET +25	7,0 / 12	welded	7900	265.20.27
20,00x26,5H2	10	281	335	27/32	ET -50	7,0 / 12	welded	7900	265.20.28
20,00x26,5H2	8	221	275	27/32	ET -50	6,0 / 14	welded	6800	265.20.29
20,00x26,5H2	10	281	335	27/32	ET -50	7,0 / 12	welded	7900	265.20.30
20,00x26,5H2	10	281	335	27/32	ET +100	6,0 / 12	welded	6700	265.20.31
20,00x26,5H2	10	281	335	27/32	ET 0	7,0 / 14	welded	9150	265.20.33
20,00x26,5H2	10	281	335	27/33	ET 0	7,0 / 14	welded	9150	265.20.33.6
24,00x26,5H2	8	221	275	21,5/27	ET -100	7,0 / 14	welded	9004	265.24.01
24,00x26,5H2	10	281	335	27/32	ET -50	7,0 / 14	welded	9000	265.24.02
24,00x26,5H2	10	281	335	27/32	ET 0	7,0 / 14	welded	9004	265.24.03
24,00x26,5H2	10	281	335	27/32	ET 0	7,0 / 14	welded	9004	265.24.04
24,00x26,5H2	8	221	275	21,5/27	ET 0	7,0 / 14	welded	9004	265.24.05
24,00x26,5H2	10	281	335	25,4	ET -80	7,0 / 14	welded	9004	265.24.05.6



Wheels Catalogue

Wheel Size	Nb of bolt holes	Central hole diameter	PCD	Bolt hole diameter	Offset	Material thickness	Type of wheel*	Load capacity at 40 km/h	Pronar part no
24,00x26,5H2	10	281	335	27/32	ET -50	7,0 / 14	welded	9004	265.24.06
24,00x26,5H2	10	281	335	27/32	ET -100	7,0 / 14	welded	9004	265.24.07
24,00x26,5H2	8	221	275	21,5/27	ET +15	7,0 / 14	welded	9004	265.24.08
24,00x26,5H2	10	281	335	25,4	ET -15	7,0 / 14	welded	9004	265.24.08.6
24,00x26,5H2	10	281	335	27/32	ET -80	7,0 / 14	welded	9004	265.24.09
24,00x26,5H2	10	281	335	27/32	ET -15	7,0 / 14	welded	9004	265.24.10
24,00x26,5H2	8	221	275	21,5/27	ET 0	7,0 / 14	welded	9004	265.24.11
24,00x26,5H2	8	221	275	21,5/27	ET -50	7,0 / 14	welded	9004	265.24.12
24,00x26,5H2	8	221	275	27/32	ET -30	7,0 / 14	welded	9004	265.24.13
24,00x26,5H2	12	390	430	17	ET -80	7,0 / 14	multifit	?	265.24.14
24,00x26,5H2	10	281	335	25,4	ET 0	7,0 / 14	welded	9004	265.24.15
24,00x26,5H2	10	281	335	27/32	ET 0	7,0 / 14	welded	9004	265.24.16
24,00x26,5H2	8	221	275	21,5/27	ET -75	7,0 / 14	welded	9004	265.24.17
24,00x26,5H2	10	281	335	27/32	ET +50	7,0 / 14	welded	9004	265.24.18
24,00x26,5H2	8	221	275	27/32	ET -40	7,0 / 14	welded	9004	265.24.19
24,00x26,5H2	10	281	335	27/32	ET -25	7,0 / 14	welded	9000	265.24.20
24,00x26,5H2	8	221	275	27/32	ET -50	7,0 / 14	welded	9004	265.24.21
24,00x26,5H2	8	221	275	27/32	ET 0	7,0 / 14	welded	9004	265.24.22
24,00x26,5H2	10	281	335	27/32	ET +20	7,0 / 14	welded	9000	265.24.23
24,00x26,5H2	10	221	285,75	20,5	ET -50	7,0 / 14	welded	9004	265.24.24
24,00x26,5H2	10	281	335	20,5	ET -50	7,0 / 14	welded	9004	265.24.25
24,00x26,5H2	10	281	335	27/32	ET +8	7,0 / 14	welded	9004	265.24.26
24,00x26,5H2	10	281	335	27/32	ET +30	7,0 / 14	welded	9004	265.24.27
24,00x26,5H2	10	281	335	25,4	ET +60	7,0 / 14	welded	9000	265.24.30
24,00x26,5PLH2	12	371	425	25,4/32	ET +10	7,0 / 14	welded	?	265.24.101
28,00x26,5H2	10	281	335	27/32	ET 0	7,0 / 14	welded	6628	265.28.01
28,00x26,5H2	10	281	335	24	ET -50	7,0 / 14	welded	?	265.28.02
28,00x26,5H2	10	281	335	27/32	ET -100	7,0 / 14	welded	6628	265.28.03
28,00x26,5H2	10	281	335	27/32	ET -50	7,0 / 14	welded	6628	265.28.04
28,00x26,5H2	10	281	335	27/32	ET 0	7,0 / 14	welded	6628	265.28.05
28,00x26,5H2	10	281	335	27/32	ET -100	7,0 / 14	welded	6750	265.28.06
28,00x26,5H2	10	221	285	25	ET 0	7,0 / 14	welded	?	265.28.07
28,00x26,5H2	10	281	335	27/32	ET -50	7,0 / 14	welded	?	265.28.08



Wheels 28"

Wheel Size	Nb of bolt holes	Central hole diameter	PCD	Bolt hole diameter	Offset	Material thickness	Type of wheel*	Load capacity at 40 km/h	Pronar part no
W8x28		101			ET + 120	4,0 / 10	lugs		28.08.02
W8x28	12	390	430	17	ET + 120	4,0 / 10	multifit	1020	28.08.03
W8x28	5	94	140	16	ET + 40	4,0 / 10	welded		28.08.04
W8x28	6	135	170	18	ET + 80	4,0 / 10	crown		28.08.05
W8x28	6	161	205	21,5/27	ET 0	4,0 / 10	welded		28.08.06
W9x28	6	181	230	20,5/26	ET 105	4,0 / 6,0	lugs		28.09.01
W10x28	6	180	230	20,5/26	??	?? / 6	lugs		28.10.01
W10x28	8	??	152,4	17	??	4,0 / 8	lugs	1275	28.10.05
W10x28	6	175	230	20,5/26	ET ??	4,5 / 10	lugs		28.10.06
W10x28	8	109,5	152,4	19,5/27	??	?? / 10	lugs	1275	28.10.10
W10x28	8	221	275	21,5/27	ET - 10	5,0 / 10	welded		28.10.22
W10x28	8	110	152,4	21,5/27	ET - 25	4,5 / 8	welded		28.10.23
W10x28	8	110	152,4	21,5/27	ET - 75	4,5 / 8	welded		28.10.24
W10x28	8	110	152,4	21,5/27	ET - 125	4,5 / 8	welded		28.10.25
W10x28	6	161	205	21,5/27	ET 0	4,5 / 10	welded	2366,4	28.10.27
W10x28	8	153	203,2	17	ET + 19	4,5 / 10	lugs	1254,6	28.10.28
W10x28		101			ET + 148	4,5 / 10	lugs		28.10.31
W10x28	8	291	330	17	ET + 19	4,5 / 10	lugs		28.10.32
W10x28	8	221	275	20	ET - 95	4,5 / 10	lugs		28.10.33
W10x28	12	390	430	17	ET - 131	4,5 / 10	multifit	1250	28.10.34
W10x28	6	161	205	21,5/27	ET + 10	4,0 / 8	welded	1601,4	28.10.35
W10x28	6	161	205	21,5/27	ET + 60	4,0 / 8	welded	1601,4	28.10.36
W10x28	6	135	170	18	ET - 10	4,0 / 10	welded		28.10.37
W10x28	8	290	330	17	ET + 135	4,0 / 10	lugs		28.10.38
W10x28	8	152,6	203,2	21,5	ET + 19	4,5 / 10	lugs	1254,6	28.10.39
W10x28	6	161	205	21,5	ET + 45	4,0 / 8	welded	1601,4	28.10.40
W10x28	8	145	190	20/26	ET + 75	4,5 / 12	lugs	1254,6	28.10.41
W10x28	8	110	152,4	18,5/24	ET - 25	4,5 / 12	welded		28.10.42
W10x28	8	110	152,4	18,5/24	ET - 125	4,5 / 12	welded		28.10.43
W10x28	6	135	170	18	ET - 31	4,0 / 10	welded		28.10.44
W10x28	8	145	190	20/26	ET + 150	4,5 / 12	lugs	1254,6	28.10.45
W10x28	8	221	275	21,5/27	ET + 10	4,5 / 12	welded		28.10.46
W10x28	8	221	275	21,5/27	ET + 90	4,5 / 12	welded		28.10.47
W11x28	6	175	230	20,5/26	??	4,5 / 10	lugs	1601,4	28.11.02
W11x28	8	109	152,4	17	??	4,5 / 10	lugs		28.11.03
W11x28	6	161	205	21,5/27	ET + 45	4,5 / 10	welded		28.11.05
W12x28	6	382,5	425	17	ET + 46	4,0 / 8	welded	2652	28.12.02
W12x28	8	109	152,4	17	ET - 27	4,5 / 10	lugs		28.12.04
W12x28	8	152,4	203,2	20,5	ET + 135	4,5 / 10	lugs	1601,4	28.12.05
W12x28	8	152,4	203,2	20,5	ET + 128	4,5 / 10	lugs		28.12.06
W12x28	8	170	220	27/32	??	4,5 / 8	lugs		28.12.09
W12x28	8	152,4	203,2	18	ET - 37,5	4,5 / 10	lugs	1601,4	28.12.24
W12x28	10	281	335	27/32	ET 0	5,0 / 12	welded	4253,4	28.12.27



Wheels Catalogue

Wheel Size	Nb of bolt holes	Central hole diameter	PCD	Bolt hole diameter	Offset	Material thickness	Type of wheel*	Load capacity at 40 km/h	Pronar part no
W12x28	8	152,6	203,2	17	ET - 44,5	4,5 / 10	welded	3304,8	28.12.30
W12x28	8	221	275	22	ET - 60	4,5 / 12	welded		28.12.35
W12x28	8	290	330	17	ET + 137	4,5 / 10	lugs		28.12.36
W12x28	8	215	275	21,5/27	ET - 50	4,5 / 10	lugs		28.12.37
W12x28	8	290	330	17	ET + 34	4,5 / 10	welded	3304,8	28.12.38
W12x28	12	385	430	17	ET + 100	4,5 / 10	multifit		28.12.39
W12x28	8	170	220	24	ET ??	4,5 / 10	lugs	1600	28.12.40
W12x28	12	390	430	17	ET + 137,5	4,5 / 10	multifit		28.12.41
W12x28	10	281	335	27/32	ET 0	5,0 / 12	welded	4253,4	28.12.42
W12x28	8	153	203,2	19	ET - 27,5	4,5 / 10	lugs		28.12.43
W12x28	8	221	275	21,5	ET - 2,5	5,0 / 12	welded		28.12.44
W12x28	8	152,6	203,2	17	ET + 27	4,5 / 10	lugs		28.12.45
W12x28	6	161	205	17	ET - 70	4,5 / 10	lugs		28.12.46
W12x28	6	161	205	21,5/27	ET 0	4,0 / 8	welded		28.12.47
W12x28	8	221	275	21,5	ET - 30	5,0 / 12	welded		28.12.48
W12x28	8	135	170	18	ET - 15	4,5 / 10	lugs	?	28.12.50
W12x28	8	153	203,2	19	ET - 20	4,5 / 10	lugs	?	28.12.53
W13x28	6	382,5	425	17	ET + 46	4,5 / 8	welded	2650	28.13.01
W13x28	8	153	203,2	19	ET - 19	4,5 / 10	lugs	1601,4	28.13.06
W13x28	10	281	335	24	ET 0	4,5 / 12	welded		28.13.07
W13x28	8	153	203,2	19	ET - 27,5	4,5 / 10	lugs		28.13.08
W13x28	10	281	335	24	ET 0	4,5 / 12	welded		28.13.09
W14x28	10	281	335	27/32	ET + 34	5,0 / 12	welded		28.14.07
W14x28	8	221	275	22	ET - 60	5,0 / 12	welded	4253,4	28.14.08
W14x28	8	290	330	18	ET + 30	5,0 / 12	welded		28.14.09
W14x28	10	281	335	22	ET - 20	5,0 / 12	welded	4253,4	28.14.10
W14x28	12	385	430	17	ET - 30	5,0 / 12	multifit		28.14.11
W14x28	8	362,5	405	17	ET + 30	5,0 / 10	welded	4253,4	28.14.13
W14x28	8	290,5	330	17	ET + 41	5,0 / 10	welded	4253,4	28.14.14
W14x28	12	385	430	17	ET + 100	5,0 / 12	multifit		28.14.15
W14x28	12	390	430	17	ET + 131	5,0 / 10	multifit		28.14.16
W14x28	8	152,6	203,2	17	ET - 35	5,0 / 10	welded		28.14.17
W14x28	8	221	275	22	ET 0	5,0 / 12	welded	4253,4	28.14.18
W14x28	8	152,4	203,2	20	ET + 72	5,0 / 12	lugs		28.14.19
W14x28	10	281	335	27/32	ET - 37	5,0 / 12	welded	4253,4	28.14.20
W15Lx28	6	382,5	425	17	ET + 46	4,5 / 8	welded		28.15.03
W15Lx28	10	281	335	27/32	ET + 45	5,0 / 12	welded	4651,2	28.15.07
W15Lx28	8	140	203,2	21,5	??	4,5 / 12	welded	4651,2	28.15.12
W15Lx28	10	281	335	27/32	ET + 19	5,0 / 12	welded	4651,2	28.15.21
W15Lx28	8	140	203,2	21,5	??	5,0 / 16	welded		28.15.22
W15Lx28	10	281	335	24	ET - 54	5,0 / 10	welded		28.15.23
W15Lx28	12	385	430	17	ET - 30	5,0 / 12	multifit		28.15.25
W15Lx28	10	281	335	27/32	ET - 30	5,0 / 10	welded		28.15.27
W15Lx28	8	221	275	22	ET - 20	5,0 / 12	welded	4651,2	28.15.28
W15Lx28	8	290	330	18	ET + 20	5,0 / 12	welded		28.15.29



Wheels Catalogue

Wheel Size	Nb of bolt holes	Central hole diameter	PCD	Bolt hole diameter	Offset	Material thickness	Type of wheel*	Load capacity at 40 km/h	Pronar part no
W15Lx28	10	281	335	22	ET - 20	5,0 / 12	welded	4651,2	28.15.30
W15Lx28	8	140	203,2	21,5	ET - 107	5,0 / 12	welded		28.15.31
W15Lx28	10	281	335	26	ET + 20	5,0 / 14	welded		28.15.32
W15Lx28	10	281	335	27/32	ET - 58	5,0 / 12	welded		28.15.33
W15Lx28	8	152,6	203,2	19	ET - 80,5	5,0 / 10	welded	4253,4	28.15.35
W15Lx28	8	221	275	21,5/27	ET 0	5,0 / 12	welded	5344,8	28.15.36
W15Lx28	10	281	335	27/32	ET - 10	5,0 / 12	welded		28.15.37
W15Lx28	10	281	335	27/32	ET - 90	5,0 / 12	welded		28.15.38
W15Lx28	8	362	405	18	ET - 20	5,0 / 12	welded		28.15.41
W15Lx28	10	281	335	27/32	ET 0	5,0 / 12	welded		28.15.42
W15Lx28	10	283,5	335	21,5	ET - 10	5,0 / 12	welded		28.15.43
W15Lx28	10	281	335	27/32	ET - 20	5,0 / 12	welded		28.15.47
W15Lx28	8	362,5	405	17	ET + 30	5,0 / 10	welded	4253,4	28.15.49
W15Lx28	8	290,5	330	17	ET + 41	5,0 / 10	welded	4253,4	28.15.50
W15Lx28	8	221	275	22	ET - 40	5,0 / 12	welded		28.15.51
W15Lx28	10	281	335	22	ET - 60	5,0 / 12	welded		28.15.52
W15Lx28	8	221	275	22	ET - 50	5,0 / 12	welded		28.15.53
W15Lx28	10	281	335	24	ET - 50	5,0 / 12	welded		28.15.54
W15Lx28	8	221	275	21,5/27	ET - 80	5,0 / 12	welded	5344,8	28.15.55
W15Lx28	8	221	275	20	ET - 80	5,0 / 12	welded	5344,8	28.15.56
W15Lx28	10	281	335	24/35	ET - 22	5,0 / 12	welded		28.15.57
W15Lx28	10	283,5	335	21,5	ET - 54	5,0 / 12	welded		28.15.58
W15Lx28	8	152,4	203,2	17	ET +30	5,0 / 10	lugs	?	28.15.60
W15Lx28	10	281	335	21,5	ET -20	6,0 / 12	welded	?	28.15.61
W15Lx28	5	290	335	21,5/37	ET +60	6,0 / 12	welded	?	28.15.62
W15Lx28	8	140	203,2	21,5	ET -68	6,0 / 12	welded	?	28.15.63
W15Lx28	10	176	225	23	ET +67	5,0 / 15	welded	4650	28.15.64
W15Lx28	8	221	275	22	ET -98	5,0 / 12	welded	?	28.15.65
W15Lx28	8	221	275	22	ET -110	5,0 / 12	welded	?	28.15.66
W15Lx28	5	281	335	24	ET +56	4,5 / 12	lugs	?	28.15.67
W16Lx28	10	281	335	27/32	ET - 58	5,0 / 12	welded	4651,2	28.16.01
W16Lx28	8	221	275	27/332	ET - 105	5,0 / 12	welded		28.16.02
W16Lx28	10	281	335	23	ET - 35	5,0 / 12	welded		28.16.03
W16Lx28	10	281	335	27/32	ET - 40	5,0 / 12	welded	4651,2	28.16.04
W16Lx28	8	221	275	22	ET - 70	5,0 / 12	welded		28.16.05
W16Lx28	10	281	335	24	ET - 70	5,0 / 12	welded	4651,2	28.16.06
W16Lx28	10	281	335	24	ET - 40	5,0 / 12	welded	4651,2	28.16.07
W16Lx28	8	221	275	22	ET -68	5,0 / 12	welded	?	28.16.08



Wheel 30"

Wheel Size	Nb of bolt holes	Central hole diameter	PCD	Bolt hole diameter	Offset	Material thickness	Type of wheel*	Load capacity at 40 km/h	Pronar part no
DW12x30	8	153	203,2	19	ET + 71	5,0 / 10	lugs	2499	30.12.02
DW12x30	8	153	203,2	19/22	ET + 5	5,0 / 10	lugs	2499	30.12.05
DW12x30	8	153	203,2	21,5	ET - 32	5,0 / 10	lugs	2499	30.12.06
DW12x30	8	152,6	203,2	21,5	ET - 32	5,0 / 10	welded		30.12.07
DW12x30	6	161	205	17	ET - 70	5,0 / 10	lugs		30.12.08
DW12x30	8	199	250	24/30	ET +26	4,5 / 12	welded	?	30.12.09
DW12x30	8	221	275	22	ET +88	5,0 / 12	welded	?	30.12.10
DW14Lx30	8	199,5	250	24/30	ET + 125	4,5 / 6	welded		30.14.01
DW14Lx30	8	152,4	203,2	20,5	ET + 135	4,5 / 10	lugs	2652	30.14.07
DW14Lx30	8	152,4	203,2	20,5	ET + 135	4,5 / 10	lugs		30.14.08
DW14Lx30	8	153	203,2	17	ET + 40	4,5 / 10	lugs		30.14.13
DW14Lx30	12	371	425	27/32	ET + 50	5,0 / 10	welded		30.14.14
DW14Lx30	12	371	425	27/32	ET + 50	5,0 / 10	welded	4250	30.14.15
DW14Lx30	12	371	425	27/32	ET + 50	5,0 / 10	welded	4253,4	30.14.21
DW14Lx30	8	221	275	21,5/27	ET 0	4,5 / 12	welded	4500	30.14.22
DW14Lx30	10	281	335	27/32	ET 0	5,0 / 12	welded	4651,2	30.14.23
DW14Lx30	8	221	275	21,5/27	ET - 15	4,5 / 15	welded		30.14.24
DW14Lx30	8	221	275	21,5/27	ET 0	4,5 / 12	welded	4488	30.14.25
DW14Lx30	12	385	430	17	ET + 80	4,5 / 12	multifit		30.14.26
DW14Lx30	8	400	480	17	ET 0	4,5 / 12	welded		30.14.27
DW14Lx30	8	221	275	24/30	ET + 25	4,5 / 12	welded		30.14.28
DW14Lx30	12	390	430	17	ET + 135	4,5 / 10	multifit		30.14.29
DW14Lx30	10	281	335	27/32	ET + 50	5,0 / 12	welded	4651,2	30.14.30
DW14Lx30	8	400	480	17	ET - 70	4,5 / 12	welded		30.14.31
DW15Lx30	10	281	335	23	ET - 58	5,0 / 10	welded		30.15.04
DW15Lx30	10	281	335	24	ET - 67	5,0 / 10	welded	4488	30.15.05
DW15Lx30	8	221	275	21,5/27	ET 0	5,0 / 12	welded	4651,2	30.15.06
W15Lx30	8	152,4	203,2	20,5	ET +134	4,5 / 10	lugs	2499	30.15.07
DW15Lx30	10	281	335	27/32	ET 0	5,0 / 12	welded	4651,2	30.15.08
W15Lx30	8	221	275	24	ET - 90	5,0 / 10	lugs	2723,4	30.15.10
DW15Lx30	8	152,4	203,2	21,5/27	ET + 20	5,0 / 10	lugs		30.15.19
DW15Lx30	12	371	425	27/32	ET - 50	5,0 / 10	welded		30.15.22
DW15Lx30	8	153	203,2	22	ET + 20	5,0 / 10	lugs		30.15.23
DW15Lx30	8	221	275	21,5/27	ET 0	5,0 / 12	welded	4253,4	30.15.24
DW15Lx30	10	281	335	22	ET - 10	5,0 / 10	welded	4651,2	30.15.27
DW15Lx30	8	221	275	21,5/27	ET + 10	5,0 / 10	welded	4651,2	30.15.28
DW15Lx30	10	281	335	27/32	ET 0	5,0 / 14	welded	4998	30.15.29
DW15Lx30	8	152,6	203,2	17	ET - 69,5	5,0 / 10	welded	4488	30.15.30
DW15Lx30	8	153	203,2	17	ET -132,5	5,0 / 10	lugs	2499	30.15.31
DW15Lx30	8	152,6	203,2	17	ET - 69,5	5,0 / 10	welded		30.15.32
DW15Lx30	8	152,6	203,2	19	ET - 34	5,0 / 10	lugs		30.15.33
DW15Lx30	8	181	230	20	ET + 75	5,0 / 10	lugs		30.15.37



Wheels Catalogue

Wheel Size	Nb of bolt holes	Central hole diameter	PCD	Bolt hole diameter	Offset	Material thickness	Type of wheel*	Load capacity at 40 km/h	Pronar part no
DW15Lx30	8	362,5	405	17	ET + 30	5,0 / 10	welded	4488	30.15.38
DW15Lx30	8	152,6	203,2	17	ET - 69,5	5,0 / 10	welded	4488	30.15.39
DW15Lx30	8	152,6	203,2	17	ET - 144,5	5,0 / 10	welded		30.15.40
DW15Lx30	8	153	203,2	17	ET - 69,5	5,0 / 10	lugs		30.15.41
DW15Lx30	12	390	430	17	ET 0	5,0 / 14	multifit		30.15.42
DW15Lx30	8	151	203,2	20	ET + 20	5,0 / 12	welded		30.15.43
DW15Lx30	8	152,6	203,2	??17	ET - 144,5	5,0 / 12	welded	4488	30.15.44
DW15Lx30	8	221	275	21,5/27	ET 0	5,0 / 12	welded		30.15.45
DW15Lx30	8	221	275	21,5/27	ET 0	5,0 / 12	welded	4651,2	30.15.46
DW15Lx30	8	221	275	21,5/27	ET - 75	5,0 / 12	welded	4651,2	30.15.47
DW15Lx30	10	281	335	24	ET - 70	5,0 / 12	welded	4488	30.15.48
DW15Lx30	10	281	335	19	ET - 10	5,0 / 10	crown	2499	30.15.49
DW15Lx30	10	281	335	22	ET + 33	5,0 / 14	welded	4488	30.15.50
DW15Lx30	8	152,4	203,2	20	ET - 16,5	5,0 / 10	lugs		30.15.51
DW15Lx30	8	221	275	21,5/27	ET 0	5,0 / 12	welded	4650	30.15.52
DW15Lx30	8	170	220	27/32	ET -61	5,0 / 12	welded	4487	30.15.53
DW15Lx30	8	386	450	26	ET +23,5	5,0 / 15	welded	?	30.15.56
DW16Lx30	12	371	425	27/32	ET + 50	5,0 / 10	welded	4488	30.16.06
DW16Lx30	8	221	275	27/32	ET 0	5,0 / 12	welded	4651,2	30.16.08
DW16Lx30	8	362	405	18	ET - 20	5,0 / 12	welded		30.16.09
DW16Lx30	12	371	425	24	ET - 20	5,0 / 12	welded		30.16.10
DW16Lx30	10	281	335	22	ET - 25	5,0 / 12	welded		30.16.11
DW16Lx30	10	281	335	22	ET - 80	5,0 / 12	welded		30.16.12
DW16Lx30	10	281	335	22	ET - 60	5,0 / 12	welded		30.16.13
DW16Lx30	10	281	335	22	ET - 25	5,0 / 12	welded		30.16.14
DW16Lx30	10	281	335	22	ET 0	5,0 / 12	welded		30.16.15
DW16Lx30	10	281	335	24	ET - 70	5,0 / 12	welded	4488	30.16.16
DW16Lx30	12	371	425	24	ET - 20	5,0 / 14	welded		30.16.17
DW16Lx30	10	290	335	22	ET - 25	5,0 / 12	welded		30.16.18
DW16Lx30	10	290	335	22	ET - 25	5,0 / 12	welded		30.16.19
DW20Lx30	8	221	275	24/30	ET + 37	5,7 / 12	welded		30.20.03
DW20Lx30	12	385	430	17	ET + 80	5,7 / 12	multifit		30.20.04
DW20Lx30	10	281	335	27/32	ET - 100	6,0 / 12	welded		30.20.05



Wheels 30.5"

Wheel Size	Nb of bolt holes	Central hole diameter	PCD	Bolt hole diameter	Offset	Material thickness	Type of wheel*	Load capacity at 40 km/h	Pronar part no
20,00x30,5H2	10	281	335	27/32	ET 0	7,0 / 14	welded	7150,2	305.20.01
20,00x30,5H2	10	281	335	27/32	ET + 50	7,0 / 14	welded	7150,2	305.20.02
20,00x30,5H2	10	281	335	27/32	ET - 50	7,0 / 14	welded	7150,2	305.20.03
20,00x30,5H2	8	221	275	21,5/27	ET 0	7,0 / 14	welded		305.20.04
20,00x30,5H2	10	281	335	27/32	ET 0	7,0 / 14	welded		305.20.05
20,00x30,5H2	10	281	335	27/32	ET - 100	7,0 / 14	welded	7150,2	305.20.06
20,00x30,5H2	10	281	335	27/32	ET - 85	7,0 / 14	welded	7150,2	305.20.07
20,00x30,5H2	12	390	430	17	ET - 40	7,0 / 14	multifit		305.20.08
20,00x30,5H2	10	281	335	27	ET 0	7,0 / 16	welded	9751,2	305.20.09
20,00x30,5H2	10	281	335	27/32	ET - 50	7,0 / 16	welded	9751,2	305.20.10
20,00x30,5H2	8	221	275	21,5/27	ET - 170	7,0 / 14	welded	7150,2	305.20.11
20,00x30,5H2	8	221	275	21,5/27	ET - 100	7,0 / 14	welded	7150,2	305.20.12
20,00x30,5H2	10	281	335	27/32	ET - 50	7,0 / 14	welded		305.20.13
20,00x30,5H2	8	221	275	21,5/27	ET - 50	7,0 / 14	welded	7150,2	305.20.14
20,00x30,5H2	10	281	335	27/32	ET - 50	7,0 / 16	welded		305.20.15
20,00x30,5H2	10	281	335	27/32	ET 0	7,0 / 16	welded	9751,2	305.20.16
24,00x30,5H2	10	281	335	27/32	ET 0	7,0 / 14	welded	8251,8	305.24.01
24,00x30,5H2	10	281	335	27/32	ET 0	7,0 / 14	welded	8251,8	305.24.02
24,00x30,5H2	10	281	335	27/32	ET - 80	7,0 / 14	welded	7500	305.24.03
24,00x30,5"	10	281	335	27/32	ET - 50	7,0 / 14	welded	8250	305.24.04
24,00x30,5H2	8	221	275	21,5/27	ET 0	7,0 / 14	welded	8250	305.24.05
24,00x30,5H2	10	281	335	27/32	ET + 90	7,0 / 14	welded	7500	305.24.06
24,00x30,5H2	10	281	335	27/32	ET 0	8,0 / 16	welded	11005	305.24.07
24,00x30,5"	10	281	335	27/32	ET -50	8,0 / 16	welded	11005	305.24.08
24,00x30,5H2	10	281	335	27/32	ET 0	8,0 / 16	welded	11005	305.24.09
24,00x30,5"	10	281	335	27/32	ET - 100	7,0 / 14	welded	7500	305.24.10
24,00x30,5H2	12	370	425	26	ET + 60	7,0 / 18	welded		305.24.11
24,00x30,5H2	10	281	335	26	ET +30	7,0 / 14	welded	?	305.24.15
24,00x30,5H2	12	370	425	26	ET +60	7,0 / 18	welded	?	305.24.16
28,00x30,5H2	10	281	335	27/32	ET 0	7,0 / 14	welded	7750	305.28.01
28,00x30,5H2	10	281	335	27/32	ET 0	8,0 / 16	welded	11540	305.28.02
28,00x30,5H2	10	281	335	27/32	ET - 50	8,0 / 16	welded	11540	305.28.03
28,00x30,5H2	10	281	335	27/32	ET - 100	8,0 / 16	welded	11540	305.28.04
28,00x30,5H2	10	281	335	27/32	ET - 120	8,0 / 16	welded	11540	305.28.05
28,00x30,5H2	10	281	335	27/32	ET 0	7,0 / 14	welded	7750	305.28.06



Wheels 32"

Wheel Size	Nb of bolt holes	Central hole diameter	PCD	Bolt hole diameter	Offset	Material thickness	Type of wheel*	Load capacity at 40 km/h	Pronar part no
W7x32	6	161	205	21,5/27	ET +55	4,5 / 10	welded	1836	32.07.01
W7x32	6	285	325	20	ET + 39	4,5 / 10	lugs		32.07.02
W7x32	6	161	205	20	ET + 40	4,5 / 10	welded		32.07.03
W7x32	8	221	275	21,5/27	ET + 56	4,5 / 10	crown		32.07.04
W7x32	8	130			ET + 44	4,5 / 10	lugs		32.07.05
W7x32	8	221	275	24	ET + 106	4,5 / 10	crown		32.07.06
W7x32	6	161	205	20	ET + 40	4,5 / 10	welded		32.07.07
W7x32	8	152,4	203,2	20	ET + 100	4,5 / 10	crown		32.07.08
W8x32	8	221	275	21,5/27	ET + 43	5,0 / 10	welded		32.08.01
W8x32	6	161	205	21,5/27	ET + 22	5,0 / 10	welded	2652	32.08.02
W8x32	8	221	275	21,5/27	ET + 56	4,5 / 12	crown	1836	32.08.05
W8x32	8	152	203,2	19	ET + 56	4,5 / 12	crown	1836	32.08.11
W8x32	12	390	430	17	ET + 56	4,5 / 10	crown	1836	32.08.12
W8x32	6	180	230	20/26	ET + 43	5,0 / 10	welded	2652	32.08.13
W8x32	8	292	330	17	ET + 43	5,0 / 12	welded		32.08.17
W8x32	8	221	275	21,5	ET + 75	5,0 / 12	welded		32.08.18
W8x32	6	161	205	20	ET + 75	5,0 / 12	welded		32.08.19
W8x32	6	180	230	20/25	ET + 96	3,5 / 6	welded	1071	32.08.20
W8x32	8	153	203,2	19	ET - 30	5,0 / 10	welded	2652	32.08.21
W8x32	6	180	230	20/25	ET + 70	3,5 / 6,0	welded	1071	32.08.22
W8x32	6	161	205	21,5/27	ET + 40	4,5 / 10	welded	2244	32.08.23
W8x32	6	161	205	21,5/27	ET + 90	4,5 / 6,0	welded	2244	32.08.24
W8x32	8	221	275	20	ET + 16	4,5 / 12	welded		32.08.25
W8x32	6	161	205	21,5/27	ET 0	4,5 / 10	welded	2350	32.08.26
W8x32	6	161	205	21,5/27	ET + 45	4,5 / 10	welded	2244	32.08.27
W8x32	6	161	205	21,5/27	ET + 70	4,5 / 10	welded	2244	32.08.28
W8x32	6	161	205	21,5/27	ET + 45	4,5 / 10	welded	2244	32.08.29
W8x32	6	161	205	21,5	ET + 70	4,5 / 10	welded	2244	32.08.30
W8x32	6	161	205	21,5/27	ET + 22	4,5 / 10	welded	2652	32.08.31
W8x32	6	161	205	18,5/23,5	ET 0	4,5 / 10	welded		32.08.32
W8x32	6	161	205	18,5/23,5	ET 0	4,5 / 10	welded		32.08.33
W8x32	6	161	205	21,5/27	ET + 55	4,5 / 10	welded	2244	32.08.34
W8x32	8	221	275	21,5/27	ET - 80	5,0 / 10	welded		32.08.35
W8x32	8	221	275	22/27	ET + 70	5,0 / 10	welded	2350	32.08.36
W8x32	6	161	205	21,5/27	ET + 70	3,5 / 6,0	welded	2244	32.08.37
W8x32	6	161	205	21,5/27	ET + 96	3,5 / 6,0	welded	2350	32.08.38
W10x32	12	390	430	17	ET + 56	4,5 / 10	multifit	2142	32.10.06
W10x32	8	221	275	24/32	ET 0	4,5 / 12	welded		32.10.07
W10x32	8	221	275	24/32	ET + 50	4,5 / 12	welded		32.10.08



Wheels Catalogue

Wheel Size	Nb of bolt holes	Central hole diameter	PCD	Bolt hole diameter	Offset	Material thickness	Type of wheel*	Load capacity at 40 km/h	Pronar part no
W10x32	8	221	275	21,5	ET - 284 ?	4,5 / 14	welded	2240	32.10.09
W10x32	8	221	275	21,5/27	ET - 154	4,5 / 14	welded	2240	32.10.10
W10x32	8	362,5	405	17	ET + 65	4,5 / 10	welded	2142	32.10.11
W10x32	8	221	275	24	ET - 26	5,0 / 12	welded		32.10.12
W11x32	8	109	152,4	17	ET + 20	4,5 / 12	lugs		32.11.01
W11x32	8	152,4	203,2	20,5	ET +122	4,5 / 12	lugs	1652,4	32.11.02
W11x32	8	152,4	203,2	19/27	ET +122	4,5 / 12	lugs		32.11.03
W11x32	8	109,5	152,4	19/27	ET + 20	4,5 / 12	lugs		32.11.04
W11x32	8	221	275	21,5/27	ET + 115	5,0 / 14	welded	2652	32.11.06
W11x32	8	161	205	21,5/27	ET 0	4,5 / 10	welded		32.11.07
W11x32	6	161	205	21,5/27	ET 0	4,5 / 10	welded	2652	32.11.08
DW21Ax32	10	281	335	27/32	ET 0	7,3 / 14	welded	6322	32.21.02
DW21Ax32	10	281	335	27/32	ET -50	7,3 / 14	welded	6322	32.21.03
DW21Ax32	10	281	335	27/32	ET 0	7,3 / 14	welded	6322	32.21.06
DW21Ax32	10	281	335	27/32	ET -70	7,3 / 14	welded	6322	32.21.07
DW21Ax32	10	281	335	27/32	ET -50	7,3 / 14	welded	6322	32.21.08
DW21Ax32	8	221	275	27/32	ET -50	7,3 / 14	welded	?	32.21.09
DW21Ax32	8	221	275	27/32	ET +100	7,3 / 14	welded	?	32.21.10
DW21Ax32	10	281	335	27/32	ET -100	7,3 / 14	welded	6322	32.21.11
DW21Bx32	10	281	335	27/32	ET 0	7,0 / 14	welded	6324	32.21.102
DW21Bx32	10	281	335	27/32	ET - 50	7,0 / 14	welded	6324	32.21.103
DW21Bx32	10	281	335	27/32	ET 0	7,0 / 14	welded	6352	32.21.106
DW21Bx32	10	281	335	27/32	ET - 70	7,0 / 14	welded	6352	32.21.107
DW21Bx32	10	281	335	27/32	ET - 50	7,0 / 14	welded	6352	32.21.108
DW21Bx32	8	221	275	27/32	ET - 50	7,0 / 14	welded		32.21.109
DW21Bx32	8	221	275	27/32	ET + 100	7,0 / 14	welded		32.21.110
DW21Bx32	10	281	335	27/32	ET - 100	7,0 / 14	welded	6352	32.21.111
DW21Bx32	10	281	335	27/32	ET - 25	7,0 / 14	welded		32.21.112
DW21Bx32	12	380	430	17	ET - 50	7,0 / 14	multifit	6352	32.21.113
DW21Bx32	10	281	335	27/32	ET -50	7,0 / 14	welded	6322	32.21.114
DW21Bx32	10	281	335	27/32	ET -50	7,0 / 14	welded	6350	32.21.115
W21Bx32	20	281	335	24	ET + 789	7,0 / 16	welded		32.21.128
W21Bx32	20	281	335	24	ET - 381	7,0 / 18	welded		32.21.129
DW27Bx32	10	281	335	27/32	ET 0	7,0 / 14	welded	6997,2	32.27.102
DW27Bx32	10	281	335	27/32	ET - 50	7,0 / 14	welded	6997,2	32.27.103
DW27Bx32	10	281	335	27/32	ET 0	7,0 / 14	welded		32.27.105
DW27Bx32	8	221	275	27/32	ET - 150	7,0 / 14	welded		32.27.109
DW27Bx32	8	221	275	27/32	ET - 50	7,0 / 14	welded		32.27.110
DW27Bx32	8	221	275	27/32	ET - 90	7,0 / 14	welded	6303,6	32.27.111
DW27Bx32	8	214	275	32/36,5	ET - 25	7,0 / 14	welded		32.27.113
DW27Bx32	10	281	335	27/32	ET - 50	7,0 / 14	welded		32.27.114
DW27Bx32	16	446	510	26	ET + 123	7,0 / 15	welded	7000	32.27.115
DW27Bx32	16	446	510	26	ET + 108	7,0 / 15	welded		32.27.116
DW27Bx32	8	221	275	26	ET 0	7,0 / 14	welded		32.27.118
DW27Bx32	10	281	335	27/32	ET - 80	7,0 / 14	welded	6997,2	32.27.120
DW27Bx32	10	280	335	25	ET - 50	7,0 / 14	welded	6997,2	32.27.121



Wheels Catalogue

Wheel Size	Nb of bolt holes	Central hole diameter	PCD	Bolt hole diameter	Offset	Material thickness	Type of wheel*	Load capacity at 40 km/h	Pronar part no
DW27Bx32	10	281	335	27/32	ET - 50	7,0 / 15	welded	7500	32.27.122
DW27Ax32	16	221	275	26	ET + 86	8,0 / 20	welded		32.27.123
DW27Bx32	10	281	335	24	ET 0	7,0 / 16	welded		32.27.124
DW27Bx32	10	281	335	27/32	ET - 100	7,0 / 14	welded		32.27.125
DW27Bx32	10	281	335	27/32	ET + 100	7,0 / 14	welded	6997,2	32.27.126
DW27Bx32	8	221	275	21,5/27	ET 0	7,0 / 14	welded		32.27.127
DW27Bx32	16	221	275	26	ET + 51	8,0 / 20	welded		32.27.128
DW27Bx32	10	281	335	27/32	ET - 80	8,0 / 16	welded	8300	32.27.129
DW27Bx32	10	281	335	27/32	ET 0	8,0 / 16	welded	8300	32.27.130
DW36Bx32	10	281	335	26	ET - 144	8,0 / 18	welded		32.36.01
DW36Ax32	10	281	335	22	ET + 140	8,0 / 18	welded		32.36.02
DW36Bx32	12	370	425	23	ET + 90	8,0 / 18	welded		32.36.03



Wheels 34"

Wheel Size	Nb of bolt holes	Central hole diameter	PCD	Bolt hole diameter	Offset	Material thickness	Type of wheel*	Load capacity at 40 km/h	Pronar part no
W12x34	8	221	275	21,5	ET + 50	4,5 / 12	welded		34.12.01
W14x34	8	222	275	24/30	ET + 28	5,0 / 14	welded		34.14.02
DW14Lx34	10	281	335	25,4/29	ET 0	5,0 / 12	welded		34.14.04
W15Lx34	8	221	430	21,5/27	ET + 100	5,0 / 10	lugs		34.15.01
DW15Lx34	8	199,5	250	24/30	ET + 125	4,5 / 6,0	welded	3304,8	34.15.03
W15Lx34	8	152,4	203,2	19/27	ET - 13	5,0 / 12	lugs	2652	34.15.04
W15Lx34	8	221	275	27/36	ET + 57	5,0 / 12	welded	4488	34.15.05
W15Lx34	8	152,4	203,2	20,5	ET + 129	5,0 / 12	lugs	2652	34.15.06
W15Lx34	8	221	275	24	ET - 100	5,0 / ??	lugs	2723	34.15.20
W15Lx34	8	368	415	24/30	ET + 33,5	5,0 / 12	welded		34.15.21
W15Lx34	8	152,4	203,2	19	ET + 129	5,0 / 12	lugs		34.15.24
DW15Lx34	8	221	275	21,5/27	ET - 50	5,0 / 14	welded	4753,2	34.15.28
W15Lx34	8	221	275	27/36	ET + 95	5,0 / 12	welded	4488	34.15.30
W15Lx34	8	221	275	32/36	ET + 14	5,0 / 10	lugs		34.15.31
DW15Lx34	10	281	335	27/32	ET 0	5,0 / 12	welded	4753,2	34.15.32
DW15Lx34	8	161	205	24	ET - 50	5,0 / 12	welded	4651,2	34.15.33
W15Lx34	8	153	203,2	17	ET + 28	5,0 / 12	lugs	2652	34.15.34
DW15Lx34	8	150,5	203,2	19,8	ET + 45	5,0 / 10	lugs		34.15.35
DW15Lx34	8	221	275	21,5/27	ET 0	5,0 / 14	welded		34.15.36
DW15Lx34	8	221	275	21,5/27	ET 0	5,0 / 14	welded		34.15.37
DW15Lx34	10	281	335	27/32	ET - 50	5,0 / 12	welded		34.15.38
DW15Lx34	8	221	275	21,5/27	ET 0	5,0 / 14	welded	4253,4	34.15.40
DW15Lx34	8	221	275	21,5/27	ET 0	5,0 / 14	welded		34.15.41
DW15Lx34	8	153	203,2	19	??	5,0 / 10	lugs	2652	34.15.42
DW15Lx34	8	221	275	27/32	ET + 14	5,0 / 12	welded		34.15.43
DW15Lx34	8	140	203,2	21,5	ET - 20	5,0 / 12	welded		34.15.45
DW15Lx34	8	152,6	203,2	19	ET - 80,5	5,0 / 12	welded	4651,2	34.15.46
DW15Lx34	8	152,6	203,2	19	ET - 80,5	5,0 / 12	welded		34.15.47
DW15Lx34	8	150,5	203,2	19,8	ET + 45	5,0 / 12	welded		34.15.48
DW15Lx34	10	281	335	27/32	ET + 15	5,0 / 12	welded	4753,2	34.15.52
DW15Lx34	8	221	275	21/27	ET - 50	5,0 / 12	welded		34.15.53
DW15Lx34	8	181	230	20	ET + 10	5,0 / 10	lugs		34.15.54
DW15Lx34	10	281	335	27/32	ET + 30	5,0 / 12	welded		34.15.56
DW15Lx34	12	390	430	17	ET + 100	5,0 / 12	welded		34.15.57
DW15Lx34	8	221	275	21,5/27	ET 0	5,0 / 12	welded		34.15.58
DW15Lx34	8	152,6	203,2	19	ET - 60	5,0 / 12	welded		34.15.59
DW15Lx34	8	152,6	203,2	19	ET - 80,5	5,0 / 12	welded	4651,2	34.15.60
DW15Lx34	8	152,4	203,2	19/27	ET - 38	5,0 / 12	lugs		34.15.61
DW15Lx34	12	390	430	17	ET + 153	5,0 / 10	multifit		34.15.62
DW15Lx34	??							2652	34.15.63
DW15Lx34	12	390	430	17	ET - 30	5,0 / 12	multifit		34.15.64
DW15Lx34	8	152,4	203,2	19	ET + 25	5,0 / 10	lugs		34.15.65
DW15Lx34	8	152,6	203,2	19	ET - 80,5	5,0 / 12	welded		34.15.66



Wheels Catalogue

Wheel Size	Nb of bolt holes	Central hole diameter	PCD	Bolt hole diameter	Offset	Material thickness	Type of wheel*	Load capacity at 40 km/h	Pronar part no
DW15Lx34	8	140	203,2	21,5	ET - 100	5,0 / 12	welded		34.15.67
DW15Lx34	8	152,6	203,2	19	ET - 55	5,0 / 12	welded	4651,2	34.15.68
DW15Lx34	10	281	335	27/32	ET + 50	5,0 / 12	welded	?	34.15.69
DW15Lx34	8	221	275	21,5/27	ET + 15	5,0 / 12	welded	4651,2	34.15.70
DW15Lx34	8	221	275	27/32	ET + 14	5,0 / 12	welded		34.15.71
DW15Lx34	8	199,5	250	24/30	ET + 104	5,0 / 14	welded		34.15.72
DW15Lx34	8	221	275	21,5	ET - 30	5,0 / 10	lugs	2723,4	34.15.73
DW15Lx34	8	181	230	21	ET + 10	5,0 / 10	lugs		34.15.74
DW15Lx34	8	152,4	203,2	19/27	ET + 84	5,0 / 12	lugs		34.15.75
DW15Lx34	8	140	203,2	20	ET + 84	5,0 / 12	lugs		34.15.76
DW15Lx34	8	150,5	203,2	20	ET + 84	5,0 / 12	lugs		34.15.77
DW15Lx34	8	152,6	203,2	19	ET - 15	5,0 / 12	crown	2723,4	34.15.78
W15Lx34	8	150,5	203,2	20	ET - 60	5,0 / 12	welded		34.15.79
DW15Lx34	10	281	335	24	ET 0	5,0 / 16	welded		34.15.80
DW15Lx34	8	152,6	203,2	19	ET - 30,5	5,0 / 12	welded		34.15.81
DW15Lx34	8	153	203,2	19	ET - 60	5,0 / 12	lugs		34.15.82
DW15Lx34	10	395	450	22	ET + 50	5,0 / 16	welded		34.15.83
DW15Lx34	8	221	275	21/27	ET -100	5,0 / 12	welded		34.15.84
DW15Lx34	8	152,6	203,2	19	ET - 55	5,0 / 12	welded	4651,2	34.15.85
W15Lx34	8	152,4	203,2	21,5/??	ET + 80	5,0 / 12	lugs	2652	34.15.86
DW15Lx34	8	221	275	27/32	ET + 15	5,0 / 12	welded	4651,2	34.15.87
W15Lx34	8	150,5	203,2	20	ET -130	5,0 / 12	welded	4488	34.15.88
W15Lx34	8	152,4	203,2	19/27	ET + 129	5,0 / 12	lugs	2652	34.15.89
DW15Lx34	10	281	335	27/32	ET + 90	5,0 / 12	welded	4750	34.15.90
W15Lx34	8	152,4	203,2	19/27	ET - 40	5,0 / 12	welded	4550	34.15.91
DW15Lx34	8	152,4	203,4	19	ET - 30	5,0 / 10	lugs		34.15.92
W15Lx34	8	221	275	21,5	ET - 30	5,0 / 12	welded	4700	34.15.93
DW16Lx34	8	199,5	250	24/30	ET + 68	5,0 / 14	welded	4625	34.16.03
W16Lx34	8	221	275	24	ET + 57	5,0 / 12	welded		34.16.06
DW16Lx34	8	221	275	24	ET - 48	6,0 / 14	welded	5610	34.16.07
DW16Lx34	10	281	335	27/32	ET + 35	5,0 / 12	welded	4651,2	34.16.08
DW16Lx34	8	152,6	203,2	19	ET - 47,5	5,0 / 12	welded	4651,2	34.16.09
DW16Lx34	12	368	420	24	ET - 60	5,0 / 12	welded		34.16.10
DW16Lx34	8	170	220	27/32	ET - 61	6,0 / 14	welded	5508	34.16.11
DW16Lx34	8	170	220	27/32	ET - 61	5,0 / 12	welded		34.16.12
DW16Lx34	8	152,6	203,2	19	ET - 47,5	5,0 / 12	welded	4651,2	34.16.13
DW16Lx34	8	152,6	203,2	19	ET - 70	5,0 / 12	welded	4651,2	34.16.14
DW16Lx34	8	199,5	250	24/30	ET + 125	4,0 / 6,0	welded		34.16.15



Wheels Catalogue

Wheel Size	Nb of bolt holes	Central hole diameter	PCD	Bolt hole diameter	Offset	Material thickness	Type of wheel*	Load capacity at 40 km/h	Pronar part no
DW16Lx34	8	221	275	21,5/27	ET - 48	5,0 / 12	welded	4651,2	34.16.16
DW16Lx34	12	368	415	24/30	ET + 33,5	5,0 / 12	welded		34.16.17
DW16Lx34	8	368	415	24/30	ET + 33,5	5,0 / 12	welded		34.16.18
DW16Lx34	8	152,6	203,2	19	ET - 70	5,0 / 12	welded	4651,2	34.16.19
DW16Lx34	8	152,6	203,2	19	ET - 56,5	5,0 / 12	welded		34.16.20
DW16Lx34	8	152,6	203,2	19	ET - 70	5,0 / 12	welded	4651,2	34.16.21
DW16Lx34	8	221	275	24	ET - 48	5,0 / 12	welded	4700	34.16.22
DW16Lx34	8	221	275	27/32	ET 0	5,0 / 12	welded	4700	34.16.23
DW18Lx34	8	149,7	203,2	19,8	ET +36	6,0 / 14	welded	3518	34.18.01
DW18Lx34	8	221	275	21,5	ET -50	6,0 / 14	welded	5608	34.18.05
DW18Lx34	8	152,4	203,2	19	ET -80	6,0 / 12	lugs	?	34.18.06
DW18Lx34	10	281	335	23	ET -75	6,0 / 16	welded	?	34.18.07
DW18Lx34	8	152,4	203,2	19	ET -25	6,0 / 12	lugs	?	34.18.08
DW18Lx34	8	152,4	203,2	21,5	ET -50	6,0 / 12	lugs	?	34.18.09
DW18Lx34	8	386	450	26	ET -48	6,0 / 16	welded	5996	34.18.10
DW20Bx34	10	281	335	27/32	ET 0	7,0 / 14	welded	5800	34.20.01
DW20Bx34	10	281	335	27/32	ET - 50	7,0 / 14	welded		34.20.02
DW23Bx34	10	281	335	27/32	ET - 40	7,0 / 14	welded		34.23.101
DW23Bx34	10	281	335	25,4	ET - 70	7,0 / 14	welded		34.23.102
DW23Bx34	10	281	335	25,4	ET - 15	7,0 / 14	welded		34.23.103
DW23Bx34	10	281	335	27/32	ET 0	7,0 / 14	welded	5650	34.23.104
DW23Bx34	10	281	335	27/32	ET - 50	7,0 / 14	welded	5000	34.23.105



Wheels 36"

Wheel Size	Nb of bolt holes	Central hole diameter	PCD	Bolt hole diameter	Offset	Material thickness	Type of wheel*	Load capacity at 40 km/h	Pronar part no
W7x36"	6	161	205	21,5/27	ET + 70	4,5 / 10	welded	2652	36.07.01
W7x36"	8	221	275	21,5/27	ET + 70	4,5 / 10	welded	2652	36.07.02
W7x36"	6	161	205	21,5/27	ET + 40	4,5 / 12	welded	2652	36.07.03
W7x36"	8	221	275	24/32	ET + 40	4,5 / 12	welded		36.07.04
W7x36"	6	161	205	20	ET + 40	4,5 / 12	welded	2652	36.07.05
W7x36"	6	161	205	21,5	ET + 70	4,5 / 12	welded	2652	36.07.06
W7x36"	8	153	203,2	19	ET - 30	4,5 / 12	welded	2652	36.07.07
W7x36"	6	161	205	21,5/27	ET + 70	4,5 / 10	welded	2652	36.07.08
W8x36"	8	170	220	27/32	ET + 88,6	4,5 / 8	lugs	1326	36.08.05
W8x36"	6	161	205	21,5/27	ET + 50	5,0 / 12	welded	2652	36.08.08
W8x36"	8	221	275	21,5/27	ET + 70	5,0 / 12	welded	2652	36.08.09
W8x36"	8	221	275	21,5	ET 0	4,5 / 10	welded		36.08.10
W8x36"	8	152	330	19	?	4,5 / 12	crown	1938	36.08.14
W8x36"	8	223	275	21,5/27	ET + 14	5,0 / 12	welded	2652	36.08.17
W8x36"	10	281	335	24	ET + 70	5,0 / 12	welded	2652	36.08.21
W8x36"	6	161	205	21,5/27	ET + 70	5,0 / 12	welded	2652	36.08.22
W8x36"	6	161	205	21,5/27	ET 0	5,0 / 12	welded		36.08.23
W8x36"	10	281	335	24	?	4,5 / 12	crown		36.08.24
W8x36"	6	161	205	21,5/27	ET 0	5,0 / 12	welded		36.08.25
W8x36"	10	281	335	27/32	ET - 100	5,0 / 12	welded		36.08.26
W8x36"	8	221	275	24/32	ET + 40	5,0 / 12	welded		36.08.27
W8x36"	6	161	205	20	ET + 15	5,0 / 12	welded		36.08.28
W8x36"	8	221	275	22	ET + 75	5,0 / 12	welded		36.08.29
W8x36"	6	161	205	20	ET + 75	5,0 / 12	welded		36.08.30
W8x36"	8	221	275	20	ET + 16	5,0 / 12	welded		36.08.31
W8x36"	6	161	205	17	ET - 65	4,5 / 10	lugs		36.08.32
W8x36"	8	170	220	24	ET - 65	4,5 / 10	lugs		36.08.33
W8x36"	8	221	275	21,5/27	ET + 30	5,0 / 12	welded	2652	36.08.34
W8x36"	8	152,6	203,2	21,5/27	ET - 30	5,0 / 12	welded	2652	36.08.35
W8x36"	6	161	205	21,5/27	ET + 60	5,0 / 12	welded	2650	36.08.36
W8x36"	6	161	205	21,5/27	ET + 90	5,0 / 12	welded	2652	36.08.37
W8x36"	5	98	140	14	ET + 125	4,5 / 6	welded		36.08.38
W8x36"		151			ET - 65	4,5 / 10	lugs		36.08.39

Wheel Size	Nb of bolt holes	Central hole diameter	PCD	Bolt hole diameter	Offset	Material thickness	Type of wheel*	Load capacity at 40 km/h	Pronar part no
W8x36"	6	161	205	21,5 / 27	ET 0	4,5 / 10	welded	1900	36.08.40
W10x36"	8	152,6	203,2	19	ET - 17,5	5,0 / 12	welded	2600	36.10.01
W10x36"	10	390	430	17	ET + 100	4,5 / 10	crown		36.10.02
W11x36"	8	221	275	21,5	ET 0	5,0 / 10	welded		36.11.06
W11x36"	6	161	205	21,5/27	ET 0	5,0 / 12	welded	2499	36.11.07
W11x36"	8	221	275	21,5/27	ET 0	5,0 / 10	welded	2499	36.11.08
W11x36"	8	152,4	203,2	19	?	4,5 / 12	lugs		36.11.09
W11x36"	8	223	275	21,5/27	ET + 14	4,5 / 12	welded	2240	36.11.12
W11x36"	8	221	275	21,5	ET + 100	5,0 / 10	welded		36.11.13
W12x36"	8	152,4	203,2	21	ET + 125	4,5 / 12	lugs	1897,2	36.12.01
W12x36"	8	153	203,2	21,5/32	ET + 21,5	4,5 / 10	lugs		36.12.03



Wheels 38"

Wheel Size	Nb of bolt holes	Central hole diameter	PCD	Bolt hole diameter	Offset	Material thickness	Type of wheel*	Load capacity at 40 km/h	Pronar part no
W8x38	10	281	335	24	ET + 75	4,5 / 12	crown		38.08.01
W8x38	8	221	275	21,5/27	ET + 110	4,5 / 12	crown		38.08.02
W10x38	8	152	203,2	19	ET + 95	4,5 / 12	lugs		38.10.02
W10x38	8	221	275	21,5/27	ET + 70	4,5 / 12	welded		38.10.03
W10x38	8	223	275	27/32	ET + 33	4,5 / 12	welded		38.10.04
W10x38	8	153	203,2	19/24	ET - 70	4,5 / 10	welded	2120	38.10.05
W10x38	6	161	205	20	ET + 75	4,5 / 12	welded	1700	38.10.06
W10x38	8	221	275	22	ET + 20	4,5 / 12	welded	1700	38.10.07
W10x38	12	390	430	17	ET - 14	4,5 / 14	multifit		38.10.08
W10x38	8	153	203	19/24	ET - 70	4,0 / 8,0	welded	1900	38.10.09
W10x38	8	221	275	22	ET + 75	4,5 / 12	welded		38.10.10
W10x38	8	221	275	22	ET + 88	4,5 / 12	welded		38.10.11
W10x38	8	221	275	22	ET + 63	4,5 / 12	welded		38.10.12
W10x38	6	161	205	20	ET - 50	4,5 / 12	welded		38.10.13
W10x38	8	221	275	21,5	ET + 105	4,5 / 12	welded		38.10.14
W10x38	8	153	203,2	17	ET + 40	4,5 / 10	welded	1900	38.10.15
W10x38	12	371	425	27/32	ET + 96	4,5 / 12	welded		38.10.16
W10x38	8	221	275	22/27	ET + 20	4,5 / 12	welded	1700	38.10.17
W10x38	6	161	205	20/27,5	ET + 75	4,5 / 12	welded	1700	38.10.18
DW11Lx38	8	199,5	250	24/30	ET + 125	4,5 / ?	welded	2499	38.11.03
DW11x38	8	221	275	21,5/27	ET - 95	5,0 / 12	welded	2499	38.11.04
DW12x38	8	152,4	203,2	20,5	ET + 75	5,0 / 12	lugs	2652	38.12.02
DW12x38	6	161	205	24	ET 0	4,5 / 12	welded		38.12.05
DW12x38	8	221	275	21,5/27	ET + 70	4,5 / 10	welded	3468	38.12.06
DW12x38	8	152,4	203,2	19	ET + 75	5,0 / 12	lugs		38.12.07
DW12x38	8	221	275	21,5 / 27	ET + 100	5,0 / 12	crown	3366	38.12.10
DW12x38	12	390	430	17	ET + 110	5,0 / 12	multifit	2650	38.12.11
DW12x38	8	221	275	21 / 27	ET - 110	4,5 / 12	welded		38.12.12
DW12x38	6	161	205	24	ET 0	4,5 / 12	welded		38.12.13
DW12x38	8	221	275	21,5	ET + 70	4,5 / 10	welded	3468	38.12.14
DW12x38	8	221	275	21,5/27	ET - 25	4,5 / 10	welded		38.12.15
W12x38	8	153	203,2	19	ET - 225	5,0 / 12	crown		38.12.16
W12x38	8	153	203,2	20	ET - 135	5,0 / 12	crown		38.12.17
DW12x38	8	221	275	21,5/27	ET + 100	4,5 / 12	crown	3150	38.12.18
DW12x38	8	152	203,2	19	ET -32	4,5 / 12	lugs	3150	38.12.19
DW12x38	8	221	275	21,5/27	ET -100	4,5 / 10	welded	?	38.12.20
DW12x38	6	161	205	21,5	ET -30	4,5 / 10	welded	3550	38.12.21
DW12x38	8	152,4	203,2	20	ET -80	5,0 / 12	lugs	3150	38.12.22
DW14Lx38	8	199,5	250	24/30	ET + 125	4,5 / 6,0	welded	2499	38.14.01
DW14Lx38	8	221	275	27/32	ET + 110	5,0 / 12	welded	3672	38.14.02
DW14Lx38	8	221	275	21,5/27	ET + 20	5,0 / 12	welded	2805	38.14.03
DW14Lx38	8	221	275	21,5/27	ET + 20	5,0 / 12	welded	3672	38.14.06



Wheels Catalogue

50

Wheel Size	Nb of bolt holes	Central hole diameter	PCD	Bolt hole diameter	Offset	Material thickness	Type of wheel*	Load capacity at 40 km/h	Pronar part no
DW14Lx38	8	221	275	21,5/27	ET + 70	5,0 / 10	welded		38.14.07
DW14Lx38	8	221	275	21,5/27	ET + 100	5,0 / 12	welded		38.14.08
DW14Lx38	8	223	275	21,5/27	ET + 14	5,0 / 12	welded		38.14.09
DW14Lx38	8	221	275	21,5/27	ET + 80	5,0 / 12	welded	3672	38.14.10
	8	221	275	21,5/27	ET - 70	5,0 / 12	welded		38.14.12
IT02291970354	8	199,5	250	24/30	ET + 125	5,0 / 7,0	welded	2805	38.15.01
DW15Lx38	8	199,5	250	24/30	ET + 125	4,5 / 6,0	welded		38.15.06
DW15Lx38	8	199,5	250	24/30	ET + 125	5,0 / 7,0	welded		38.15.10
DW15Lx38	8	221	275	27/32	ET + 30	5,0 / 14	welded		38.15.16
W15Lx38	8	221	275	27/32	ET + 75	5,0 / 12	lugs		38.15.18
DW15Lx38	8	221,5	275	27/32	ET - 98,5	5,0 / 14	welded		38.15.19
DW15Lx38	8	221	275	21,5/27	ET 0	6,0 / 14	welded	5610	38.15.25
DW15Lx38	8	221	275	27/32	ET + 12	5,0 / 12	welded		38.15.26
DW15Lx38	8	221	275	21,5/27	ET - 60	5,0 / 12	crown	2805	38.15.27
DW15Lx38	8	199,5	250	24/30	ET + 68,5	5,0 / 14	welded		38.15.28
DW15Lx38	8	221	275	21,5/27	ET + 100	5,0 / 12	welded	4651,2	38.15.29
DW15Lx38	8	153	203,2	19	ET + 28	5,0 / 12	lugs	3162	38.15.30
DW15Lx38	10	281	335	27/32	ET 0	5,0 / 14	welded		38.15.31
DW15Lx38	8	221	275	21,5/27	ET + 50	5,0 / 12	welded		38.15.32
DW15Lx38	10	281	335	27/32	ET - 50	5,0 / 14	welded	4651,2	38.15.33
DW15Lx38	8	221	275	21,5	ET - 100	5,0 / 12	lugs	3162	38.15.34
DW15Lx38	10	281	335	27/32	ET 0	6,0 / 14	welded	6507,6	38.15.35
DW15Lx38	10	281	335	27/32	ET 0	6,0 / 14	welded	6507,6	38.15.36
DW15Lx38	10	281	335	27/32	ET 0	5,0 / 14	welded	4080	38.15.37
DW15Lx38	8	221	275	21,5/27	ET 0	5,0 / 12	crown		38.15.38
DW15Lx38	8	139,7	203,2	19	ET + 20	5,0 / 12	welded		38.15.39
DW15Lx38	12	385	430	17	ET + 100	5,0 / 14	multifit		38.15.40
DW15Lx38	10	281	335	27/32	ET 0	5,0 / 14	welded	4080	38.15.41
DW15Lx38	8	221	275	21,5/27	ET 0	5,0 / 14	welded	4080	38.15.42
DW15Lx38	8	221	275	21,5	ET - 100	5,0 / 12	welded	4651,2	38.15.43
DW15Lx38	12	390	430	17	ET - 151	5,0 / 12	multifit		38.15.44
DW15Lx38	12	385	430	17	ET - 75	5,0 / 14	multifit		38.15.45
DW15Lx38	10	281	335	27/32	ET + 50	5,0 / 14	welded	4651,2	38.15.46
DW15Lx38	8	221	275	21,5	ET - 70	5,0 / 14	welded		38.15.47
DW15Lx38	8	221	275	21,5/27	ET 0	6,0 / 14	welded	5610	38.15.48
DW15Lx38	8	221	275	21,5/27	ET - 70	5,0 / 12	welded		38.15.49
DW15Lx38	10	281	335	27/32	ET 0	6,0 / 16	welded		38.15.50
DW15Lx38	10	281	335	27/32	ET - 25	6,0 / 16	welded		38.15.51
DW15Lx38	8	152,4	203,2	19,5	ET - 32	5,0 / 12	crown		38.15.52
DW15Lx38	8	152,4	203,2	21	ET + 30	5,0 / 12	crown		38.15.53
DW15Lx38	8	221	275	24	ET - 50	5,0 / 12	welded		38.15.54
DW16Lx38	8	221	275	24	ET - 98	5,0 / 14	welded		38.16.03



Wheel Size	Nb of bolt holes	Central hole diameter	PCD	Bolt hole diameter	Offset	Material thickness	Type of wheel*	Load capacity at 40 km/h	Pronar part no
DW16Lx38	8	221	275	24	ET - 65	5,0 / 14	welded	4651,2	38.16.04
DW16Lx38	8	221	275	27/32	ET - 68,5	5,0 / 14	welded	4651,2	38.16.06
DW16Lx38	8	221	275	27/32	ET - 101	5,0 / 14	welded	4651,2	38.16.07
DW16Lx38	8	221	275	21,5	ET 0	6,0 / 14	welded	5600	38.16.11
DW16Lx38	8	199,5	250	24/30	ET 0	6,0 / 14	welded		38.16.16
DW16Lx38	8	221	275	24	ET + 52	6,0 / 14	welded		38.16.19
DW16Lx38	12	385	430	17	ET - 75	6,0 / 14	multifit		38.16.24
DW16Lx38	8	140	203,2	18,5	ET - 40	5,0 / 14	welded	4488	38.16.25
DW16Lx38	8	221	275	21,5	ET - 80	5,0 / 12	welded	4488	38.16.26
DW16Lx38	8	152,4	203,2	20	ET - 120	5,0 / 12	welded		38.16.27
DW16Lx38	8	152,6	203,2	19	ET - 28,5	5,0 / 14	welded	4550	38.16.28
DW16Lx38	10	281	335	27/ 32	ET + 30	6,0 / 14	welded		38.16.29
DW16Lx38	10	281	335	27/32	ET + 80	6,0 / 14	welded		38.16.30
DW16Lx38	8	140	203,2	21	ET + 172	6,0 / 12	lugs		38.16.31
DW16Lx38	8	152,6	203,2	19	ET - 28,5	5,0 / 12	welded	4488	38.16.33
DW16Lx38	8	221,5	275	27/32	ET - 98,5	5,0 / 14	welded		38.16.34
DW16Lx38	8	221	275	27/32	ET - 98,5	5,0 / 12	welded		38.16.35
DW16Lx38	8	152,6	203,2	19	ET - 51	5,0 / 12	welded	4488	38.16.36
DW16Lx38	8	140	203,2	20	ET - 40	5,0 / 14	welded	4488	38.16.37
DW16Lx38	8	221	275	27/32	ET + 26	5,0 / 14	welded		38.16.38
DW16Lx38	8	152,6	203,2	19	ET - 51	5,0 / 12	welded	4488	38.16.39
DW16Lx38	8	152,6	203,2	19	ET - 51	5,0 / 12	welded	4488	38.16.40
DW16Lx38	10	281	335	27/32	ET - 50	6,0 / 14	welded		38.16.41
DW16Lx38	8	152,6	203,2	19	ET - 51	5,0 / 14	welded	4488	38.16.42
DW16Lx38	10	281	335	27/32	ET 0	6,0 / 14	welded		38.16.43
DW16Lx38	8	221	275	27/32	ET - 48	5,0 / 14	welded	4651,2	38.16.44
DW16Lx38	8	221	275	23	ET - 98	5,0 / 14	welded	4700	38.16.45
DW18Lx38	8	221	275	27/32	ET - 50	5,0 / 14	welded		38.18.03
DW18Lx38	10	335	580	27/32	ET - 50	7,0 / 14	welded	7109,4	38.18.05
DW18Lx38	10	281	335	27/32	ET 0	6,0 / 14	welded	7109,4	38.18.06
DW18Lx38	8	221,5	275	27/32	ET - 98,5	6,0 / 14	welded	7109,4	38.18.18
DW18Lx38	8	221	275	24	ET - 12	6,0 / 14	welded	7109,4	38.18.19
DW18Lx38	8	221,5	275	24	ET - 65	6,0 / 14	welded		38.18.20
DW18Lx38	10	281	335	27/32	ET - 45	6,0 / 14	welded	7109,4	38.18.22
DW18Lx38	12	385	430	17	ET - 75	6,0 / 14	multifit		38.18.23
DW18Lx38	10	281	335	27/32	ET 0	6,0 / 14	welded		38.18.24
DW18Lx38	8	221,5	275	24	ET - 59	6,0 / 14	welded	7109,4	38.18.25
DW18Lx38	8	221	275	22	ET - 70	6,0 / 14	welded	7109,4	38.18.27
DW18Lx38	8	221	275	22	ET - 25	6,0 / 14	welded	7109,4	38.18.28
DW18Lx38	8	140	203,2	20	ET - 25	6,0 / 14	welded	7109,4	38.18.29
DW18Lx38	8	221,5	275	27/32	ET - 130	6,0 / 14	welded		38.18.30
DW18Lx38	10	275	335	24	ET + 15	6,0 / 14	welded		38.18.31



Wheel Size	Nb of bolt holes	Central hole diameter	PCD	Bolt hole diameter	Offset	Material thickness	Type of wheel*	Load capacity at 40 km/h	Pronar part no
DW18Lx38	10	281	335	24	ET - 20	6,0 / 12	welded	5610	38.18.32
DW18Lx38	8	152,4	203,2	22	ET - 120	6,0 / 14	welded		38.18.33
DW18Lx38	8	221,5	275	27/32	ET - 50	6,0 / 14	welded		38.18.34
DW18Lx38	8	221	275	27/32	ET - 80	6,0 / 14	welded		38.18.35
DW18Lx38	8	221	275	24	ET - 98	6,0 / 14	welded		38.18.36
DW18Lx38	10	281	335	27/32	ET - 50	6,0 / 14	welded	7109,4	38.18.39
DW18Lx38	8	221	275	24	ET - 98	6,0 / 14	welded		38.18.41
DW18Lx38	10	431	485	24	ET + 50	6,0 / 14	welded		38.18.42
DW18Lx38	8	152,4	203,2	24	ET - 175	6,0 / 14	welded		38.18.43
DW18Lx38	8	221,5	275	27/32	ET 0	6,0 / 14	welded		38.18.44
DW18Lx38	10	281	335	27/32	ET - 45	7,0 / 14	welded		38.18.45
DW18Lx38	8	140	203,2	20	ET - 25	6,0 / 14	welded	7109,4	38.18.46
DW18Lx38	8	221	275	22	ET - 70	6,0 / 14	welded	7109,4	38.18.47
DW18Lx38	8	221	275	24	ET 0	6,0 / 14	welded		38.18.48
DW18Lx38	12	390	430	17	ET - 137	6,0 / 12	multifit		38.18.49
DW18Lx38	8	152,4	203,2	19	ET - 51	6,0 / 14	welded		38.18.50
DW18Lx38	10	281	335	27/32	ET - 70	6,0 / 14	welded		38.18.51
DW18Lx38	8	221,5	275	27/32	ET - 60	6,0 / 14	welded		38.18.52
DW18Lx38	10	281	335	27/32	ET - 50	6,0 / 14	welded	7109,4	38.18.53
DW18Lx38	8	221	275	24	ET - 33	6,0 / 14	welded	7109,4	38.18.54
DW18Lx38	10	281	335	27/32	ET - 45	7,0 / 16	welded		38.18.55
DW18Lx38	8	152,4	203,2	21	ET - 136	6,0 / 12	lugs		38.18.56
DW18Lx38	8	221	275	27/32	ET - 48	6,0 / 14	welded		38.18.57
DW18Lx38	8	221	275	21,5	ET 0	6,0 / 14	welded		38.18.58
DW18Lx38	10	281	335	26/32	ET 0	7,0 / 14	welded		38.18.59
DW18Lx38	10	281	335	26/32	ET - 45	7,0 / 14	welded		38.18.60
DW18Lx38	8	152,4	203,2	21	ET - 20	6,0 / 12	crown		38.18.61
DW18Lx38	8	152,4	203,2	21	ET -20	6,0 / 12	welded	?	38.18.62
DW18Lx38	8	221	275	24	ET -65	6,0 / 14	welded	?	38.18.63
DW18Lx38	8	221	275	24	ET -115	6,0 / 14	welded	?	38.18.64
DW18Lx38	8	221	275	24	ET -105	6,0 / 14	welded	?	38.18.65
DW18Lx38	8	221	275	21	ET -70	6,0 / 12	lugs	?	38.18.66
DW20Bx38	8	221	275	24	ET - 70	6,0 / 14	welded	6528	38.20.01
DW20Bx38	8	221	275	24	ET - 70	6,0 / 14	welded		38.20.02
DW20Bx38	8	221	275	21,5	ET - 90	6,0 / 14	welded		38.20.03
DW20Bx38	8	140	203,2	20	ET - 25	6,0 / 14	welded		38.20.04
DW20Bx38	8	281	335	24	ET - 20	6,0 / 14	welded		38.20.05
DW20Bx38	10	281	335	27	ET + 70	6,0 / 14	welded		38.20.06
DW20Bx38	8	221	275	24	ET + 13	6,0 / 14	welded		38.20.07
DW20Bx38	12	390	430	17	ET - 145	6,0 / 14	multifit		38.20.08
DW20Bx38	10	281	335	27	ET 0	7,0 / 16	welded		38.20.09
DW23Ax38	10	281	335	27	ET - 50	7,0 / 14	welded	8262	38.23.02
DW23Ax38	8	221	275	24	ET - 70	7,0 / 14	welded	8262	38.23.03
DW23Ax38	10	281	335	27/32	ET 0	7,0 / 14	welded	8262	38.23.04
DW23Ax38	10	281	335	27/32	ET - 50	7,0 / 14	welded	8262	38.23.05
DW23x38	12	390	430	17	ET - 145	7,0 / 14	multifit		38.23.06
DW23Ax38	12	370	425	26	ET + 90	7,0 / 18	welded		38.23.07



Wheels Catalogue

53

Wheel Size	Nb of bolt holes	Central hole diameter	PCD	Bolt hole diameter	Offset	Material thickness	Type of wheel*	Load capacity at 40 km/h	Pronar part no
DW23Ax38	10	281	335	27/32	ET - 50	7,0 / 14	welded	8262	38.23.09
DW23Ax38	10	281	335	27/32	ET - 100	7,0 / 14	welded	8262	38.23.10
DW23Bx38	10	281	335	27/32	ET - 40	7,0 / 14	welded	8250	38.23.08
DW23Bx38	10	281	335	27/32	ET -45	8,0 / 18	welded	9000	38.23.13



Wheels 42"

Wheel Size	Nb of bolt holes	Central hole diameter	PCD	Bolt hole diameter	Offset	Material thickness	Type of wheel*	Load capacity at 40 km/h	Pronar part no
W8x42	8	160	220	27/32	ET + 70	4,5 / 8	welded	1275	42.08.01
W8x42	8	199,5	250	24/30	ET + 80	4,5 / 8	welded	2550	42.08.03
W8x42	8	221	275	24/30	ET - 50	4,5 / 8	welded	2550	42.08.04
W8x42	6	161	205	21,5/27	ET 0	4,5 / 8	welded	2550	42.08.05
W8x42	8	221	275	21,5/27	ET + 100	4,5 / 8	welded		42.08.06
W8x42	8	221	275	24/30	ET + 60	4,5 / 8	welded	2550	42.08.07
W8x42	8	221	275	27/32	ET + 64	4,5 / 8	welded		42.08.09
W8x42	8	281	335	21,5	ET 0	5,0 / 14	welded		42.08.10
W8x42	6	161	205	21,5/27	ET + 22	4,5 / 10	welded		42.08.11
W8x42	8	223	275	27/32	ET + 33	4,5 / 8	welded		42.08.12
W8x42	6	161	205	21,5/27	ET + 60	4,5 / 12	welded	2652	42.08.13
W8x42	6	161	205	21,5/27	ET 0	4,5 / 10	welded		42.08.14
W8x42	8	171	220	27/32	ET + 70	4,5 / 8	welded	2550	42.08.15
W8x42	6	161	205	21,5/27	ET + 38	4,5 / 12	welded		42.08.16
W8x42	8	221	275	21,5/34	ET + 100	4,5 / 8	welded		42.08.17
W8x42	8	199,5	250	24/30	ET + 125	5,0 / 8	welded	2550	42.08.18
W8x42	10	281	335	27/32	ET + 100	4,5 / 8	welded	2550	42.08.19
W8x42	8	160	220	27/32	ET + 70	4,5 / 8	welded	2550	42.08.20
W8x42	8	153	203	20.5	ET + 100	4,5 / 8	welded		42.08.21
W8x42	8	223	275	21,5/27	ET + 33	4,5 / 8	welded	2550	42.08.22
W8x42	8	199,5	250	16/20	ET + 127	4,5 / 6	welded	1275	42.08.23
W8x42	8	199,5	250	24/30	ET + 125	4,5 / 6	welded	2550	42.08.24
W8x42	12	390	430	17	ET - 14	5,0 / 14	multifit		42.08.25
W8x42	6	161	205	16/20	ET + 125	4,5 / 6	welded		42.08.26
W8x42	8	199,5	250	24/30	ET + 125	4,5 / 6	welded	1275	42.08.27
W8x42	6	161	205	20	ET + 75	4,5 / 12	welded	2652	42.08.28
W8x42	6	161	205	20	ET - 50	4,5 / 12	welded	2652	42.08.29
W8x42	8	221	275	22	ET + 20	4,5 / 12	welded	2652	42.08.30
W8x42	8	221	275	22	ET + 75	4,5 / 12	welded	2652	42.08.31
W8x42	8	221	275	21/27	ET + 124	4,5 / 8	welded	2652	42.08.32
W8x42	6	221	275	21,5/27	ET + 150	4,5 / 12	crown		42.08.33
W10x42	8	221	275	21,5	ET + 65	4,5 / 10	welded		42.10.03
W10x42	12	390	430	17	ET + 125	4,5 / 12	multifit	2652	42.10.04
W10x42	8	152	203	22	ET - 132	4,5 / 12	crown		42.10.05
W10x42	8	160	220	27/32	ET + 70	4,5 / 8	welded	1275	42.10.06
W10x42	8	170	220	27/32	ET + 110	4,5 / 8	welded		42.10.07
W10x42	8	221	275	22	ET + 105	4,5 / 12	welded		42.10.08
W10x42	8	221	275	22	ET + 130	4,5 / 12	welded	2652	42.10.09
DW16Lx42	8	221	275	24	ET -230	6,0 / 12	welded	?	42.16.01
DW16Lx42	8	221	275	24	ET +185	6,0 / 12	welded	?	42.16.02
DW16Lx42	8	221	275	24	ET +113	6,0 / 12	welded	?	42.16.03
DW18Lx42	10	281	335	27/32	ET 0	7,0 / 20	welded	8007	42.18.103
DW18Lx42	8	221	275	22	ET - 100	7,0 / 18	welded	8007	42.18.107
DW18Lx42	8	221	275	24	ET - 48	7,0 / 18	welded		42.18.111
DW18Lx42	10	281	335	24	ET + 8	7,0 / 18	welded		42.18.112
DW18Lx42	10	281	335	22	ET + 66	7,0 / 18	welded	8007	42.18.113
DW18Lx42	10	281	335	27/32	ET 0	7,0 / 20	welded	8007	42.18.114



Wheels Catalogue

Wheel Size	Nb of bolt holes	Central hole diameter	PCD	Bolt hole diameter	Offset	Material thickness	Type of wheel*	Load capacity at 40 km/h	Pronar part no
DW18Lx42	10	281	335	27/32	ET 0	7,0 / 20	welded	8007	42.18.115
DW20Bx42	10	281	335	27/32	ET + 70	7,0 / 18	welded	7109	42.20.01
DW20Bx42	10	281	335	24	ET 0	7,0 / 18	welded	7109	42.20.02
DW20Bx42	8	221	275	24	ET - 100	7,0 / 18	welded	7109	42.20.03
DW20Bx42	8	221	275	22	ET 0	7,0 / 18	welded	7109	42.20.04
DW20Bx42	10	431	485	24	ET + 50	7,0 / 18	welded	7109	42.20.05
DW20Bx42	8	221	275	24	ET - 70	7,0 / 18	welded	7109	42.20.06
DW20Bx42	8	221	275	22	ET + 35	7,0 / 20	welded	7109	42.20.07
DW20Bx42	8	221	275	22	ET - 100	7,0 / 18	welded	7109	42.20.08
DW20Bx42	10	281	335	27/32	ET 0	7,0 / 18	welded	7109	42.20.09
DW20Bx42	12	390	430	17	ET - 145	7,0 / 14	multifit		42.20.10
DW20Bx42	10	281	335	27/32	ET + 70	7,0 / 15	welded	5610	42.20.11
DW20Bx42	8	445	502	22	ET + 50	7,0 / 18	welded	7109	42.20.12
DW20Bx42	10	281	335	24	ET 0	7,0 / 18	welded	7109	42.20.102
DW20Bx42	8	221	275	24	ET - 100	7,0 / 18	welded	7109	42.20.103
DW20Bx42	8	221	275	22	ET 0	7,0 / 18	welded	7109	42.20.104
DW20Bx42	8	221	275	22	ET + 6	7,0 / 16	crown		42.20.105
DW20Bx42	10	281	335	27/32	ET 0	7,0 / 16	welded	7109	42.20.109
DW20Bx42	10	281	335	27/32	ET + 70	7,0 / 15	welded	5610	42.20.111
DW20Bx42	8	445	502	22	ET + 50	7,0 / 18	welded	7109	42.20.112
DW20Bx42	8	221	275	22	ET - 60	7,0 / 18	welded	7109	42.20.113
DW23Bx42	8	221	275	24	ET - 100	7,0 / 18	welded	8007	42.23.01
DW23Bx42	12	390	430	17	ET - 145	7,0 / 14	multifit		42.23.03
DW23Ax42	10	281	335	27/32	ET - 40	7,0 / 18	welded	8007	42.23.04



Wheels 44"

Wheel Size	Nb of bolt holes	Central hole diameter	PCD	Bolt hole diameter	Offset	Material thickness	Type of wheel*	Load capacity at 40 km/h	Pronar part no
W7x44	8	151	203	20	ET +100	4,5 / 10	crown	2652	44.07.01
W7x44	6	161	205	21,5/27	ET + 70	4,5 / 12	welded	2652	44.07.03
W7x44	8	221	275	21,5/27	ET + 70	4,5 / 12	welded	2652	44.07.04
W8x44	8	221	275	21,5/27	ET + 70	4,5 / 10	welded	2550 at 30 km/h	44.08.02
W8x44	8	160	220	27/34	ET + 65	4,5 / 10	welded		44.08.03
W8x44	8	221	275	21,5/27	ET + 70	5,0 / 12	crown		44.08.05
W8x44	10	281	480	12,5	ET + 100	4,5 / 10	welded	2499	44.08.09
W8x44	8	221	430	21,5/27	ET + 100	4,5 / 12	welded		44.08.11
W8x44	8	151	203	20	ET + 70	5,0 / 12	crown		44.08.12
W8x44	8	199,5	250	24/30	ET + 125	4,5 / 12	welded	1897	44.08.13
W8x44	8	152,4	203	20	ET + 70	5,0 / 12	crown		44.08.15
W8x44	12	390	430	17	ET + 115	5,0 / 12	multifit		44.08.16
W8x44	8	221	275	21,4/27	ET + 100	4,5 / 12	welded		44.08.17
W8x44	8	221	275	21,5/27	ET + 70	4,5 / 10	welded	2040	44.08.18
W8x44	8	221	275	21,5	ET + 70	4,5 / 12	welded		44.08.19
W8x44	8	161	205	21,5/27	ET + 60	4,5 / 12	welded		44.08.20
W8x44	blind	130	blind	blind	ET + 115	5,0 / 12	crown		44.08.22
W8x44	6	161	205	21,5/27	ET + 70	4,5 / 12	welded		44.08.23
W8x44	8	221	275	21,5/27	ET + 70	4,5 / 12	welded	2366,4	44.08.24
W8x44	8	221	275	21,5/27	ET + 150	5,0 / 12	crown		44.08.25
W8x44	8	221	275	21,5/27	ET + 45	4,5 / 12	welded		44.08.26
W8x44	8	221	275	21,5/27	ET 0	4,5 / 12	welded		44.08.27
W8x44	8	221	275	27/32	ET + 70	4,5 / 12	welded		44.08.28
W8x44	10	281	335	27/32	ET + 69	5,5 / 14	welded	3508,8	44.08.29
W8x44	8	199,5	250	24/30	ET + 95	4,5 / 12	welded	1897,2	44.08.30
W8x44	8	221	275	24/30	ET + 70	4,5 / 12	welded		44.08.31
W8x44	8	152	203	19	ET + 150	5,0 / 12	crown		44.08.32
W8x44	8	223	275	21,5/27	ET + 33	4,5 / 12	welded		44.08.33
W8x44	6	161	205	20	ET + 70	4,5 / 12	welded		44.08.34
W8x44	8	221	275	21,5/27	ET + 130	4,5 / 12	welded	1897,2	44.08.35
W8x44	8	152,4	203,2	19/24	ET + 150	5,0 / 12	crown		44.08.36
W8x44	8	199,5	250	24/30	ET + 33	4,5 / 12	welded		44.08.37
W8x44	8	221	275	21,5/27	ET + 125	5,0 / 12	crown		44.08.38
W8x44	8	221	275	27/32	ET + 50	4,5 / 12	welded	2366,4	44.08.39
W8x44	6	161	205	21,5/27	ET + 130	4,5 / 12	welded	2000	44.08.40
W8x44	8	221	275	21,5/27	ET + 75	4,5 / 12	welded		44.08.41
W8x44	6	161	205	21,5/27	ET +95	4,5 / 12	welded	1897	44.08.43



Wheels 46"

Wheel Size	Nb of bolt holes	Central hole diameter	PCD	Bolt hole diameter	Offset	Material thickness	Type of wheel*	Load capacity at 40 km/h	Pronar part no
W10x46	8	221	275	21,5/27	ET - 55	5,0 / 10	welded		46.10.01
W10x46	8	221	275	21,5/27	ET +70	5,0 / 10	welded		46.10.02
W10x46	8	152,4	203,2	22	ET + 160	5,0 / 12	crown	2652	46.10.03
W10x46	8	221	275	21,5/27	ET + 160	5,0 / 12	crown	2750	46.10.04
W10x46	8	221	275	21,5/27	ET - 50	5,0 / 12	welded		46.10.05
W10x46	12	390	430	17	ET + 160	5,0 / 12	crown	2652	46.10.06
W10x46	8	221	275	21,5	ET + 70	5,0 / 12	welded	2652	46.10.07
W10x46	8	140	203,2	18	ET - 15	5,0 / 14	welded		46.10.08
W10x46	8	221	275	21,5/27	ET - 100	5,0 / 12	crown	2652	46.10.09
W10x46	8	221	275	21,5/27	ET - 55	5,0 / 55	crown	2652	46.10.10
W10x46	8	221	275	21,5/27	ET + 70	5,0 / 12	welded	2652	46.10.11
W10x46	8	221	275	21,5	ET - 70	5,0 / 14	welded		46.10.12
W10x46	8	221	275	22	ET + 40	5,0 / 12	welded	2652	46.10.13
W10x46	8	152	203,2	19/24	ET + 160	5,0 / 12	welded	2652	46.10.14
W10x46	8	221	275	27/32	ET + 50	5,0 / 12	welded	2750	46.10.15
W10x46	8	221	275	27/32	ET +50	5,0 / 16	welded	2750	46.10.18
W12x46	8	152,4	203,2	22	ET + 160	5,0 / 12	crown	2652	46.12.01
W12x46	8	221	275	24	ET - 65	5,0 / 12	welded		46.10.02
W12x46	8	221	275	21,5/27	ET + 70	5,0 / 12	welded	2652	46.10.03
W12x46	12	390	430	17	ET + 160	5,0 / 12	multifit	2652	46.10.04



Wheels 48"

Wheel Size	Nb of bolt holes	Central hole diameter	PCD	Bolt hole diameter	Offset	Material thickness	Type of wheel*	Load capacity at 40 km/h	Pronar part no
W8x48	8	221	275	21,5/27	ET - 55	5,0 / 10	welded	2366	48.08.01
W8x48	8	221	275	21,5	ET + 70	5,0 / 12	welded	2366	48.08.01
W8x48	8	245	275	21,5/27	ET + 160	5,0 / 12	crown	2652	48.08.04
W8x48	8	221	275	21,5/27	ET + 160	5,0 / 12	crown	2652	48.08.05
W8x48	8	152	203,2	19/24	ET + 160	5,0 / 12	crown	2652	48.08.06
W8x48	8	221	275	21,5/27	ET + 70	5,0 / 12	welded	2805	48.08.07
W8x48	12	390	430	17	ET + 125	5,0 / 12	multifit		48.08.08
W8x48	?	130			ET +125	5,0 / 12	crown		48.08.09
W8x48	8	221	275	27/32	ET + 70	5,0 / 12	welded	2805	48.08.10
W8x48	10	281	335	27/32	ET + 70	5,0 / 12	welded	2805	48.08.11
W8x48	8	221	275	21,5/27	ET - 100	5,5 / 12	crown	2917	48.08.12
W8x48	6	161	205	21,5/27	ET - 40	5,0 / 12	crown	2652	48.08.13
W8x48	8	153	203,2	22	ET - 36	5,0 / 15	welded		48.08.14
W8x48	8	199,5	250	24/30	ET + 65	5,0 / 12	welded	2805	48.08.15
W8x48	10	281	335	24,5	ET + 15	5,0 / 12	welded		48.08.16
W8x48	8	221	275	27/32	ET + 70	??? / 12	welded		48.08.17
W8x48	6	161	205	21,5/27	ET + 70	5,0 / 12	welded		48.08.18
W8x48	10	281	335	24,5	ET + 76,5	5,0 / 12	welded		48.08.19
W8x48	8	221	275	21,5	ET + 105	5,0 / 12	welded	2805	48.08.20
W8x48	8	221	275	21,5/27	ET + 125	5,0 / 12	crown	2652	48.08.21
W10x48	10	281	335	27/32	ET + 100	5,0 / 12	welded	??2366	48.10.02
W10x48	8	221	275	27/32	ET - 60	5,0 / 15	welded	2805	48.10.03
W10x48	6	390	430	17	ET + 65	5,0 / 12	multifit	2652	48.10.04
W10x48	8	152	203,2	19/24	ET + 160	5,0 / 12	crown	2652	48.10.05
W10x48	8	221	275	21,5/27	ET 0	5,0 / 12	welded	2805	48.10.06
W10x48	10	281	335	27/32	ET + 100	5,0 / 12	welded	2805	48.10.07
W10x48	8	199,5	250	24/30	ET + 65	5,0 / 12	welded	2805	48.10.08
W10x48	10	281	335	27/32	ET + 100	5,0 / 12	welded	2805	48.10.09
W10x48	8	221	275	21,5	ET - 70	5,0 / 15	welded	2805	48.10.10
W12x48	8	221	275	21,5/27	ET + 55	5,0 / 15	welded	3160	48.12.02
W12x48	8	221	275	21,5/27	ET + 100	5,0 / 12	crown	2652	48.12.03
W12x48	12	390	430	17	ET + 65	5,0 / 12	multifit	2652	48.12.04
W12x48	10	281	335	27/32	ET - 70	5,0 / 15	welded		48.12.05
W12x48	8	221	275	21,5/27	ET + 70	5,0 / 12	crown	2652	48.12.06
W12x48	8	221	275	21,5/27	ET 0	5,0 / 15	welded	3160	48.12.07
W12x48	8	221	275	21,5	ET - 82	6,0 / 12	welded		48.12.09



Wheels 54"

Wheel Size	Nb of bolt holes	Central hole diameter	PCD	Bolt hole diameter	Offset	Material thickness	Type of wheel*	Load capacity at 40 km/h	Pronar part no
W10x54	10	281	335	24	ET + 15	6,0 / 18	welded		54.10.01
W10x54	10	281	335	27/32	ET + 6	6,0 / 18	welded		54.10.02
W12x54	10	281	335	22	ET + 45	6,0 / 18	welded		54.12.01